

Free Questions for A10-System-Administration by certscare

Shared by Estrada on 03-04-2023

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

You are planning an Active-Active-Active VRRP-A three-device deployment that, upon failover of any device, distributes the load from a single device to both standby devices simultaneously. How many VRIDs are required?

tions:	
2	
VRID Default is enough	
6	
5	
3	
1	
swer:	

Question 2

Question Type: MultipleChoice

Which three items does aXAPI require to configure an ACOS object (such as an SLB object)? (Choose three.)

Options:

A- Endpoint with parameters

B- Authorization signature

- C- Device's VIP URL
- D- Device's serial number
- E- Device's management/data IP
- F- Encrypted connection to device

Answer:		
B, E, F		

Question 3

Which statement is true about the requirements for ACOS devices that are part of an aVCS cluster?

Options:

- A- Any Thunder series devices can be clustered together in an aVCS set
- B- Devices must be the same model but can have different optional hardware cards
- C- Devices must be the same model and have the same optional hardware cards

Answer:

С

Question 4

Question Type: MultipleChoice

Which commands display the ACOS device serial number? (Choose two.)

Options:

A- show system			
B- show hardware			
C- show environment			
D- show serial			
E- show version			

Answer:

B, E

Question 5

Question Type: MultipleChoice

Which statement correctly describes the result of the following commands?

ACOS(config)#logging host 192.168.216.45

ACOs(config)#end

ACOS#active-partition p1

Currently active partition: p1

ACOS[p1](config)#logging host 2.2.2.2

ACOS[p1](config)#logging host partition shared

Options:

A- System logs generated from partition "p1" will be sent to logging server "2.2.2.2", and only warning severity log messages are sent to the shared logging server's "192.168.216.45".

B- System logs generated from partition "p1" will be sent to logging server "2.2.2.2", as well as to the shared logging server's "192.168.216.45".

C- System logs generated from partition "p1" will be sent to logging server "2.2.2.2".

D- System logs generated from partition "p1" will be sent to the shared logging server's "192.168.216.45".

Answer:

В

Question 6

Question Type: MultipleChoice

Describe VRRP-A (high availability) and aVCS interoperability.

Options:

- A- Enabling VRRP-A requires that aVCS is operational
- B- Enabling aVCS require VRRP-A is operational
- C- VRRP-A and aVCS operate independently of each other
- D- VRRP-A and aVCS must function simultaneously

Answer:

D

Question 7

Question Type: MultipleChoice

The "show admin" displays the following output. Select the correct statements concerning admins on this device. (Choose two.)

UserName	Status	Privilege	Access	Partition
admin	Enabled	R/W	C/W/A	
Fred	Enabled	P.En	W/A	acme
Sally	Enabled	P.RW	C	acme

Options:

- A- Sally is a read write administrator on the Acme partition.
- **B-** Fred is a read write administrator on the Acme partition.
- C- Fred can only log in with the web or api client.
- **D-** User admin has no access to the acme partition.
- E- Fred can run aXAPI scripts against the acme partition using his login information.
- **F-** Sally can only log in with the web client.
- G- Sally is a read write administrator on the shared partition.

Answe	Answer:					
A, C						

Question 8

What do we know about the state of the system from the CLI prompt? (Choose two.)

A1-vMaster[1/1][Helium2]#

Options:

- A- There is only 1 member in this A10 Virtual Chassis.
- B- There are at least 2 private partitions configured.
- C- aVCS has been configured, and this host is part of aVCS set 1.
- D- aVCS has been configured, and this host is part of aVCS set 1/1.
- E- Application Delivery Partitions have been configured.

Answer:

D, E

Question 9

Question Type: MultipleChoice

Given the following "show vcs summary" output, which statements are true about the virtual chassis set? (Choose three.)

VCS Chassis:	
VCS Enabled:	YES
Chassis ID:	1
Floating IP:	1.0.0.10
Mask:	255.255.255.0
Multicast IP:	224.0.0.210
Multicast Port:	41217
Version:	4.1.0-P1

Members (* means local device):

_	ID	State	Priority	IP:Port	Location
	1	vMaster	0	1.0.0.1:41216	Remote
	2 3	Unknown vBlade(*)	0 0	3.0.0.3:41216 1.0.0.3:41216	Remote Local

Total: 3

Options:

- A- Three devices were configured as part of the virtual chassis.
- B- The command was run from the aVCS vMaster.
- C- The aVCS vMaster of the group can always be accessed at IP Address 1.0.0.1.
- D- The aVCS vMaster of the set can always be accessed at IP Address 224.0.0.210.
- E- The command was run from device 3 of the set.

F- This is aVCS set-id 1.

Answer:

A, E, F

To Get Premium Files for A10-System-Administration Visit

https://www.p2pexams.com/products/a10-system-administration

For More Free Questions Visit

https://www.p2pexams.com/a10-networks/pdf/a10-system-administration

