



Free Questions for 010-151 by actualtestdumps

Shared by Boyd on 15-04-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

When activating the firmware via UCSM which two firmware versions must be activated at the same time?

Options:

- A- UCS Manager and System
- B- UCS Manger and Kernel
- C- CIMC and Kernel
- D- System and Kernel

Answer:

D

Explanation:

https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/ucs-manager/GUI-User-Guides/Firmware-Mgmt/3-1/b_UCSM_GUI_Firmware_Management_Guide_3_1/b_UCSM_GUI_Firmware_Management_Guide_3_1_chapter_011.html

Question 2

Question Type: MultipleChoice

Which Cisco UCS Virtual Interface Card Series is designed exclusively for the M5 generation?

Options:

- A- M81KR VIC
- B- VIC 1400 Series
- C- VIC 1300 Series
- D- VIC 1200 Series

Answer:

B

Explanation:

Question 3

Question Type: MultipleChoice

What are two common steps to troubleshooting a rack server with unrecognized or memory errors? (Choose two.)

Options:

- A- Ensure DIMMs are installed in correct slots
- B- Check CPU sockets for bent pins
- C- Check that the AC power cord is OK
- D- Reseat DIMMs
- E- Check the front I/O cable connection to the motherboard

Answer:

A, D

Explanation:

https://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/c/ts/guide/b_C-Series_Troubleshooting_Guide.pdf page 11

Question 4

Question Type: MultipleChoice

Which two transceivers can support 100 Gigabit Ethernet? (Choose two.)

Options:

- A- SFP+
- B- SFP28
- C- QSFP+
- D- QSFP28
- E- SFP-DD

Answer:

C, D

Question 5

Question Type: MultipleChoice

What enables NVM Express host software to communicate with nonvolatile memory?

Options:

A- SATA

B- SAS

C- PCIe

D- SCSI

Answer:

C

Explanation:

https://nvmexpress.org/wp-content/uploads/NVM-Express-1_4-2019.06.10-Ratified.pdf page 6

Question 6

Question Type: MultipleChoice

Which statement about the Cisco Nexus 3408-S switch is true?

Options:

- A- It is offered in a three-rack-unit (3-RU) form factor.
- B- It supports 200G or 400G line card expansion modules.
- C- It has dual-redundant power supplies.
- D- It is 4-slot chassis with 400G line card expansion modules.

Answer:

C

Explanation:

<https://www.cisco.com/c/en/us/products/collateral/switches/nexus-3000-series-switches/datasheet-c78-741562.html>

To Get Premium Files for 010-151 Visit

<https://www.p2pexams.com/products/010-151>

For More Free Questions Visit

<https://www.p2pexams.com/cisco/pdf/010-151>

