



**Free Questions for 4A0-N02 by actualtestdumps**

**Shared by Mathews on 12-12-2023**

**For More Free Questions and Preparation Resources**

**Check the Links on Last Page**

## Question 1

---

**Question Type:** MultipleChoice

---

Which of the following statements is NOT correct about the communication between two NSGs in different branch offices?

### Options:

---

- A- These two NSGs exchange OpenFlow-TLS with their controller to establish the tunnel for overlay traffic.
- B- These two NSGs must be managed by the same VSD/VSD HA cluster.
- C- The overlay tunnels established between the NSGs must be VXLAN encapsulation.
- D- The overlay tunnels are established during bootstrapping.

### Answer:

---

C

## Question 2

---

**Question Type:** MultipleChoice

---

Which of the following is NOT defined in the NSG infrastructure G/W profile?

**Options:**

---

- A- Identify the VSD proxy
- B- Enable two-factor installer authentication
- C- Port speed and mode
- D- NTP, stats, syslog server

**Answer:**

---

B

## Question 3

---

**Question Type: MultipleChoice**

---

Which of the following is TRUE about NSG dual uplink?

**Options:**

---

- A- It only provides redundancy for data traffic.
- B- Traffic is load balanced between primary and secondary links.
- C- One primary VSC is selected on each uplink.
- D- Both uplinks can be connected to the same network or to two different networks.

**Answer:**

---

B

## Question 4

---

**Question Type: MultipleChoice**

---

Which of the following statements about the NSG vports is TRUE?

**Options:**

---

- A- The NSG responds to DHCP requests on a host vport by default.

- B-** A host MAC address is dynamically learned on a host vport.
- C-** A host vport allows multiple devices to be connected through a switch.
- D-** IP address assignment is handled by the NSG for a host on a host vport.

**Answer:**

---

D

## Question 5

---

**Question Type:** MultipleChoice

---

Which one of the following statements is correct regarding bridge vPorts in the VNS solution?

**Options:**

---

- A-** A DHCP pool can be configured on a subnet connected to an NSG bridge vPort, the NSG then becomes the DHCP server.
- B-** VSD is in charge of the IP address assignment to the devices behind the NSG vPort.
- C-** There must be more than one device behind the bridge vPort.
- D-** The static IP to MAC mapping configuration is not on the bridge vPort.

**Answer:**

---

A

## Question 6

---

**Question Type:** MultipleChoice

---

Which of the following is FALSE regarding VNS bootstrapping?

**Options:**

---

- A-** The bootstrapping configuration templates on VSD ensures NSG configuration conformance.
- B-** NSG is ready for dispatch without prior configuration.
- C-** It solves the problem of site CPE activation without having to send a skilled technician on site.
- D-** NSG exchanges the plain text proprietary bootstrap protocol with VSD.

**Answer:**

---

D

## Question 7

---

**Question Type:** MultipleChoice

---

What type of NAT is used so that any external host can send to iAddr: iPort by sending traffic to eAddr: ePort? (i=internal, e=external)

### Options:

---

- A- Full-cone NAT
- B- Address-restricted NAT
- C- Port-restricted NAT
- D- Symmetric NAT

### Answer:

---

A

**To Get Premium Files for 4A0-N02 Visit**

<https://www.p2pexams.com/products/4a0-n02>

**For More Free Questions Visit**

<https://www.p2pexams.com/nokia/pdf/4a0-n02>

