Question 1

Which configuration step is necessary when automatic updating is required of iOS apps provisioned through Systems Manager that are found in the App Store?

Options:

A- No configuration step is necessary; automatic updating is the default behavior.

B- Configure automatic updating of iOS devices in the Meraki installed profile.

C- Create a security policy that enables automatic updates.

D- Create a profile with automatic update enabled and apply it to iOS devices.

Answer:

C

Question 2

Which information is used to calculate whether a WAN link has high usage?

Options:

A- data under Security & SD WAN > Appliance Status > Uplink > Live Data

B- total historical throughput of an uplink

C- total number of devices that are actively passing traffic

D- value under Security & SD WAN > SD WAN & Traffic Shaping > Uplink Configuration

Answer:

D

Question 3

Question Type: MultipleChoice

Which VLAN is used to source pings across the site-to-site VPN when using the MX Live tools?

Options:

A- highest VLAN ID that is configured and set to NO to use VPN

B- lowest VLAN ID that is configured and set to YES to use VPN

C- highest VLAN ID that is configured and set to YES to use VPN

D- lowest VLAN ID configured and set to NO to use VPN

Answer:

C

Explanation:

Using_the_Ping_Live_Tool

Question 4

Question Type: **MultipleChoice**

Which information do the MXs in a High Availability pair share?

A- spanning-tree state

B- time synchronization state

C- DHCP association database

D- stateful firewall database

Answer:

A

Question 5

Question Type: **MultipleChoice**

Which Cisco Meraki product must be deployed in addition to Systems Manager so that Systems Manager Sentry enrollment can be used?

Options:

A- MS Switch

B- Meraki Insight

C- MR Access Point

D- MV Smart Camera

Answer:

C

Question 6

Question Type: **MultipleChoice**

A Cisco Meraki MV camera is monitoring an office and its field of vision currently captures work desks and employee computer screens. However, recording employee computer screens is prohibited by local regulation.

Which feature in Dashboard can be used to preserve the current position of the camera while also meeting regulation requirements?

Options:

A- zone exclusion

B- privacy window

C- area or interest

D- sensor crop

E- restricted mode

Answer:

E