



Free Questions for [DEA-5TT2](#) by [actualtestdumps](#)

Shared by [Gaines](#) on [12-12-2023](#)

For More Free Questions and Preparation Resources

[Check the Links on Last Page](#)

Question 1

Question Type: MultipleChoice

In IPv4, what is the proper conversion from binary to decimal for the number 11010010?

Options:

A- 202

B- 210

C- 226

D- 258

Answer:

B

Question 2

Question Type: MultipleChoice

A network administrator has a Dell EMC switch that has been configured with several VLANs. Each VLAN switch virtual interface (SVI) has an IP address assigned to it with each of them on different subnets. In addition, routing has been enabled on the switch.

Which action occurs when the switch receives a packet on one of its SVIs but the destination IP address of the packet does not match the IP address of that SVI?

Options:

- A-** Switch checks its routing table and forwards the packet accordingly.
- B-** Switch duplicates the packet and sends it to all interfaces.
- C-** Switch replies back to the source with an ICMP Reject packet.
- D-** Switch drops the packet.

Answer:

A

Question 3

Question Type: MultipleChoice

Which Dell EMC Networking M-Series 10 GbE switch model supports a VLT?

Options:

A- MXL

B- M6220 C. M6348

D- M8024-K

Answer:

A

Question 4

Question Type: MultipleChoice

What is the default route preference value for a Border Gateway Protocol (BGP) internal route?

Options:

- A- 40
- B- 110
- C- 200
- D- 253

Answer:

C

Question 5

Question Type: MultipleChoice

What is the bandwidth of an RPM for a C9010 Network Director?

Options:

- A- 200 Mbps
- B- 2.56 Mbps
- C- 1.52 Tbps

D- 2.56 Tbps

Answer:

D

Question 6

Question Type: MultipleChoice

Which IEEE standard defines the Data Link Layer, Discovery protocol?

Options:

A- 802.1AB B. 802.1AX C. 802.1D D. 802.1W

Answer:

A

Question 7

Question Type: MultipleChoice

Which fields are mandatory TLVs in a LLDP PDU frame?

Options:

- A- System Capabilities and Management Address
- B- Chassis ID, Port ID, and Time-to-Live
- C- IP Address, Default Gateway, and DNS
- D- Port Description, System Name, and System Description

Answer:

B

Question 8

Question Type: MultipleChoice

A VLAN has been configured to have an IPv6 address and a stateless address autoconfiguration for clients. Which IPv6 address prefix will the default gateway have on a client?

Options:

A- fd01::/64

B- fe08::/64

C- fe80::/64

D- ff02::/8

Answer:

C

Question 9

Question Type: MultipleChoice

Which flags are used in the TCP header to initiate and end TCP connections or sessions?

Options:

A- Initiate = Acknowledge (ACK) End = Synchronize (SYN)

B- Initiate = Acknowledge (ACK) End = Finish (FIN)

C- Initiate = Synchronize (SYN) End = Finish (FIN)

D- Initiate = Finish (FIN)
End = Synchronize (SYN)

Answer:

C

Question 10

Question Type: MultipleChoice

A network administrator wants to use a subnet that will only have two host addresses. Which subnet mask meets this requirement?

Options:

A- 255.255.255.248

B- 255.255.255.252

C- 255.255.255.254

D- 255.255.255.256

Answer:

B

To Get Premium Files for DEA-5TT2 Visit

<https://www.p2pexams.com/products/dea-5tt2>

For More Free Questions Visit

<https://www.p2pexams.com/dell-emc/pdf/dea-5tt2>

