



**Free Questions for DES-4122 by actualtestdumps**

**Shared by Chambers on 29-01-2024**

**For More Free Questions and Preparation Resources**

**Check the Links on Last Page**

# Question 1

---

## Question Type: MultipleChoice

---

A company that has very specific firmware requirements has acquired Dell EMC PowerEdge servers. Any replaced parts of the type must match the original parts identically. The procedure must be as simple as possible with minimal risk.

What action should a technician take to help accomplish this goal?

### Options:

---

- A- Configure servers to access the remote firmware repository
- B- Enable the Match Firmware of Replaced Part setting in the system BIOS
- C- Install and configure a repository manager
- D- Enable the Collect System Inventory On Restart (CSIOR) attribute

### Answer:

---

B

# Question 2

---

**Question Type: MultipleChoice**

---

What is a characteristic of out-of-band management?

**Options:**

---

- A- Dedicated device
- B- Agent based
- C- Less secure
- D- Dependent upon OS

**Answer:**

---

A

## Question 3

---

**Question Type: MultipleChoice**

---

A Dell EMC PowerEdge 14G server uses Intel OPTANE DC Persistent Memory in App Direct mode. What is the minimum size DIMM supported for this type of memory?

**Options:**

---

**A-** 64 GB

**B-** 128 GB

**C-** 256 GB

**D-** 512 GB

**Answer:**

---

B

## Question 4

---

**Question Type:** MultipleChoice

---

Which processor configuration is used by the Dell EMC PowerEdge R740 server?

**Options:**

---

**A-** 4 socket AMD

**B-** 2 socket AMD

**C-** 2 socket Intel

**D-** 4 socket Intel

**Answer:**

---

C

## Question 5

---

**Question Type:** MultipleChoice

---

A technician working with a Dell EMC PowerEdge 1 take corrective action?

**Options:**

---

**A-** Check the System Event Log

Check PSU LED

Reseat the PSU

**B-** Check the System Event Log

Check PSU LED

Do a virtual reset of the iDRAC

**C-** Check the LCC Log

Check PSU LED

Reseat the CPU

**D-** Check the LCC Log

Check PSU LED

Reseat the PSU

**Answer:**

---

B

## Question 6

---

**Question Type:** MultipleChoice

---

What are key values related to systems management when deploying OpenManage Enterprise with Dell EMC PowerEdge servers?

**Options:**

---

**A-** Automate

Basic Hardware Element Management  
Agent-free Management  
Simple and effective

**B-** Simplify

Basic Hardware Element Management  
Agent-free Management  
Fee-based license

**C-** Simplify

Fee-based license Agent-free Management Secure

**D-** Simplify

Unify  
Automate  
Secure

**Answer:**

---

D

## Question 7

---

**Question Type:** MultipleChoice

---

After completing a disk rebuild operation, a technician needs to configure the system so that the rebuild process happens faster the expense of slowing users down.

Which setting should be changed?

**Options:**

---

- A- Rebuild Rate in the BIOS settings
- B- System Profile to Performance in the BIOS settings
- C- System Profile to Performance in the iDRAC GUI
- D- Rebuild Rate in the iDRAC GUI

**Answer:**

---

D

## Question 8

---

**Question Type: MultipleChoice**

---

What is the drive characteristic of a BOSS M.2 drive in a Dell EMC PowerEdge server?



**Options:**

---

- A- Single-level cell
- B- Read Intensive
- C- Quad-level cell
- D- Write Intensive

**Answer:**

---

B

## Question 9

---

**Question Type:** MultipleChoice

---

How can a technician know whether IDRAC9 System Lockdown mode is enabled?

**Options:**

---

- A- Lockdown activation message in red box in the iDRAC web GUI Access to LCC is disabled when the server boots
- B- Lockdown activation message in red box in the iDRAC web GUI Access to LCC requires a password when the server boots
- C- Lockdown activation message in yellow box in the iDRAC web GUI Access to LCC is disabled when the server boots
- D- Lockdown activation message in yellow box in the iDRAC web GUI Access to LCC requires a password when the server boots

**Answer:**

---

C

## Question 10

---

**Question Type:** MultipleChoice

---

You must configure a BOSS card with 2 x 120GB drives for a Dell EMC PowerEdge server. What is the only supported mode?

**Options:**

---

- A- RAID 0
- B- RAID 5
- C- RAID 1

**D-** Non-RAID Mirroring

**Answer:**

---

C

## Question 11

---

**Question Type:** MultipleChoice

---

What is required for iDRAC Direct 2.0 to connect with IDRAC9 interfaces such as RACADM and WSMAN?

**Options:**

---

**A-** Wi-Fi connection

**B-** NFC connection

**C-** Ethernet cable

**D-** Micro-AB USB

**Answer:**

---

D

**To Get Premium Files for DES-4122 Visit**

**<https://www.p2pexams.com/products/des-4122>**

**For More Free Questions Visit**

**<https://www.p2pexams.com/dell-emc/pdf/des-4122>**

