Question 1

What information is required to configure an iSCSI initiator?

Options:

A- Alias, Zone, Zone Config name

B- Target IP Address, subnet, gateway

C- VLAN tag, port speed, Multicast control setting

D- MAC address, VLAN broadcast address

Answer:

B

Question 2

A customer has a volume that was created with the wrong datapage size. What is the simplest and least disruptive method to change this volume's page size?

Options:

A- Copy the volume, then mount the new volume

B- Mirror the volume, then mount the mirrored volume

C- Mirror the volume, then migrate to mirror

D- Migrate the volume, then delete the source volume

Answer:

A

Question 3

Question Type: MultipleChoice

When a SC is in a failover state what will occur in the surviving controller?

Options:

A- Data and metadata will be available

B- The read cache that is associated with the failed controller will be created

C- The deduplication dictionary from the failed controller will load

D- Deduplication will run

Answer:

B

Question 4

Question Type: **MultipleChoice**

For what is Application Protection Manager used?

Options:

A- SQL databases

B- Hyper-V machine resources

C- VMware virtual machines

D- Oracle databases

Answer:

D

Explanation:

https://i.dell.com/sites/csdocuments/Shared-Content_data-Sheets_Documents/en/ Dell_Storage_SC_Series_Management_Suite.pdf

Question 5

Question Type: MultipleChoice

Which Live Volume Requirement or Best Practice is necessary for disaster recovery?

Options:

A- Primary and Secondary Storage Centers configured in Unisphere for SC Series

B- QoS defined on the Primary system

C- Licensed Live Volume on secondary Storage Center

D- Fibre Channel or iSCSI with a round trip latency of less than 10 ms

Answer:

D

Explanation:

https://www.dell.com/storagehelp/dellstorageclient/2016R3.10/en-us/GUID-B24ADB33-10CD- 4AE1-8A2E-4489C19983E1.html

Question 6

Question Type: **MultipleChoice**

You are trying to discover a brand new SCv3020 but the process if failing. DHCP is not available. What is the best solution for this issue?

A- Enable MTU and flowcontrol on the switch

B- Configure IPv4 address on the system running the DSM Client on the target subnet

C- Set BMC IPs

D- Configure IPv4 on DSM Client machine and enable IPv6 addressing

Answer:

B

Question 7

Question Type: MultipleChoice

When creating a new server in Unisphere Central for SC Series, what should show up automatically if it has been properly configured on the host?

Options:

A- Name

B- HBA

C- OS

D- MPIO

Answer:

A

Explanation:

https://www.dellemc.com/en-us/collaterals/unauth/white-papers/products/storage-1/h13827- unisphere-central-v4-wp.pdf

Question 8

Question Type: **MultipleChoice**

What is the HDD size that enforces dual redundancy?

Options:

A- 2 TB and higher

B- Up to 3 TB

C- 4 TB and higher

D- 3 TB and higher

Answer:

A

Explanation:

https://www.dell.com/storagehelp/dellstorageclient/2016R3.10/en-us/GUID-3941B3A0-0A0C-47D6- 9BCC-55E0F9310868.html

Question 9

Question Type: **MultipleChoice**

You have connected a 12 GB expansion enclosure using Mini-SAS HD cables. When powered on, some of the cable do not show a link. Why?

Options:

A- Inserted upside down

B- Incorrect cable voltage

C- Non powered cable

D- Inserted sideways

Answer:

B

Question 10

Question Type: MultipleChoice

You are required to install twenty-four (24) 3.5'' 12 Gb disks on a deployed system. Which disk enclosure would support this?

Options:

A- SC420

B- SC400

C- SCv320

D- SC460

Answer:

A

Explanation:

https://www.dell.com/ai/business/p/storage-sc7020/pd