



**Free Questions for H12-721 by actualtestdumps**

**Shared by Weeks on 20-10-2022**

**For More Free Questions and Preparation Resources**

**Check the Links on Last Page**

## Question 1

---

**Question Type:** MultipleChoice

---

The network administrator of a company discards traffic that exceeds the throughput of the device. The USG discards the traffic that exceeds the device throughput. The USG discards the traffic that exceeds the device throughput. The following command can achieve this function?

**Options:**

---

- A- utm bypass enable
- B- undo utm bypass enable
- C- ips bypass enable
- D- undo ips bypass enable

**Answer:**

---

B

## Question 2

---

**Question Type: MultipleChoice**

---

Which of the following is not a message sent during ip-link detection?

**Options:**

---

- A- ARP packet
- B- IGMP message
- C- ICMP message
- D- Hello message

**Answer:**

---

B, D

**Explanation:**

---

Answer : BD Note: ip-link will periodically improve icmp and arp detection messages to

**Question 3**

---

**Question Type: MultipleChoice**

---

On the web configuration page, choose System --> High Reliability --> Hot Standby and click Check for HRP Configuration Consistency. Button. The following window pops up. Which of the following configurations can solve the problem (assuming the heartbeat is added to the DMZ area)?



**Options:**

---

- A- firewall packet-filter default permit interzone trust local
- B- firewall packet-filter default permit interzone trust dmz
- C- firewall packet-filter default permit interzone untrust dmz
- D- firewall packet-filter default permit interzone local

**Answer:**

---

D

## Question 4

---

**Question Type:** MultipleChoice

---

Which is incorrect about IPSec NAT Traversal?

### Options:

---

- A- Both A AH and ESP support NAT traversal
- B- IPSec NAT traversal does not support IKE main mode (pre-shared mode)
- C- IPSec ESP packets are encapsulated through NAT using UDP packets.
- D- All IKE messages exchanged with the initiator use 4500 port communication

### Answer:

---

A

## Question 5

---

**Question Type: MultipleChoice**

---

The preemption function of the VGMP management group is enabled by default, and the delay time is 60s.

**Options:**

---

**A-** TRUE

**B-** FALSE

**Answer:**

---

B

**Explanation:**

---

Note: The preemption function of the VGMP management group is enabled by default. The delay time is 30s, the priority of the master is 65001, and the priority of the slave is 65000.

## **Question 6**

---

**Question Type: MultipleChoice**

---

Regarding VRRP messages, what are the following statements correct?

**Options:**

---

- A- VRRP uses TCP packets.
- B- VRRP uses UDP packets.
- C- The destination address of the C VRRP packet is 224.0.0.18.
- D- The TTL value of the D VRRP packet is 255.

**Answer:**

---

C, D

## Question 7

---

**Question Type:** MultipleChoice

---

In the client-initial mode, the L2TP dialup fails. From the debug information below, it can be seen that the most likely cause is the dialup failure.

```
*0.12783270 E200E-B PPP/7/debug2:  
PPP Error:  
Virtual-Template1:0 CHAP : Server auth failed No. 1 !  
*0.12783410 E200E-B PPP/7/debug2:
```

### Options:

---

- A- username and password are inconsistent with aaa configuration
- B- Ins name configuration error
- C- tunnel password is not configured
- D- is not enabled l2tp

### Answer:

---

A



**To Get Premium Files for H12-721 Visit**

**<https://www.p2pexams.com/products/h12-721>**

**For More Free Questions Visit**

**<https://www.p2pexams.com/huawei/pdf/h12-721>**

