



Free Questions for H12-711_V3.0 by actualtestdumps

Shared by Mcclure on 12-12-2023

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: FillInTheBlank

Multiple different () cannot be added to the same interface on the firewall at the same time (fill in the blank)

Answer:

Question 2

Question Type: FillInTheBlank

In USG6000E, the initial priority of VGMP is () (fill in the blank)

Answer:

Question 3

Question Type: FillInTheBlank

() is an "indirect intrusion attack. This attack mode is to virtually place a computer controlled by an intruder between two communicating computers in a network connection through various technical means. (fill in the blank)

Answer:

Question 4

Question Type: FillInTheBlank

The backup methods of dual-system hot backup include automatic backup (), manual batch backup, and automatic synchronization of the configuration of the active and standby FW after the device restarts. (fill in the blank)

Answer:

Question 5

Question Type: FillInTheBlank

After an engineer completes the source NAT configuration, the internal network still cannot access the external network. The engineer wants to query the detailed information of the address translation by using the command to query the session table, so the engineer directly uses the () command in the user view to query the address translation. information. (fill in the blank)

Answer:

Question 6

Question Type: FillInTheBlank

After the firewall detects an intrusion, the administrator can view the intrusion log information in the firewall business log or () log. (fill in the blank)

Answer:

Question 7

Question Type: FillInTheBlank

Configure authentication options If you use web push page authentication, you also need to configure a corresponding security policy to allow the data flow with the default port number () to reach the firewall itself. (fill in the blank)

Answer:

Question 8

Question Type: FillInTheBlank

In the VGMP group state, if the device's own VGMP group priority is equal to the peer device's VGMP group priority, the device's VGMP group state is (). (answer in letters) (fill in the blank)

Answer:

Question 9

Question Type: FillInTheBlank

If the company network administrator needs to check the status of the heartbeat interface after configuring the company's dual-system hot backup, the command he needs to type is () The system view has been entered by default) (fill in the blank)

Answer:

To Get Premium Files for H12-711_V3.0 Visit

https://www.p2pexams.com/products/h12-711_v3.0

For More Free Questions Visit

<https://www.p2pexams.com/huawei/pdf/h12-711-v3.0>

