



Arista ACE-A1.2 Mock Exam

Shared by Williamson on 17-06-2026

For More Free Questions and Preparation Resources

Check the Links on Last Page



Question 1

Question Type: MultipleChoice

How many Arista switches may be a part of a single MLAG domain?

Options:

- A- 2
- B- 4
- C- 8
- D- 16



Answer:

A

Question 2

Question Type: MultipleChoice

Which password setting controls the Privilege Exec mode on an Arista switch?

Options:

- A- boot password
- B- enable secret
- C- management secret
- D- enable



Answer:

B

Question 3

Question Type: MultipleChoice

Which of the following statuses will be displayed when VMTracer has connected to vSphere?

Options:

- A- Connected
- B- Attached
- C- Active
- D- It allows you to view the skew rate between two clock sources when using IEEE 1588 Precision Time Protocol.

Answer:

A

Question 4

Question Type: MultipleChoice

What is the name of the Arista EOS feature that allows you to set triggers and perform actions on those triggers?

Options:

- A- Event Manager
- B- Event Monitor
- C- Event Trigger
- D- Event History

Answer:

A

Question 5

Question Type: MultipleChoice

Which of the following commands will show the currently running version of EOS?

Options:

- A- show version
- B- show version detail

- C- bash more /etc/Eos-release
- D- VMTracer's Adaptive Segmentation feature will automatically add or prune VLANs learned from vCenter from the trunks connecting to the local switch on which the local ESXi host is connected.

Answer:

D

Question 6

Question Type: MultipleChoice

Which command will successfully configure Ethernet5 to be 40Gbps on an Arista 7150-52 switch?

Options:

- A- An Arista 7150-52 does not support 40Gbps
- B- Since Ethernet 5 is a 10Gbps port, 40Gbps is not possible.
- C- Arista(config-if-Et5)#speed forced 40gfull
- D- Arista(config-if-Et5)#speed 40gfull

Answer:

C

Question 7

Question Type: MultipleChoice

What are the three types of LANZ updates?

Options:

- A- Start, Update, and Stop
- B- Start, Update, and End
- C- Begin, Update, and End
- D- Begin, Update, and Stop

LANZ operates by setting threshold values on the interface and global buffer pools and then generates records for the start and end events causing those threshold values to be exceeded. Update records are also generated when buffer use exceeds those thresholds for a prolonged

period of time.

Answer:

B

Question 8

Question Type: MultipleChoice

Which of the following are not valid boot-config file entries?

Options:

- A- NETGW=192.168.1.1
- B- IMAGE-flash:EOS-4.12.1.swi
- C- SWI=flash:EOS-4.12.1.swi
- D- SWIX=flash:EOS-4.12.1.swi

Answer:

B

Question 9

Question Type: MultipleChoice

Arista Switches employ Which option best?

Options:

- A- Merchant silicon ASICs
- B- Custom ASICs
- C- Both
- D- Arista switches do not use ASICs

Answer:

A

Question 10

Question Type: MultipleChoice

Which of the following statements are true?

Options:

- A- VMTracer is a licensed feature.
- B- VMTracer is free.
- C- VMTracer is only supported on certain Arista switches.
- D- VMTracer is not supported in vEOS.

Answer:

A

To Get Premium Files for ACE-A1.2 Visit

<https://www.p2pexams.com/products/ace-a1.2>

For More Free Questions Visit

<https://www.p2pexams.com/arista/pdf/ace-a1.2>

20%
DISCOUNT

P2P
exams