



Free Questions for H12-222 by [braindumpscollection](#)

Shared by [Parks](#) on 20-10-2022

For More Free Questions and Preparation Resources

[Check the Links on Last Page](#)

Question 1

Question Type: MultipleChoice

Which of the following statements regarding the VRRP master is false?

Options:

- A- The VRRP master periodically sends VRRP packets.
- B- The VRRP master uses the virtual MAC address to respond to ARP Request packets destined for the virtual IP address.
- C- The VRRP master forwards IP packets destined for the virtual MAC address.
- D- Even if the router becomes the master, the backup router with a higher priority preempts to be the master.

Answer:

D

Question 2

Question Type: MultipleChoice

Which of the following are included in the full lifecycle guest management of the Agile Controller? (Multiple Choice)

Options:

- A- Account registration
- B- Account approval and distribution
- C- Account authentication
- D- Account audit and deregistration

Answer:

A, B, C, D

Question 3

Question Type: MultipleChoice

Which of the following command is used to apply the traffic policy to an interface on an AR router?

Options:

- A- traffic-policy pi inbound
- B- traffic classifier pi inbound
- C- traffic behavior pi inbound
- D- services-policy pi inbound

Answer:

A

Question 4

Question Type: MultipleChoice

A 32-bit MPLS header consists of a 20-bit label used for packet forwarding; A 3-bit EXP field that identifies the IP packet priority; A 1-bit bottom-of-stack flag that identifies the last label; And an 8-bitTTL field. Which statement regarding the TTL field is true?

Options:

- A- This field is used to prevent packet forwarding loops, similar to the TTL field in an IP header.

- B-** This field is used for label management.
- C-** This field used to control the upstream device in label distribution.
- D-** This field limitation the LSR.

Answer:

A

Question 5

Question Type: MultipleChoice

Administrators can query the online user status on eSight to check whether unauthorized users exist, improving the security monitoring capabilities.

Options:

- A-** TRUE
- B-** FALSE

Answer:

A

Question 6

Question Type: MultipleChoice

When the IP address of an interface on a firewall is pinged/ ping packets are processed by the internal module of the firewall but are not forwarded,

Options:

A- TRUE

B- FALSE

Answer:

A

Question 7

Question Type: MultipleChoice

Which of the following statements regarding data forwarding on a traditional IP network are true? (Multiple Choice)

Options:

- A-** The traditional IP forwarding is connection-oriented and has low efficiency.
- B-** On a traditional IP network, optimal paths are calculated based on the IGP metrics.
- C-** All the routers on a traditional IP network need to know routes on the entire network or default routes.
- D-** Traditional IP forwarding uses hop-by-hop forwarding.
- E-** A traditional IP network cannot provide a good QoS guarantee.

Answer:

B, C, D

Question 8

Question Type: MultipleChoice

Which of the following statements regarding the switch configuration are true? (Multiple Choice)

Options:

- A- By default, the DHCP service must be enabled when you configure the DHCP server and DHCP relay agent.
- B- VLANIF 100 receives DHCP packets and forwards the packets to the external DHCP server through a relay agent.
- C- Specify VLANIF 100 to the DHCP server group dhcpgroup1.
- D- Create a DHCP server group first and add a DHCP server to the group.
- E- By default, DHCP servers on the network are added to dhcpgroup1 automatically.

Answer:

A, B, C, D

Question 9

Question Type: MultipleChoice

Which of the following statements regarding the physical topology monitoring function of eSight are true? (Multiple Choice)

Options:

- A-** eSight displays the layout and status of NEs, subnets, and links on the GUI.
- B-** eSight supports visualized monitoring of the network-wide running status.
- C-** eSight displays the architecture of the entire network and relationship between network entities.
- D-** The physical topology monitoring provides an entry for unified network monitoring, improving O&M efficiency.

Answer:

A, B, C, D

Question 10

Question Type: MultipleChoice

Which of the following packets are transmitted in unicast mode during IP address application by the DHCP client and IP address allocation by the DHCP server? (Multiple Choice)

Options:

- A-** DHCP Offer
- B-** DHCP Request

C- DHCP Discover

D- DHCPACK

Answer:

A, D

Question 11

Question Type: MultipleChoice

Which of the following statements regarding the firewall zone security level is false?

Options:

A- The default security level of the new zone is 1.

B- Only the security level of the user-defined zone can be configured.

C- The configured security level cannot be changed.

D- Two zones cannot be configured with the same security level.

Answer:

A

Question 12

Question Type: MultipleChoice

LSRs use various label distribution control modes to set up LSPs. Which of the following statements is false?

Options:

- A-** There are two label distribution control modes: independent and ordered.
- B-** If the label advertisement mode is DU and the label distribution control mode is Independent, an LSR distributes labels without waiting for labels from the downstream device.
- C-** If the label advertisement mode is DoD and the label distribution control mode is Independent, the transit device distributes labels only after receiving a label mapping message from the egress device.
- D-** If the label advertisement mode is DU and the label distribution control mode is Ordered, the transit LSR distributes labels to the ingress device only after receiving a label mapping message from the egress device.

Answer:

C

To Get Premium Files for H12-222 Visit

<https://www.p2pexams.com/products/h12-222>

For More Free Questions Visit

<https://www.p2pexams.com/huawei/pdf/h12-222>

