



Free Questions for H12-811_V1.0 by [braindumpscollection](#)

Shared by [Sweet](#) on 06-06-2022

For More Free Questions and Preparation Resources

[Check the Links on Last Page](#)

Question 1

Question Type: MultipleChoice

There are hosts in a private network that need to access 1nternet. In order to achieve this requirement, which of the following configurations should be done by the administrator on the edge router of the network? (*)

Options:

- A- Default route
- B- STP
- C- DHCP
- D- NAT

Answer:

A, D

Question 2

Question Type: MultipleChoice

When deploying ACL on Huawei equipment, which of the following descriptions is correct is ().*

Options:

- A-** ACL can match the TCP/UDP port number of the packet, and can specify the range of port numbers
- B-** The same ACL can be called under multiple interfaces
- C-** When ACL defines rules, it can only proceed in the order of 10, 20, 30
- D-** ACL cannot be used to filter OSPF traffic, because OSPF traffic does not use UDP protocol encapsulation
- E-** When calling ACL under the interface, it can only be applied to the outbound direction

Answer:

A, B

Question 3

Question Type: MultipleChoice

The router Radius information configuration is shown in the figure. Which of the following statements are correct? #Radius-server template Huawei radius-server shared.key cipher Huawei radius-server authentication 200.0.12.1 1812 radius-server accounting

200.0.12.1 1813#*

Options:

- A- The source IP address of the Radius packet sent by the router is 200.0.12.2
- B- The P address of the accounting server is 200.0.12.1
- C- The P address of the authorization server is 200.0.12.1
- D- The P address of the authentication server is 200.0.12.1

Answer:

B, C, D

Question 4

Question Type: MultipleChoice

Link aggregation is a common technology in enterprise networks. Which of the following descriptions are the advantages of link aggregation technology? ()

Options:

- A- Improve safety
- B- Achieve load sharing
- C- Increase bandwidth
- D- Improve reliability

Answer:

B, C, D

Question 5

Question Type: MultipleChoice

Which of the following features does the default VLAN in the Layer 2 Ethernet switch have? (*)

Options:

- A- The default VLAN cannot be deleted manually

- B-** By default, all ports of the switch are member ports of the default VLAN
- C-** A default VLAN must be created before it can be assigned a port
- D-** The P address configured on the switch will only be applied to the member ports of the default VLAN

Answer:

A, B

Question 6

Question Type: MultipleChoice

ip route-static.10.0.2.2255.255.255.25510.0.12.2 preference20, the correct statement about this command is ()

Options:

- A-** The NextHop of this route is 10.0.12.2
- B-** The priority of this route is 20
- C-** This route can guide the forwarding of packets with the destination P address of 10.0.2.2.
- D-** This route can guide the forwarding of packets with the destination IP address 10.0.12.2

Answer:

A, B, C

Question 7

Question Type: MultipleChoice

In the OSPF protocol, the correct one in the following description of DR is (). (*)

Options:

- A-** Establish an adjacency relationship between DR and BDR
- B-** If the priority values of the two routers are equal, the router with the larger Router ID is selected as the DR
- C-** By default, all routers in this broadcast network will participate in the DR election
- D-** If the priority values of the two routers are different, the router with the smaller priority value is selected as the DR

Answer:

A, B, C

Question 8

Question Type: MultipleChoice

The administrator cannot log in to the Huawei router through Telnet, but other administrators can log in normally. What are the possible reasons for the following items? ()

Options:

- A- The administrator user account has been deleted
- B- The administrator user account has been disabled
- C- The Telnet service of the AR2200 router has been disabled
- D- The authority level of the administrator user account has been modified to 0

Answer:

A, B

Question 9

Question Type: MultipleChoice

In an OSPF broadcast network, with which routers does a Dothter router exchange link state information? ()

Options:

A- BDR

B- All OSPF neighbors

C- DR Other

D- DR

Answer:

A, D

To Get Premium Files for H12-811_V1.0 Visit

https://www.p2pexams.com/products/h12-811_v1.0

For More Free Questions Visit

<https://www.p2pexams.com/huawei/pdf/h12-811-v1.0>

