



Free Questions for JN0-222 by [braindumpscollection](#)

Shared by [Stevens](#) on [20-10-2022](#)

For More Free Questions and Preparation Resources

[Check the Links on Last Page](#)

Question 1

Question Type: MultipleChoice

Exhibit.

```
<rpc-reply xmlns:junos="http://xml.juniper.net/junos/20.1R0/junos">
  <configuration junos:commit-seconds="1589295982" junos:commit-localtime="2020-05-12 15:06:22
UTC" junos:commit-user="user">
    <interfaces>
      <interface>
        <name>ge-0/0/1</name>
        <unit>
          <name>0</name>
          <family>
            <inet>
              <address>
                <name>192.168.10.1/24</name>
              </address>
            </inet>
          </family>
        </unit>
      </interface>
      <interface>
        <name>fxp0</name>
        <unit>
          <name>0</name>
          <family>
            <inet>
              <address>
                <name>172.25.11.1/24</name>
              </address>
            </inet>
          </family>
        </unit>
      </interface>
    </interfaces>
  </configuration>
</rpc-reply>
```

Referring to the exhibit, which XML XPath expression will only show the IP address XML elements?

Options:

A- //address/name

B- //name

C- /name

D- /address/name

Answer:

A

Explanation:

https://www.w3schools.com/xml/xpath_syntax.asp

Question 2

Question Type: MultipleChoice

While conducting an automation test, you must issue a command using the curl tool to request the text formatted output from the show interfaces ge-0/0/0 terse command.

In this scenario, which command would you use?

Options:

- A- curl "u 'lab:lab123' 'http://10.210.10.155:3000/rpc/get-interface-information&format=text&interface-name=ge- 0/0/0&terse='
- B- curl "u 'lab:lab123' 'http://10.210.10.155:3000/rpc/get-interface-information@interface-name=ge-0/0/0?terse='
- C- curl "u 'lab:lab123' 'http://10.210.10.155:3000/rpc/get-interface-information@format=text&interface-name=ge-0/0/0? terse='
- D- curl "u 'lab:lab123' 'http://10.210.10.155:3000/rpc/get-interface-information@format=text?interface-name=ge- 0/0/0&terse='

Answer:

D

Question 3

Question Type: MultipleChoice

Which character is used to separate multiple parameters in a single REST API call?

Options:

A- &

B- #

C- ?

D- =

Answer:

A

Explanation:

com.juniper.junos_space.sdk.help/html/reference/Commonbehav.html

Question 4

Question Type: MultipleChoice

Which Junos system process handles NETCONF automation commands?

Options:

A- snmpd

B- eventd

C- mgd

D- jsd

Answer:

C

Question 5

Question Type: MultipleChoice

Exhibit.

```
- name: Update JunOS Configuration
hosts: firewalls
roles:
  - Juniper.junos
connection: local
gather_facts: no
tasks:
  - name: Checking NETCONF
    wait_for:
      host: "{{ inventory_hostname }}"
      port: 830
      sleep: 30
  - name: Update Config
    juniper_junos_config:
      load: set
      src: "{{ inventory_hostname }}.conf"
      host: "{{ mgmt_ip }}"
      user: "{{ username }}"
      ssh_private_key_file: "{{playbook_dir}}/{{ rsa_key_name }}"
      timeout: 180
    register: out
```

Referring to the exhibit, what is the function of the register key?

Options:

- A- to set an input value for the juniper_junos_rpc module
- B- to configure a global setting for the playbook
- C- to define a variable containing the return value from the module
- D- to print a result to standard out

Answer:

C

Question 6

Question Type: MultipleChoice

What are three elements of Infrastructure as Code (IaC)? (Choose three.)

Options:

- A- code review

B- integration

C- flow

D- feedback

E- version control

Answer:

B, C, E

To Get Premium Files for JN0-222 Visit

<https://www.p2pexams.com/products/jn0-222>

For More Free Questions Visit

<https://www.p2pexams.com/juniper/pdf/jn0-222>

