



Free Questions for 300-430 by certscare

Shared by Craig on 20-10-2022

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

A Cisco 8540 WLC manages Cisco Aironet 4800 Series APs and sends AoA data to a Cisco CMX 3375 Appliance for Hyperlocation. The load from the

WLC is distributed to another virtual CMX server using CMX grouping. The virtual CMX server shows location RSSI data and not Hyperlocation. No AOA

metrics are shown on the metrics page of the CMX virtual appliance under System > Metrics > Location Metrics. How must the network administrator

RESOLVE THIS ISSUE?

Options:

- A-** Allow port 2003 for AoA packets to flow through between the CMX appliances.
- B-** Enable Wireless > Access Points > Global configuration > Enable Hyperlocation on the WLC.
- C-** Use one Hyperlocation-enabled WLC and CMX for AoA data
- D-** Enable the HALO module on the CMX appliance for the data collection

Answer:

C

Question 2

Question Type: MultipleChoice

When configuring a large, high-availability wireless network which change to a mobility group creates less load on the controllers and maintains the same mobility messages?

Options:

- A- Configure mobility group multicast messaging.
- B- Remove unnecessary controllers from the mobility group.
- C- Configure the controllers into separate RF groups from the mobility groups.
- D- Separate the controllers into different mobility groups per controller.

Answer:

A

Question 3

Question Type: MultipleChoice

A hospital wants to offer indoor directions to patient rooms utilizing its existing wireless infrastructure. The wireless network has been using location

services specifications. Which two components must be installed to support this requirement? (Choose two.)

Options:

- A- Cisco CMX Analytics
- B- Cisco MSE
- C- Cisco CMX AppEngage
- D- WIPS
- E- Cisco CMX Visitor Connect

Answer:

A, B

Question 4

Question Type: MultipleChoice

ALLAR A network engineer must segregate all iPads on the guest WLAN to a separate VLAN. How does the engineer accomplish this task without using

Cisco ISE?

Options:

- A-** Enable RADIUS DHCP profiling on the WLAN.
- B-** Create a local policy on the WLC.
- C-** Use an mDNS profile for the iPad device.
- D-** Use 802.1x authentication to profile the devices

Answer:

B

Question 5

Question Type: MultipleChoice

An engineer must enable LSS for the Apple TV mDNS service only when ORIGIN is set to Wired. Which action meets this requirement?

Options:

- A-** Set ORIGIN to Wired. Enable LSS by using the config mdns service lss Apple TV command.
- B-** Set ORIGIN to either Wireless or All. Enable LSS by using the config mdns service lss enable Apple TV command
- C-** Set ORIGIN to Wired. Enable LSS by using the config mdns service lss All command
- D-** Set ORIGIN to either Wireless or All. Enable LSS by using the config mdns service lss All command.

Answer:

A

Question 6

Question Type: MultipleChoice

An engineer is deploying a virtual MSE. The network has 3000 APs and needs 7000 IPS licenses. To which size server does the engineer scale it?

Options:

- A- virtual
- B- standard
- C- high end
- D- low end

Answer:

C

Question 7

Question Type: MultipleChoice

#300 #301 A network administrator managing a Cisco Catalyst 9800-80 WLC must place all iOS connected devices to the guest SSID on VLAN 101. The rest of the clients must connect on VLAN 102 to distribute load across subnets. To achieve this configuration, the administrator configures a local policy on the WLC. Which two configurations are required? (Choose two.) KO

O

Options:

- A- Allow HTTP and DHCP profiling under policy map.
- B- Enable device classification on global wireless settings. '
- O C. Add local profiling policy under global security policy settings
- D- Assign a policy map under global security policy settings.
- E- Create a service template

Answer:

B, E

Question 8

Question Type: MultipleChoice

A shopping center uses AireOS controllers with Cisco Wave 2 APs. A separate WLAN named Guest-012345678-WLAN is used for guest wireless clients. Management need's location analytics to determine popular areas. CMX must track only associated clients. What must be selected on the CMX server settings?

Options:

- A- Exclude probing clients
- B- Enable Locally Administered MAC Filtering
- C- Enable Location MAC Filtering
- D- Duty Cycle Cutoff

Answer:

A

To Get Premium Files for 300-430 Visit

<https://www.p2pexams.com/products/300-430>

For More Free Questions Visit

<https://www.p2pexams.com/cisco/pdf/300-430>

