Question 1

What is required when you configure the PFCG role for an end-user on the front-end server? Note: There are 2 correct answers to this question.

Options:

A) The catalog assignment for the start authorization

B) The S_RFC authorization object for the OData access

C) The Fiori Launchpad designer assignment

D) The group assignment to display it in the Fiori Launchpad

Answer:

A

Question 2

Why should you create multiple dispatchers in SAP Identity Management? Note: There are 2 correct answers to this question.

Options:

A) To accommodate scalability

B) To support fail-over scenarios

C) To handle password provisioning

D) To handle special network access requirements

Answer:

A, D

Question 3

Question Type: MultipleChoice

User1 grants role 1 to user2. Who can revoke role 1 role from user2?

Options:

A) The system OBA user

B) The owner of role 1

C) Only User1

D) Any user with the 'ROLE ADMIN' database role

Answer:

D

Question 4

In your system, you have a program which calls transaction

Options:

A) Users with access to this program can still execute transaction A without explicit authorizations given to this transaction. How do you prevent the access of users to the transaction A from within the program?

A) Make sure you do NOT assign transact on A to the authorization object S_TCODE in the role that you assign to the unauthorized users.

B) Maintain SE93 with authorization objects for transact on A.

C) Maintain the check indicator in table TCDCOUPLES

D) Ensure that transact on A is NOT assigned into the same program authorization group

Answer:

B

Question 5

Question Type: MultipleChoice

The SSO authentication using X.509 client certificates is configured. Users complain that they can't log in to the back-end system. The trace file shows the following error message: 'HTTP request [2/5/9] Reject untrusted forwarded certificate'. What is missing in the configuration? Note: There are 2 correct answers to this question.

Options:

A) On the back-end, the profile parameter icm/HTTPS/verify client must NOT be set to 0

B) On the web-dispatcher, the SAPSSLS.pse must be signed by a trusted certification authority

C) On the web-dispatcher, the profile parameter icm/HTTPS/verify_client must be set to 0

D) The web dispatcher's SAPSSLC.PSE certificate must be added to the trusted reverse proxies list in icm/trusted_reverse_proxy_<xx>

Answer:

A, B

Question 6

Question Type: MultipleChoice

The SAP HANA database has its parameters configured with its default values. How can the SAP_INTERNAL_HA NA_SUPPORT catalog role be used?

Options:

A) The role can be granted to another role (nested)

B) The role can be granted to multiple users at a time

C) The role can be granted only with system privileges

D) The role can be granted to the SYSTEM user

Answer:

D

Question 7

Question Type: **MultipleChoice**

You are evaluating the 'Cross-client object change' option using transact on SCC4 for your Unit Test Client in the development environment. Which setting do you recommend?

Options:

A) Changes to repository and cross-client customizing allowed

B) No changes to repository and cross-client customizing objects

C) No changes to cross-client customizing objects

D) No changes to repository objects

Answer:

B

Question 8

Question Type: MultipleChoice

Your customer runs a 3-tier environment You are asked to set up controls around monitoring the sensitive objects (such as programs, user-exits, function modules) in a development system before they are transported to the quality assurance system.

Which table would you maintain to monitor such sensitive objects before executing an import?

Options:

A) TMSCDES

B) TMSBUFFER

C) TMSMCONF

D) TMSTCRI

Answer:

D