



Free Questions for 4A0-M05 by certsdeals

Shared by Bates on 15-04-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Which of the following networks is NOT required by CMM?

Options:

- A- An OAM network for CMM management
- B- An internal network for inter-VM communication
- C- A data switch fabric for carrying 3G data plane traffic between IPDS and IPPS.
- D- An external network for communication with external entities.

Answer:

D

Question 2

Question Type: MultipleChoice

Which of the following statements regarding CMM internal network is FALSE?

Options:

- A- It is a layer 2 network.
- B- It is connected to all CMM VMs.
- C- It is used for communication between CMM VMs.
- D- It requires a customer provided subnet address.

Answer:

D

Question 3

Question Type: MultipleChoice

Which of the following statements regarding CMM scaling is TRUE?

Options:

- A- DBS VMs can scale out in steps of a single VM.
- B- NECC VMs can scale out in steps of a single VM.
- C- CPPS VMs can scale out in steps of a single VM.
- D- IPDS VMs can scale out in steps of a single VM.

Answer:

C

Question 4

Question Type: MultipleChoice

Which of the following lifecycle management operations is NOT supported by CMM?

Options:

- A- Healing of all CMM VMs

B- Scale out of CPPS, PAPS, and IPPS VMs

C- Scale in of NECC and IPDS VMs

D- Instantiation of all CMM VMs

Answer:

C

Question 5

Question Type: MultipleChoice

Which of the following Nokia products is used to perform lifecycle management operations on CMM?

Options:

A- CloudBand infrastructure software (CBIS)

B- CloudBand application manager (CBAM)

C- CloudBand network director (CBND)

D- Network services platform (NSP)

Answer:

B

Question 6

Question Type: MultipleChoice

Which of the following best describes the function of CBAM in the Nokia CPC?

Options:

- A-** Provides the EMS function for element management of individual CPC components.
- B-** Provides the NFVO function to support the definition and management of end-to-end services.
- C-** Provides the VNFM function to manage the life cycle of VNFs including deployment and scaling.
- D-** Provides the VIM function to manage the compute and network resources required by VNFs.

Answer:

C

Question 7

Question Type: MultipleChoice

Which of the following provides the virtual hardware environment for the guest OS on a Linux system?

Options:

A- libvirt

B- QEMU

C- virsh

D- ESXi

Answer:

B

Question 8

Question Type: MultipleChoice

Which of the following OpenStack projects provides networking services to VMs?

Options:

- A- Neutron
- B- Nova
- C- Keystone
- D- Horizon

Answer:

A

Question 9

Question Type: MultipleChoice

Which of the following statements about interface redundancy with OVS is FALSE?

Options:

- A- OVS provides redundancy through a Linux bonded interface on the hypervisor.
- B- Guest VMs have two virtual NICs connected to OVS through a Linux bridge.
- C- Ethernet frames are sent between the redundant interfaces to verify connectivity.
- D- OVS connects to two physical ports connected to distinct leaf switches.

Answer:

C

To Get Premium Files for 4A0-M05 Visit

<https://www.p2pexams.com/products/4a0-m05>

For More Free Questions Visit

<https://www.p2pexams.com/nokia/pdf/4a0-m05>

