



Free Questions for [DES-1221](#) by [certsdeals](#)

Shared by [Waller](#) on [15-04-2024](#)

For More Free Questions and Preparation Resources

[Check the Links on Last Page](#)

Question 1

Question Type: MultipleChoice

Which network is used by the PowerStore for communication to the cluster database?

Options:

A- inter-node

B- ICM

C- IDN

D- ICD

Answer:

B

Question 2

Question Type: MultipleChoice

What are the IP requirements for ICW on PowerStore X and PowerStore T models?

Options:

- A- PowerStore T requires three storage IP addresses and PowerStore X requires five storage IP addresses
- B- PowerStore T requires four management IP addresses and PowerStore X requires six management IP addresses
- C- PowerStore T requires five management IP addresses and PowerStore X requires six management IP addresses
- D- PowerStore T requires seven storage IP addresses and PowerStore X requires three storage IP addresses

Answer:

B

Question 3

Question Type: MultipleChoice

A PowerStore T cluster has 3 appliances. Users are unable to access NAS services. What might be the issue?

Options:

- A- Master appliance is off-line
- B- NAS appliance failover is incorrectly configured
- C- Trial license is expired
- D- Resource balancer service has failed

Answer:

B

Question 4

Question Type: MultipleChoice

What is a requirement for the Import External Storage migration feature?

Options:

- A- PowerStore Global Storage Discovery IP address must be configured

- B-** PowerPath host-based multipathing software
- C-** PowerStore LACP bonded ports are tagged for replication
- D-** Direct Fibre Channel connections between storage systems

Answer:

A

Question 5

Question Type: MultipleChoice

Which API does PowerStore use to communicate with ESXi server during vVols provisioning operation?

Options:

- A-** REST
- B-** SOAP
- C-** VAAI
- D-** VASA

VASA is a VMware-defined API meant to provide a common way for VMware to integrate with storage vendors. The API is implemented

using an out-of-band, Simple Object Access Protocol (SOAP) over HTTPS.

Answer:

D

Question 6

Question Type: MultipleChoice

What is the total number of NVRAM devices used in PowerStore 3000?

Options:

A- 2

B- 4

C- Up to 6

D- Up to 21

Answer:

A

Question 7

Question Type: MultipleChoice

What is the correct power up sequence for a PowerStore?

Options:

A- 1. Base Enclosure Node B, 2. Base Enclosure Node A, 3. Expansion Enclosure

B- 1. Base Enclosure, 2. Expansion Enclosure

C- 1. Base Enclosure Node A, 2. Base Enclosure Node B, 3. Expansion Enclosure

D- 1. Expansion Enclosure, 2. Base Enclosure

Answer:

D

Question 8

Question Type: MultipleChoice

What is a way to verify the data path connectivity between a source VNX2 storage system and the PowerStore system when configuring an import session?

Options:

- A- Examine Fibre Channel zoning
- B- Verify host initiators on PowerStore Manager
- C- Review Server Manager MPIO properties
- D- Use the VNX2 SP ping operation

Answer:

D

Question 9

Question Type: MultipleChoice

A storage administrator has configured the addition of a VNX2 as a remote system for migration.

Which Import External Storage migration feature architectural components are now established?

Options:

- A- Host iSCSI initiators are registered on the VNX2 storage system
- B- Data path and management control path to the source storage system
- C- Data path and management control path to the access host
- D- Host Fibre Channel initiators are registered on the VNX2 storage system

Answer:

B

To Get Premium Files for DES-1221 Visit

<https://www.p2pexams.com/products/des-1221>

For More Free Questions Visit

<https://www.p2pexams.com/dell-emc/pdf/des-1221>

