

# Free Questions for H12-261\_V3.0 by certsdeals

Shared by Nieves on 12-12-2023

For More Free Questions and Preparation Resources

**Check the Links on Last Page** 

## **Question 1**

### **Question Type:** MultipleChoice

Regarding the authentication of the ISIS protocol, the correct statement is:

### **Options:**

- A- The two routers are configured for area authentication and interface authentication respectively, and the passwords are the same, then the two routers can establish a neighbor relationship
- B- After configuring area authentication, the IIH, SMP, and LSP sent by the router must carry the authentication TLV.
- C- After configuring interface authentication, the IIH sent by the router must carry the authentication TLV
- D- Interface authentication can authenticate the Hello packets of Leve1-1 and Leve1-2

### **Answer:**

A, C, D

# **Question 2**

**Question Type:** MultipleChoice

There are many ways to establish a cluster on a modular switch. What methods does Huawei modular switch support to establish a cluster?

### **Options:**

- A- Established through the cluster daughter card on the interface board
- B- Established through the cluster card on the main control board
- C- Established through the service interface on the interface board
- D- Established through the cluster card on the switching network board


#### Answer:

B, C, D

# **Question 3**

**Question Type:** MultipleChoice

Look at the picture and talk?



### **Options:**

- A- GE0/0/2 on STB is an alternative port
- B- GE0/0/1 on SWA is a backup port
- C- GE0/0/1 on SWB is an alternative port
- D- SWB will become the root bridge

### **Answer:**

D

# **Question 4**

### **Question Type:** MultipleChoice

Which type of BGP EVPN route does BGP EVPN use for MAC address advertisement, ARP information advertisement and IRB route advertisement?

### **Options:**

- A- Type3
- B- Type1
- C- Type2
- D- Type4

### **Answer:**

C

# **Question 5**

**Question Type:** MultipleChoice

Which of the following is the wrong description about the establishment of the BFD session?

### **Options:**

- A- Statically configuring a BFD session refers to manually configuring BFD session parameters through the command line, including local identifiers and remote identifiers, etc.
- B- When dynamically establishing a BFD session, the local identifier is dynamically allocated
- C- BFD sessions can only be established dynamically
- D- The system distinguishes between static BFD sessions and dynamic BFD sessions by dividing the identifier area.

#### **Answer:**

С

## **Question 6**

### **Question Type:** MultipleChoice

BFD judges whether a fault occurs by periodically detecting packets, which is a fast fault detection mechanism relying on routing protocols.

A- TRUE	
B- FALSE	
Answer:	
В	
uestion 7	
uestion Type: Multiple	
uestion Type: Multiple	Choice a fault occurs by periodically detecting packets, which is a fast fault detection mechanism relying on routing
uestion Type: Multiple BFD judges whether a	
uestion Type: Multiple BFD judges whether a	

Answer:
В
Question 8
Question Type: MultipleChoice
ICMPv6 has two types of error message (Error Messages) and information message (Information Messages).
Options:
A- TRUE  B- FALSE
Answer:
A
Question 9

### **Question Type:** MultipleChoice

After the establishment of the RPT village, what is the wrong description about the SPT switching?

### **Options:**

- A- The SPT path is the shortest and the forwarding performance is better
- B- The RPT tree may not be the optimal path for group insertion traffic forwarding
- C- All multicast traffic passes through the RP router, and the RP router may become the bottleneck of data forwarding
- D- After the SPT switching is completed, the multicast traffic still passes through the RPT tree

#### **Answer:**

D

# **Question 10**

### **Question Type:** MultipleChoice

As shown in the figure, private network routing information is exchanged between PE1 and PE2 and their respective CEs through SPF, and the same Domain ID is declared on both PE1 and PE2. When importing routes from BGP to OSPF on PE2, which of the following

types of LSAs may be delivered to CE2?

# **Options:**

- A- Type5 LSA
- B- Type7 LSA
- C- Type3 LSA
- D- Type1 LSA

### Answer:

A, B, C

# To Get Premium Files for H12-261\_V3.0 Visit

https://www.p2pexams.com/products/h12-261\_v3.0

## **For More Free Questions Visit**

https://www.p2pexams.com/huawei/pdf/h12-261-v3.0

