



Free Questions for DES-5221 by certsinside

Shared by Wagner on 29-01-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Which configuration supports tagged frames on VLAN 20 and untagged frames on VLAN 5?

Options:

A- interface ethernet 1/1/9

switchport trunk mode allowed vlan 20 switchport access mode vlan 5 no shutdown

B- interface ethernet 1/1/9 switchport trunk allowed vlan 20 switchport access vlan 5 switchport mode trunk

C- interface ethernet 1/1/9

switchport trunk mode allowed vlan 20 switchport access vlan 5 no shutdown

D- interface ethernet 1/1/9 switchport mode trunk switchport trunk allowed vlan 20 switchport access vlan 5

Answer:

D

Question 2

Question Type: MultipleChoice

An administrator is implementing VLT in OS10. What type of port-channel must they configure for the VLTi?

Options:

- A- Administrator needs to configure a LACP Port-Channel.
- B- Trunking and one (1) native VLAN need to be defined on the port-channel.
- C- None, a port-channel is created automatically during VLT discovery.
- D- Administrator needs to configure a static Port-Channel.

Answer:

C

Question 3

Question Type: MultipleChoice

Which LSA types are used in a single area OSPF topology?

Options:

A- 4, 5 and 7

B- 1 and 7

C- 1, 2 and 5

D- 2, 3 and 5

Answer:

C

Question 4

Question Type: MultipleChoice

When creating an alias in OS10 what is the maximum number of variable input parameters that can be defined?

Options:

A- 6

B- 9

C- 3

D- 12

Answer:

B

Explanation:

https://topics-cdn.dell.com/pdf/networking-s5148f-on_connectivity-guide4_en-us.pdf page 51

Question 5

Question Type: MultipleChoice

How are multiple hardware based ACLs filtered?

Options:

A- NTP

B- DHCP

C- NPU

D- IP

Answer:

C


Explanation:

https://www.dell.com/support/manuals/us/en/04/networking-z9264f-on/os10-enterprise-user-guide-10_4_2-pub/access-control-lists?guid=guid-c220a14f-c6cb-4950-ba88-15cbd59316aa&lang=en-us

Question 6

Question Type: MultipleChoice

Refer to the exhibit.



A default route exists on OS10-C that points all internet traffic towards 10.0.13.3 on OS10-B. A network administrator needs to re-route internet traffic only sourced from Host-1 to 10.0.12.2 on OS10-A instead. What feature can the administrator implement to accomplish this goal?

Options:

- A- Static Default Routing
- B- OSPF Cost Manipulation
- C- Source-Based Routing
- D- Policy-Based Routing


Answer:

D

Question 7

Question Type: MultipleChoice

Refer to the exhibit.



No static routing has been configured. For iBGP loopback-based peering, which statement is correct?

Options:

- A-** It is not necessary for the routing table on S1 to have an entry for the loopback network of S3.
- B-** S1 should have the Loopback network of S3 in its routing table for loopback-based peering.
- C-** For iBGP peering, physical interface addresses must be used.
- D-** A static route on S1 to 144.254.32.1/32 will eliminate the need for loopback-based peering with S3.

Answer:

B

To Get Premium Files for DES-5221 Visit

<https://www.p2pexams.com/products/des-5221>

For More Free Questions Visit

<https://www.p2pexams.com/dell-emc/pdf/des-5221>

