



Free Questions for EX447 by certsinside

Shared by Crawford on 18-01-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Install and configure ansible

User sandy has been created on your control node with the appropriate permissions already, do not change or modify ssh keys. Install the necessary packages to run ansible on the control node. Configure ansible.cfg to be in folder /home/sandy/ansible/ansible.cfg and configure to access remote machines via the sandy user. All roles should be in the path /home/sandy/ansible/roles. The inventory path should be in /home/sandy/ansible/inventory.

You will have access to 5 nodes.

node3.example.com

Configure these nodes to be in an inventory file where node 1 is a member of group dev, node2 is a member of group test, node3 is a member of group proxy, node4 and node 5 are members of group prod. Also, prod is a member of group webservers.

Options:

A) Explanation:

```
In/home/sandy/ansible/ansible.cfg
```

```
[defaults]
```

```
inventory=/home/sandy/ansible/inventory
```

```
roles_path=/home/sandy/ansible/roles
```

```
remote_user= sandy
host_key_checking=false
[privilegeescalation]
become=true
become_user=root
become_method=sudo
become_ask_pass=false
In /home/sandy/ansible/inventory
[dev]
node 1 .example.com
[test]
node2.example.com
[proxy]
node3 .example.com
[prod]
node4.example.com
node5 .example.com
[webservers:children]
prod
```

Answer:

A

Question 2

Question Type: MultipleChoice

Install and configure ansible

User bob has been created on your control node. Give him the appropriate permissions on the control node. Install the necessary packages to run ansible on the control node.

Create a configuration file `/home/bob/ansible/ansible.cfg` to meet the following requirements:

- * The roles path should include `/home/bob/ansible/roles`, as well as any other path that may be required for the course of the sample exam.
- * The inventory file path is `/home/bob/ansible/inventory`.
- * Ansible should be able to manage 10 hosts at a single time.
- * Ansible should connect to all managed nodes using the bob user.

Create an inventory file for the following five nodes:

Configure these nodes to be in an inventory file where node1 is a member of group dev, node2 is a member of group test, node3 is a member of group proxy, node4 and node 5 are members of group prod. Also, prod is a member of group webservers.

Options:

A) Explanation:

```
In/home/sandy/ansible/ansible.cfg
```

```
[defaults]
```

```
inventory=/home/sandy/ansible/inventory
```

```
roles_path=/home/sandy/ansible/roles
```

```
remote_user= sandy
```

```
host_key_checking=false
```

```
[privilegeescalation]
```

```
become=true
```

```
become_user=root
```

```
become_method=sudo
```

```
become_ask_pass=false
```

```
In /home/sandy/ansible/inventory
```

```
[dev]
```

```
node 1 .example.com
```

```
[test]
```

```
node2.example.com
```

```
[proxy]
```

```
node3 .example.com
```

```
[prod]
```

```
node4.example.com
```

```
node5 .example.com
```

```
[webservers:children]
```

```
prod
```

Answer:

A

Question 3

Question Type: MultipleChoice

Install and configure ansible

User bob has been created on your control node. Give him the appropriate permissions on the control node. Install the necessary packages to run ansible on the control node.

Create a configuration file `/home/bob/ansible/ansible.cfg` to meet the following requirements:

- * The roles path should include `/home/bob/ansible/roles`, as well as any other path that may be required for the course of the sample exam.
- * The inventory file path is `/home/bob/ansible/inventory`.
- * Ansible should be able to manage 10 hosts at a single time.
- * Ansible should connect to all managed nodes using the bob user.

Create an inventory file for the following five nodes:

Configure these nodes to be in an inventory file where node1 is a member of group dev. nodc2 is a member of group test, nodc3 is a member of group proxy, nodc4 and node 5 are members of group prod. Also, prod is a member of group webservers.

Options:

A) Explanation:

```
In/home/sandy/ansible/ansible.cfg
```

```
[defaults]
```

```
inventory=/home/sandy/ansible/inventory
```

```
roles_path=/home/sandy/ansible/roles
```

```
remote_user= sandy
```

```
host_key_checking=false
```

```
[privilegeescalation]
```

```
become=true
```

```
become_user=root
```

```
become_method=sudo
```

```
become_ask_pass=false
```

```
In /home/sandy/ansible/inventory
```

```
[dev]
```

```
node 1 .example.com
```

```
[test]
```

```
node2.example.com
```

```
[proxy]
```

```
node3 .example.com
```

```
[prod]
node4.example.com
node5 .example.com
[webservers:children]
prod
```

Answer:

A

Question 4

Question Type: MultipleChoice

Install and configure ansible

User sandy has been created on your control node with the appropriate permissions already, do not change or modify ssh keys. Install the necessary packages to run ansible on the control node. Configure ansible.cfg to be in folder /home/sandy/ansible/ansible.cfg and configure to access remote machines via the sandy user. All roles should be in the path /home/sandy/ansible/roles. The inventory path should be in /home/sandy/ansible/inventory.

You will have access to 5 nodes.

```
node3.example.com
```


Configure these nodes to be in an inventory file where node 1 is a member of group dev. node2 is a member of group test, node3 is a member of group proxy, node4 and node 5 are members of group prod. Also, prod is a member of group webservers.

Options:

A) Explanation:

```
In/home/sandy/ansible/ansible.cfg
```

```
[defaults]
```

```
inventory=/home/sandy/ansible/inventory
```

```
roles_path=/home/sandy/ansible/roles
```

```
remote_user= sandy
```

```
host_key_checking=false
```

```
[privilegeescalation]
```

```
become=true
```

```
become_user=root
```

```
become_method=sudo
```

```
become_ask_pass=false
```

```
In /home/sandy/ansible/inventory
```

```
[dev]
```

```
node 1 .example.com
```

```
[test]
```

```
node2.example.com
```

```
[proxy]
```

```
node3 .example.com
```

[prod]
node4.example.com
node5 .example.com
[webservers:children]
prod

Answer:

A

To Get Premium Files for EX447 Visit

<https://www.p2pexams.com/products/ex447>

For More Free Questions Visit

<https://www.p2pexams.com/redhat/pdf/ex447>

