



CheckPoint 156-836 CCME Practice Questions

Shared by Wooten on 24-08-2026

For More Free Questions and Preparation Resources

Check the Links on Last Page



Question 1

Question Type: MultipleChoice

Is it possible to define distribution mode per interface?

Options:

- A- Yes, only for downlink interfaces
- B- No, only for the Security Group
- C- Yes, only for uplink interfaces
- D- Yes, for both uplink and downlink interfaces

Answer:

D

Question 2

Question Type: MultipleChoice

Which feature is used to force trusted non-F2F traffic into the fully accelerated path for handling by SecureXL.

Options:

- A- Fast Accelerator
- B- hypersync
- C- rate limiting
- D- SecureXL

Answer:

D

Question 3

Question Type: MultipleChoice

What is an uplink interface used for?

Options:

- A- To connect in between appliances
- B- To connect appliances to customer's infrastructure
- C- To connect Orchestrators to customer's infrastructure
- D- To connect in between Orchestrators

Answer:

C

P2P
exams

Question 4

Question Type: MultipleChoice

What does asg monitor command do?

Options:

- A- This command does not exist
- B- Monitor health status of entire system
- C- Monitor traffic on Appliances in Security Group
- D- Show real-time cluster status of Appliances in Security Group

Answer:

D

P2P
exams

Question 5

Question Type: MultipleChoice

During an upgrade, Is Multi-Version Clustering (MVC) supported?

Options:

- A- No. Maestro does not support MVC because ClusterXL is disabled during an upgrade.

- B- No, Maestro does not support MVC.
- C- Maestro supports MVC or full connectivity upgrade as of R80.40.
- D- Yes, MVC is supported as of R81 for Maestro.

Answer:

C

Question 6

Question Type: MultipleChoice

Layer 4 distribution is enabled by default in Maestro. Which is not a scenario when you would want to leave this enabled?

Options:

- A- When there is a large number of source ports in use by protocols such as HTTP, HTTPS, and DNS.
- B- When dynamic routing protocols, such as BGP or OSPF are used.
- C- When there is a heavy imbalance of traffic between the SGMs that are members of the same SG.
- D- When the SG is NATing a very high percentage of traffic passing through it.

Answer:

B

Question 7

Question Type: MultipleChoice

What is the maximum number of Appliances within Security group in Dual-Site configuration?

Options:

- A- 28
- B- 31
- C- 15
- D- 16

Answer:

A

Question 8

Question Type: MultipleChoice

A splitter cannot be used:

Options:

- A- To connect a single port on an Orchestrator to the same Appliance
- B- To connect a single port on an Orchestrator to multiple ports on an external switch
- C- To connect a single port on an Appliance to multiple ports on the Orchestrator
- D- To connect a single port on an Orchestrator to multiple Appliances

Answer:

A

Question 9

Question Type: MultipleChoice

Each morning at 1:00 am, a series of automatic diagnostics on all the SGMs runs by automatic execution of which command?

Options:

- A- hcp -r all
- B- asg diag list
- C- asg diag verify
- D- asg perf -v

Answer:

C

Question 10

Question Type: MultipleChoice

Complete the sentence: Dual Orchestrators work as. _____

Options:

- A- Load Sharing cluster
- B- Active-Active cluster
- C- Active - Standby cluster
- D- Hot-Swap RAID



Answer:

B

Question 11

Question Type: MultipleChoice

What cannot be learned from the output of asg monitor command?

Options:

- A- Uptime
- B- Port status
- C- Security Policy status
- D- Appliances cluster status



Answer:

D

Question 12

Question Type: MultipleChoice

What is the throughput penalty of Security Group?

Options:

- A- Depends on the type of Appliance
- B- 1% per member
- C- 10% per Security Group with no relation to the number of members
- D- 5% per member

Answer:

B



To Get Premium Files for 156-836 Visit

<https://www.p2pexams.com/products/156-836>

For More Free Questions Visit

<https://www.p2pexams.com/checkpoint/pdf/156-836>

20%
DISCOUNT

P2P
exams