

# Free Questions for 300-415 by go4braindumps

# Shared by Emerson on 18-01-2024

For More Free Questions and Preparation Resources

**Check the Links on Last Page** 

# **Question 1**


### **Question Type:** MultipleChoice

### Refer to the exhibit





hage not for d or type unknown

B)



C)






Options:			
A) Option			
B) Option			
C) Option			
D) Option			

### Answer:

С

# **Question 2**

**Question Type:** MultipleChoice



Refer to the exhibit A vBond controller was added to the controller list with the same Enterprise Root CA certificate as vManage. The two controllers can reach each other via VPNO and share the same organization name, but the control connection is not initiated- Which action resolves the issue?


### **Options:**

- A) Synchronize the WAN Edge list on vManage with controllers.
- **B)** Configure NTP on both controllers to establish a connection.
- C) Configure a valid systom IP on the vBond controller.
- D) Configure a valid vBond IP on vManage.

Answer:		
D		


# **Question 3**

**Question Type:** MultipleChoice




Refer to the exhibit The engineering must assign tags to 3 Of its 74 server networks as soon as they are advertised to peers These server network must not be advertised AS which configuration fulfil the requirement?


A)




B)



C)






# Options: A) Option A B) Option B C) Option C D) Option D

### Answer:

D

# **Question 4**

**Question Type:** MultipleChoice



Refer to the exhibit. A network administrator is configuring OSPF advanced configuration parameters from a template using the vManager GUI for a branch WAN Edge router to calculate the cost of summary routes to an ASBR. Which action achieves this configuration?

### **Options:**

A) Disable RFC 1583 Compatiblt

B) Enable Originate

C) Enable RFC 1M3 Compatible


D) Disable Original

### Answer:

С

# **Question 5**

**Question Type:** MultipleChoice



Refer to the exhibit The network team must configure application-aware routing for the Service VPN 50.0.0/16 The SLA must prefer MPLS for video traffic but the remaining traffic must use a public network What must be defined other than applications before the application-aware policy is create?

# Options: A) SLA Class, Site VPN. Prefix B) Data Prefix, Site VPN TLOC C) Application, SLA VPN. Prefix D) Color, SLA Class, Sue, VPN


### Answer:

А

# **Question 6**

**Question Type:** MultipleChoice

### Refer to the exhibit



Refer to the exhibit A WAN Edge device was recently added to vManage but a control connection could not be established Which action resolves this issue?

### **Options:**


- A) Rectify the Rod CA certificate mismatch on WAN Edge devices
- B) Install the bootstrap code on WAN Edge and check for CSR
- C) Send the serial number to vBond from the vManage controller.
- D) Resolve the ZTP reachability and rectify smart account credentials issue

### Answer:


С

# **Question 7**

### Refer to the exhibit




Refer to the exhibit The network team must configure EIGRP peering at HQ with devices in the service VPN connected to WAN Edge CSRv. CSRv is currently configured with




Which configuration on the WAN Edge meets the requiremnet


### A)




B)



C)



D)



### **Options:**


- A) Option A
- B) Option B
- C) Option C
- D) Option D

### Answer:

С


# **Question 8**

### Refer to the exhibit




Refer to the exhibit Which configuration must the engineer use to form underlay connectivity for the Cisco SD-WAN network?


### A)




B)



C)






<b>Options:</b>			
A) Option A			
B) Option B			
C) Option C			
D) Option D			

Answer:			
С			


# **Question 9**

**Question Type: MultipleChoice** 




Refer to the exhibit An engineer is configuring a QoS policy to shape traffic for VLAN 100 on a subinterface Which policy configuration accomplishes the task?


A)




B)



C)






Options:			
A) Option A			
B) Option B			
C) Option C			
D) Option D			

### Answer:


С

# **Question 10**


**Question Type:** MultipleChoice




Refer to the exhibit The network team must configure EI GRP peering at HQ with devices in the service VPN connected to WAN Edge CSRv. CSRv is currently configured with









B)



C)





<b>Options:</b>			
A) Option A			
B) Option B			
C) Option C			
D) Option D			

### Answer:

С

## **To Get Premium Files for 300-415 Visit**

https://www.p2pexams.com/products/300-415

For More Free Questions Visit

https://www.p2pexams.com/cisco/pdf/300-415

