



Free Questions for 300-430 by certsinside

Shared by Morgan on 15-04-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Refer to the exhibit.

Data Rates**

| | |
|----------|-------------|
| 1 Mbps | Disabled ▼ |
| 2 Mbps | Disabled ▼ |
| 5.5 Mbps | Disabled ▼ |
| 6 Mbps | Supported ▼ |
| 9 Mbps | Mandatory ▼ |
| 11 Mbps | Disabled ▼ |
| 12 Mbps | Mandatory ▼ |
| 18 Mbps | Supported ▼ |
| 24 Mbps | Mandatory ▼ |
| 36 Mbps | Supported ▼ |
| 48 Mbps | Supported ▼ |
| 54 Mbps | Supported ▼ |

An engineer is configuring a Cisco wireless LAN controller and needs wireless multicast to use the 54Mbps rates. Which action meets this requirement?

Options:

- A- Change the 24 Mbps to Supported.
- B- Set all data rates below 54 Mbps to Supported.
- C- Change the 54 Mbps to Mandatory.
- D- Set all data rates below 54 Mbps to Disable.

Answer:

D

Question 2

Question Type: MultipleChoice

Refer to the exhibit.

```
(Cisco Controller) >show nmsp notification interval

Nmsp Notification Interval Summary

RSSI Interval:
Client..... 20 sec
RFID..... 20 sec
Rogue AP..... 20 sec
Rogue Client..... 20 sec

Spectrum Interval:
Interferer device..... 20 sec

(Cisco Controller) >
```

An administrator notices slower location updates from the controller to Cisco CMX. Which command must be configured to get an update every 5 seconds for rogues?

Options:

- A- config location notification interval rssi rogues 5
- B- config nmsp notification interval rssi rogues 5
- C- config subscription notification interval rssi rogues 5
- D- config cmx notification interval rssi rogues 5

Answer:

B

Question 3

Question Type: MultipleChoice

An engineer wants to upgrade the APs in a Cisco FlexConnect group. To accomplish this upgrade, the FlexConnect AP Upgrade setting will be used. One AP of each model with the lowest MAC address in the group must receive the upgrade directly from the controller. Which action accomplishes this direct upgrade?

Options:

- A- Remove the APs from the group.
- B- Reboot all APs before the upgrade.
- C- Allocate the master APs to different groups.
- D- Do not set any master APs.

Answer:

C

Question 4

Question Type: MultipleChoice

An engineer is in the process of implementing Fastlane on a wireless network with a Mobility Express AP installed and Apple end-user devices. Due to a security concern, the IT department has updated all the iPads to version 14.5.423551943. Which QoS profile must the engineer configure on the user

WLAN?

Options:

- A- Platinum
- B- Best Effort
- C- Bronze
- D- Silver

Answer:

A

Question 5

Question Type: MultipleChoice

An IT administrator deploys Cisco 2802i APs in all office locations, including main campus and branch offices. The WLC that manages the APs is located at the data center on the main campus. The APs on the main campus are configured to use Local mode and the APs in the branches use FlexConnect mode. Which configuration must be applied to the APs for corporate devices on the main campus to be mapped to the local LAN switch on different VLANs according to the VLAN tag ID and WLAN?

Options:

- A- Enable Central DHCP Processing.
- B- Disable FlexConnect Local Auth
- C- Enable FlexConnect Local Switching.
- D- Disable VLAN-based Central Switching.

Answer:

A

Question 6

Question Type: MultipleChoice

An IT administrator deployed an OEAP to the home of a remote user, but the OEAP cannot reach the WLC. Which two configuration settings must be completed before an OEAP is deployed successfully? (Choose two.)

Options:

- A- Configure Secondary Controller Name and Management IP address in the High Availability tab.
- B- Configure LSC to authorize the OEAP.
- C- Configure the AP mode to FlexConnect and check the box for Office Extend AP.
- D- Configure the WLC with an external IP address on the virtual interface.
- E- Configure Primary Controller Name and Management IP address in the High Availability tab.

Answer:

C, E

Question 7

Question Type: MultipleChoice

An engineer is configuring a new wireless network for guest access. The Facebook page of the company must be viewed by the guest users before they get access to the network. A Cisco MSE is used as a wireless component. Which URL must be used in the configuration as the external redirection URL?

Options:

- A- <http://<MSE>:8083/visitor/login.do>
- B- <http://<MSE>:8083/fbwifi/forward>
- C- <http://<MSE>:8084/visitor/login.do>
- D- <http://<MSE>:8084/fbwifi/forward>

Answer:

D

To Get Premium Files for 300-430 Visit

<https://www.p2pexams.com/products/300-430>

For More Free Questions Visit

<https://www.p2pexams.com/cisco/pdf/300-430>

