



Free Questions for 350-401 by go4braindumps

Shared by Mccoy on 15-04-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Which port is required to allow APs to join a WLC when directed broadcasts are used on a Cisco iOS switch?

Options:

A- UDP5246

B- TCP 5246

C- TCP 5247

D- UDP5247

Answer:

D

Question 2

Question Type: MultipleChoice

Refer to the exhibit.

```
from requests.auth import HTTPBasicAuth
import requests

ROUTER="192.0.2.1"
BASEURI="restconf/data/Cisco-IOS-XE-native:native"
SUBURI="router/router-bgp"

response = requests.get(
    f"https://{ROUTER}/{BASEURI}/{SUBURI}",
    auth=HTTPBasicAuth('admin', 'S3cr3tP4ss'),
    verify=False)

print(f"HTTP Response: {response.status_code} {response.reason}\n")
print(response.text)
```

```
admin@linux:/tmp$ python3 get-bgp.py
HTTP Response: 404 Not Found

<errors xmlns="urn:ietf:params:xml:ns:yang:ietf-restconf">
  <error>
    <error-message>uri keypath not found</error-message>
    <error-tag>invalid-value</error-tag>
    <error-type>application</error-type>
  </error>
</errors>

admin@linux:/tmp$
```

An engineer is creating a Python script to fetch the BGP configuration from a device using RESTCONF. What does the output indicate?

Options:

- A- The BGP data resource identifier in the URL Incorrect.
- B- There is no BGP process running on the device
- C- RESTCONF is not enabled on the device.

Answer:

A

Question 3

Question Type: MultipleChoice

Which action occurs during a Layer 3 roam?

Options:

- A- The client receives a new IP address after authentication occurs.
- B- The client is marked as "foreign" on the original controller.
- C- The client database entry is moved from the old controller to the new controller.
- D- traffic is tunneled back to the original control after a Layer 3 roam occurs.

Answer:

D

Question 4

Question Type: MultipleChoice

When the "deny" statement is used within a route map that is used for policy-based routing how is the traffic that matches the deny route-map line treated?

Options:

- A-** Traffic is routed to the null 0 interface of the router and discarded.
- B-** Traffic is returned to the normal forwarding behavior of the router.
- C-** An additional sequential route-map line is needed to divert the traffic to the router's normal forwarding behavior.
- D-** An additional sequential route-map line is needed to policy route this irafic.

Answer:

B

Question 5

Question Type: MultipleChoice

Which configuration allows administrators to configure the device through the console port and use a network authentication server?

A)

```
aaa new-model
aaa authentication login default local
aaa authorization console
aaa authorization config-commands
username netadmin secret 9 $9$VfPmf8elb4RVV8$seZ/bDAx1uV
```

B)

```
aaa new-model
aaa authentication login default line
```

C)

```
aaa new-model
aaa authentication login default group radius
aaa authorization console
aaa authorization config-commands
```

D)

```
aaa new-model
aaa authentication login default local
aaa authorization console
aaa authorization config-commands
```

Options:

- A- Option
- B- Option
- C- Option
- D- Option

Answer:

C

Question 6

Question Type: MultipleChoice

Which feature does Cisco DNA Center Assurance provide?

Options:

- A- application policy configuration
- B- device onboarding and configuration
- C- software upgrade and management
- D- data correlation and analysis

Answer:

D

Question 7

Question Type: MultipleChoice

Refer to the exhibit.


```
aaa new-model
!
username admin privilege 15 secret S3cr3tP4ss
!
ip http secure-server
ip http authentication aaa
```

An administrator must enable RESTCONF access to a router. Which two commands or command sets must be added to the existing configuration? (Choose two.)

A)

```
aaa authentication login default local
aaa authorization exec default local
```

B)

```
restconf
```

C)

```
netconf-yang
```

D)

```
username restconf privilege 0
```

Options:

- A- Option A
- B- Option B
- C- Option C
- D- Option D

Answer:

C

Question 8

Question Type: MultipleChoice

An engineer must configure HSRP for VLAN 1200 on SW1. The second switch is configured by using the last usable IP address in the network as the virtual IP. Which command set accomplishes this task?

A)

```
SW1(config)# interface vlan 1200
SW1(config-if)# ip address 172.12.0.254 255.255.255.0
SW1(config-if)# standby version 2
SW1(config-if)# standby 1200 ip 172.12.0.2
```

```
SW1(config-if)# standby 1200 preempt
```

B)

```
SW1(config)# interface vlan 1200
SW1(config-if)# ip address 172.12.0.2 255.255.255.0
SW1(config-if)# standby version 2
SW1(config-if)# standby 1200 ip 172.12.0.254
SW1(config-if)# standby 1200 preempt
```

C)

```
SW1(config)# interface vlan 1200
SW1(config-if)# ip address 172.12.0.2 255.255.255.0
SW1(config-if)# standby 1200 ip 172.12.0.254
SW1(config-if)# standby 1200 timers 5 15
SW1(config-if)# standby 1200 preempt
```

D)

```
SW1(config)# interface vlan 1200
SW1(config-if)# ip address 172.12.0.1 255.255.255.0
SW1(config-if)# standby 1200 ip 172.12.0.254
SW1(config-if)# standby 1200 timers 5 15
SW1(config-if)# standby 1200 preempt
```

Options:

- A- Option A
- B- Option B
- C- Option C
- D- Option D

Answer:

B

Question 9

Question Type: MultipleChoice

Which security feature does stateless authentication and authorization use for REST API calls?

Options:

A- OAuth 2 token

B- API keys

C- SSL/TLS certificate encryption

D- Cookie-based session authentication

Answer:

A

To Get Premium Files for 350-401 Visit

<https://www.p2pexams.com/products/350-401>

For More Free Questions Visit

<https://www.p2pexams.com/cisco/pdf/350-401>

