



Free Questions for 350-501 by go4braindumps

Shared by Dejesus on 07-06-2022

For More Free Questions and Preparation Resources


Check the Links on Last Page

Question 1


Question Type: MultipleChoice

An engineer is setting up overlapping VPNs to allow VRF ABC and XYZ to communicate with VRF CENTRAL but wants to make sure that VRF ABC and XYZ cannot communicate. Which configuration accomplishes these objectives?


A)



B)



C)



Options:

- A) Option A
- B) Option B
- C) Option C

Answer:

B

Question 2

Question Type: MultipleChoice

Which two uses of the YANG data modeling language are true? (Choose two)

Options:

- A) It can be used to shape slats data of network elements
- B) It can be used to access a device by HTTP
- C) It can be used to model the configuration used by NETCONF operations
- D) It can be used to replace the OSI model for troubleshooting

E) It can be used to replace RESTCONF as a mechanism to install and manipulate configuration

Answer:

A, B

Question 3

Question Type: MultipleChoice

A customer of an ISP requests support to setup a BGP routing policy. Which BGP attribute should be configured to choose specific BGP speakers as preferred exit points for the customer AS?

Options:

- A)** highest local preference outbound
- B)** lowest local preference inbound
- C)** highest local preference inbound
- D)** lowest multi-exit discriminator

Answer:

A

Question 4

Question Type: MultipleChoice

A network engineer is implementing a QoS policy for outbound management traffic classification and marking on a CPE device with these requirements:

A network engineer is implementing a QoS policy for outbound management traffic classification and marking on a CPE device with these requirements

- * Management protocols must be marked with DSCP AF class 2 with low drop probability.
- * Monitoring protocols must be marked with DSCP AF class 1 with low drop probability.
- * All remaining traffic must be marked with a DSCP value of 0.

Which configuration must the engineer implement to satisfy the requirements?

A)

Image not found or type unknown



B)

Image not found or type unknown



C)

Image not found or type unknown



D)

Image not found or type unknown



Options:

A) Option A

B) Option B

C) Option C

D) Option D

https://www.cisco.com/c/en/us/td/docs/switches/datacenter/nexus1000/sw/4_0/qos/configuration/guide/nexus1000v_qos/qos_6dscp_val.pdf

Answer:

C

Question 5

Question Type: MultipleChoice

Refer to the exhibit.

Image not found or type unknown



An engineer is configuring router R1 for OSPFv3 as shown. Which additional configuration must be performed so that the three active interfaces on the router will advertise routes and participate in OSPF IPv6 processes?

Options:

- A)** from 2.2.2.2, with a TTL of less than 2
- B)** to 2.2.2.2, with a TTL of less than 253
- C)** from 2.2.2.2, with a TTL of 253 or more

D) to 2.2.2.2, with a TTL of 2 or more


Answer:

A

Question 6


Question Type: MultipleChoice

Refer to the exhibit.



A network operator must configure CSR1 interfaces GigabitEthernet2 and GigabitEthernet1 to rewrite VLAN tags 12 and 21 for traffic between R1 and R2 respectively. Which configurator accomplishes this task?

A)



9B)



Image not found or type unknown

C)



Image not found or type unknown

Options:

A) Option A

B) Option B

C) Option C

Answer:

C

To Get Premium Files for 350-501 Visit

<https://www.p2pexams.com/products/350-501>

For More Free Questions Visit

<https://www.p2pexams.com/cisco/pdf/350-501>

