



Free Questions for 350-601 by certsinside

Shared by Wallace on 07-06-2022

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: DragDrop

An engineer deploys a custom guest shell rootfs onto multiple switches. Drag and drop the steps from the left into the correct order on the right.

image not found or type unknown
image not found or type unknown



Answer: image not found or type unknown



image not found or type unknown

Question 2

Question Type: MultipleChoice

image not found or type unknown



Refer to the exhibit.

image not found or type unknown
image not found or type unknown



Why does the python code for Cisco NX-API print error message?

Options:

- A) The "type" is wrong in the header of the request and should be "cli_ conf".
- B) NX-API does not allow configuration for features via the requests module.
- C) The "type" is wrong is the body of the request and should be "cli_ conf".
- D) The JSON is not a supported format for the NX-API.


Answer:

C

Question 3

Question Type: MultipleChoice

Refer to the exhibit. An engineer must monitor ingress traffic from SW1 and SW2 port-channel interfaces from SW3. Which configuration must be implemented to accomplish this goal? A)



B)

Image not found or type unknown



C)

Image not found or type unknown



D)

Image not found or type unknown



Options:

A) Option A

B) Option B

C) Option C

D) Option D

Answer:


D

Question 4


Question Type: MultipleChoice

A network engineer configures a converged network adapter (CNA) and must associate a virtual fiber Channel 7 interface to VSAN 7. The CAN connected to the interface Eth1/7, and VLAN 700 is mapped to the VSNA. Which configuration must be applied to create the virtual Fiber Channel interface and associate it with the Ethernet physical interface?

A)



B)



C)




Image not found or type unknown



Options:

- A) Option A
- B) Option B
- C) Option C
- D) Option D

Answer:

D

Question 5

Question Type: MultipleChoice

Refer to the exhibit.

```
NEXUS(config)# radius-server timeout 15
NEXUS(config)# ip radius source-interface Vlan100
NEXUS(config)# radius-server host 10.1.50.31 key 7 "Fowhg1234"
authentication accounting
NEXUS(config)# aaa group server radius RADIUS
NEXUS(config-radius)# server 10.1.50.31
NEXUS(config-radius)# deadtime 10
NEXUS(config-radius)# use-vrf management
NEXUS(config-radius)# source-interface mgmt 0
NEXUS(config)# aaa authentication login default group RADIUS
```

What is the result of implementing the configuration?

Options:

- A) RADIUS traffic is sourced from the VLAN 200 interface.
- B) The RADIUS server timeout value is 15 milliseconds.
- C) Only the RADIUS server is used for authentication.
- D) Users specify the RADIUS server when they log in.

Answer:

C

Question 6

Question Type: MultipleChoice

Which three firmware packages are included in the Cisco UCS C-Series Rack-Mount UCS-Managed Server Software bundle? (Choose three.)

Options:

- A) CIMC
- B) board controller
- C) system
- D) third-party
- E) BIOS
- F) adapter

Answer:

A, B, E

To Get Premium Files for 350-601 Visit

<https://www.p2pexams.com/products/350-601>

For More Free Questions Visit

<https://www.p2pexams.com/cisco/pdf/350-601>

