

# Free Questions for 1Y0-241 by actualtestdumps

Shared by Ballard on 29-01-2024

For More Free Questions and Preparation Resources

**Check the Links on Last Page** 

# **Question 1**

Question Typ	e: Mul	ltipleC	hoice
Q GLODELOIL I J N			

A Citrix Administrator needs to use a client's IP address as the source IP address for Citrix ADC-to-server connections.

Which Citrix ADC mode can the administrator use to meet this requirement?

### **Options:**

- A- USNIP
- B- Layer 2
- C- Layer 3
- D- USIP

### **Answer:**

D

### **Explanation:**

When you enable the USIP address mode of a NetScaler appliance, the appliance forwards each packet to the appropriate back end server with the client IP address. https://support.citrix.com/article/CTX121974

### **Question 2**

### **Question Type:** MultipleChoice

A Citrix Administrator needs to confirm that all client certificates presented to the authentication vServer are valid until the year 2023.

Which expression can the administrator use to meet this requirement?

#### **Options:**

- A- CLIENT.SSL.CLIENT\_CERT.VALID\_NOT\_AFTER.EQ(GMT2023)
- B- CLIENT.SSL.CLIENT\_CERT.VALID\_NOT\_BEFORE.EQ(GMT2023)
- C- CLIENT.SSL.ORIGIN\_SERVER\_CERT.VALID\_NOT\_AFTER.EQ(GMT2023)
- D- CLIENT.SSL.CLIENT\_CERT.DAYS\_TO\_EXPIRE.EQ(2023)

#### **Answer:**

### **Explanation:**

https://docs.citrix.com/en-us/citrix-adc/current-release/appexpert/policies-and-expressions/adv-policy-exp-working-with-dates-times-and-numbers/exp-for-ssl-certificate-date.html

# **Question 3**

### **Question Type:** MultipleChoice

Scenario: A Citrix Administrator needs to improve website loading speed. End users are reporting slow GIF

image rendering speeds as they scroll down a website, which affects overall page load time.

Which Citrix ADC feature can the administrator enable to improve website performance?

### **Options:**

A- Domain sharding

- **B-** Image lazy loading
- C- Image optimization
- D- Image shrink-to attributes

#### **Answer:**

C

### **Explanation:**

Reduces the image to the size indicated in the image tag by Citrix ADC, enabling client browsers to load images faster. https://docs.citrix.com/en-us/citrix-adc/current-release/optimization/front-end-optimization.html

# **Question 4**

#### **Question Type:** MultipleChoice

Scenario: A Citrix ADC is configured with Interface 1/1 and bound to VLAN 40. A Citrix Administrator executed the below command:

> bind vlan 10 --ifnum 1/1

What is the result of executing this command on the Citrix ADC?

### **Options:**

- A- Interface 1/1 is bound to VLAN 20, and native VLAN is 20.
- B- Interface 1/1 is bound to VLAN 20, and native VLAN is NOT changed.
- C- Interface 1/1 is bound to VLAN 20, and native VLAN is 40.
- D- Interface 1/1 is bound to VLAN 20, and native VLAN is 1.

#### **Answer:**

Α

### **Explanation:**

https://www.citrix.com/blogs/2014/12/29/netscaler-vlans-demystified/

https://support.citrix.com/article/CTX115575

# **Question 5**

**Question Type:** MultipleChoice

set gslb vServer-GSLB-1-MIR ENABLED

What will the Citrix ADC appliance send when the above command is executed?

### **Options:**

- A- The Remote GSLB service as the first record in the response and adds the remaining active services as additional records
- B- The Local GSLB service as the first record in the response and adds the remaining active services as additional records
- C- Only the best GSLB service in the response
- D- The best global server load balancing (GSLB) service as the first record in the response, and the remaining active services as additional records

#### **Answer:**

D

### **Explanation:**

https://docs.citrix.com/en-us/citrix-adc/current-release/global-server-load-balancing/how-to/protect-setup-against-failure.html

'if you enable multiple IP responses (MIR), the Citrix ADC appliance sends the best GSLB service as the first record in the response and adds the remaining active services as extra records.'

# **Question 6**

### **Question Type:** MultipleChoice

Which two protocols would provide end-to-end data encryption, while allowing a Citrix ADC to optimize the responses? (Choose two.)

### **Options:**

- A- HTTP protocol for the services
- B- SSL bridge protocol for the vServer
- C- SSL bridge protocol for the services
- **D-** SSL protocol for the services
- E- HTTP protocol for the vServer
- F- SSL protocol for the vServer

### **Answer:**

D, F

### **Explanation:**

https://docs.citrix.com/en-us/citrix-adc/current-release/ssl/how-to-articles/end-to-end-encrypt.html

# **Question 7**

### **Question Type:** MultipleChoice

Scenario: A Citrix Administrator manages an environment that has a Citrix ADC high availability (HA) pair running on two MPX appliances. The administrator notices that the state of the secondary Citrix ADC is 'Unknown'.

What is causing the secondary state to be 'Unknown'?

### **Options:**

- A- The synchronization on the secondary appliance is disabled.
- B- TCP port 22 is disabled between the primary and secondary ADCs.
- C- The administrator made both Citrix ADCs primary.
- D- The remote procedure call (RPC) nodes are incorrectly configured.

D	
Explanation:	
nttps://docs.citrix.com/en-	us/citrix-adc/current-release/system/high-availability-introduction/troubleshooting-high-availability.html
uestion 8	
destion 6	
estion Type: MultipleCho	ce
	ceives packets destined for a MAC address owned by the Citrix ADC. The destination IP address of the
Scenario: A Citrix ADC rec packets does NOT belong	ceives packets destined for a MAC address owned by the Citrix ADC. The destination IP address of the
Scenario: A Citrix ADC rec packets does NOT belong The Citrix ADC will	ceives packets destined for a MAC address owned by the Citrix ADC. The destination IP address of the to the Citrix ADC. Layer 3 mode is enabled by default on the Citrix ADC.
Scenario: A Citrix ADC rec packets does NOT belong	ceives packets destined for a MAC address owned by the Citrix ADC. The destination IP address of the to the Citrix ADC. Layer 3 mode is enabled by default on the Citrix ADC.
Scenario: A Citrix ADC recoackets does NOT belong	ceives packets destined for a MAC address owned by the Citrix ADC. The destination IP address of the to the Citrix ADC. Layer 3 mode is enabled by default on the Citrix ADC.

A- route			
B- process			
C- bridge			
C- bridge D- drop			
Answer:			
A			

### **Explanation:**

https://docs.citrix.com/en-us/citrix-adc/current-release/getting-started-with-citrix-adc/configure-system-settings/configure-modes-packet-forwarding.html

# **Question 9**

**Question Type:** MultipleChoice

Scenario: A load-balancing vServer is configured to utilize the least bandwidth load-balancing method. A service attached to this vServer is brought into the effective state during production hours.

Options:
A- Least connections
B- Least bandwidth
C- Custom load
D- Round-robin
Answer:
A
Explanation:
https://docs.citrix.com/en-us/citrix-adc/current-release/load-balancing/load-balancing-customizing-algorithms/leastconnection-method.html

During the startup of a vServer, which load-balancing method is used by default?

### To Get Premium Files for 1Y0-241 Visit

https://www.p2pexams.com/products/1y0-241

### **For More Free Questions Visit**

https://www.p2pexams.com/citrix/pdf/1y0-241

