



Free Questions for CV0-003 by actualtestdumps

Shared by Donovan on 07-06-2022

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

After accidentally uploading a password for an IAM user in plain text, which of the following should a cloud administrator do FIRST?

Options:

- A) Identify the resources that are accessible to the affected IAM user
- B) Remove the published plain-text password
- C) Notify users that a data breach has occurred
- D) Change the affected IAM user's password
- E) Delete the affected IAM user

Answer:

B

Question 2

Question Type: MultipleChoice

SIMULATION

The QA team is testing a newly implemented clinical trial management (CTM) SaaS application that uses a business intelligence application for reporting. The UAT users were instructed to use HTTP and HTTPS.

Refer to the application dataflow:

1A -- The end user accesses the application through a web browser to enter and view clinical data.

2A -- The CTM application server reads/writes data to/from the database server.

1B -- The end user accesses the application through a web browser to run reports on clinical data.

2B -- The CTM application server makes a SOAP call on a non-privileged port to the BI application server.

3B -- The BI application server gets the data from the database server and presents it to the CTM application server.

INSTRUCTIONS


You are a cloud engineer who is tasked with reviewing the firewall rules as well as virtual network settings.


You should ensure the firewall rules are allowing only the traffic based on the dataflow.

You have already verified the external DNS resolution and NAT are working.

Verify and appropriately configure the VLAN assignments and ACLs. Drag and drop the appropriate VLANs to each tier from the VLAN Tags table. Click on each Firewall to change ACLs as needed.


If at any time you would like to bring back the initial state of the simulation, please click the Reset All button.





Internet 

CNAME = ctm.app.com = cerberus.app.com
A = cerberus.app.com = 64.23.71.93

Virtual Switch 

Action	Source	Destination	Protocol	Port
ALLOW	192.168.1.51	192.168.2.15	TCP	88
DENY	192.168.1.52	0.0.0.0 127.0.0.1 64.23.71.93 192.168.1.51 192.168.1.52 192.168.2.15	TCP UDP ANY	80 88 443 1533 9400 ANY
DENY	192.168.2.15	192.168.2.24 192.168.3.24 192.168.4.125	UDP	ANY
DENY	192.168.2.15 192.168.2.24 192.168.3.24 192.168.4.125	0.0.0.0	TCP	443
DENY	192.168.4.125	0.0.0.0	ANY	ANY

Port Groups

- VLAN 100 = NLB
- VLAN 101 = CTM
- VLAN 102 = BI
- VLAN 103 = CA
- VLAN 104 = DB
- VLAN 105 = MGMT
- VLAN 106 = WEB

VLAN Tags

- VLAN 100
- VLAN 101
- VLAN 102
- VLAN 103
- VLAN 104
- VLAN 105
- VLAN 106

1A

2A

Reset Answer


Save


Close



Database Server
192.168.4.125

VLAN 105





Options:

A) On firewall 3, change the DENY 0.8.8.0 entry to rule 3 not rule 1.

B) On firewall 3, change the DENY 0.0.0.0 entry to rule 3 not rule 1.

Answer:

B

Question 3

Question Type: MultipleChoice

SIMULATION

A company has decided to scale its e-commerce application from its corporate datacenter to a commercial cloud provider to meet an anticipated increase in demand during an upcoming holiday.

The majority of the application load takes place on the application server under normal conditions. For this reason, the company decides to deploy additional application servers into a commercial cloud provider using the on-premises orchestration engine that installs and configures common software and network configurations.

The remote computing environment is connected to the on-premises datacenter via a site-to-site IPsec tunnel. The external DNS provider has been configured to use weighted round-robin routing to load balance connections from the Internet.

During testing, the company discovers that only 20% of connections completed successfully.

INSTRUCTIONS

Review the network architecture and supporting documents and fulfill these requirements:

Part 1:

Analyze the configuration of the following components: DNS, Firewall 1, Firewall 2, Router 1, Router 2, VPN and Orchestrator Server.

Identify the problematic device(s).


Part 2:


Identify the correct options to provide adequate configuration for hybrid cloud architecture.


If at any time you would like to bring back the initial state of the simulation, please click the Reset All button.


Part 1:

Cloud Hybrid Network Diagram













Orchestration Server	
Name	Basic_Server
Network	10.1.1.0/24
Name	Cloud_Server
Network	10.1.2.0/24
Name	Application_Server
Baseline	Basic_Server
Type	Webserver
Version	1.0
Name	Database_Server
Baseline	Basic_Server
Type	Database Server
Version	1.0
Name	Corporate_Datacenter
Baseline	Application_Server
Count	1









Part 2:

Only select a maximum of TWO options from the multiple choice question

- Deploy a Replica of the Database Server in the Cloud Provider.
- Update the PSK (Pre-shared key) in Router 2.
- Update the A record on the DNS from 2.2.2.2 to 1.1.1.1.
- Promote deny All to allow All in Firewall 1 and Firewall 2.
- Change the Address Space on Router 2.
- Change internal IP Address of Router 1.
- Reverse the Weight property in the two CNAME records on the DNS.
- Add the Application Server at on-premises to the Load Balancer.

Options:

- A)** Deploy a Replica of the Database Server in the Cloud Provider
- B)** Update the PSK (Pre-shared key) in Router 2
- C)** Update the A record on the DNS from 2.2.2.2 to 1.1.1.1.
- D)** Promote deny All to allow All in Firewall 1 and Firewall 2.
- E)** Change the Address Space on Router 2.
- F)** Change internal IP Address of Router 1
- G)** Reverse the Weight property in the two CNAME records on the DNS

H) Add the Application Server at on-premises to the Load Balancer.

Answer:

B, E

Explanation:

- * Change the Address Space on Router2
- * Update the PSK (Pre-shared key in Router2)

Question 4

Question Type: MultipleChoice

After accidentally uploading a password for an IAM user in plain text, which of the following should a cloud administrator do FIRST?

Options:

- A) Identify the resources that are accessible to the affected IAM user
- B) Remove the published plain-text password
- C) Notify users that a data breach has occurred
- D) Change the affected IAM user's password
- E) Delete the affected IAM user

Answer:

B

Question 5

Question Type: MultipleChoice

SIMULATION

A company has decided to scale its e-commerce application from its corporate datacenter to a commercial cloud provider to meet an anticipated increase in demand during an upcoming holiday.

The majority of the application load takes place on the application server under normal conditions. For this reason, the company decides to deploy additional application servers into a commercial cloud provider using the on-premises orchestration engine that installs and configures common software and network configurations.

The remote computing environment is connected to the on-premises datacenter via a site-to-site IPsec tunnel. The external DNS provider has been configured to use weighted round-robin routing to load balance connections from the Internet.

During testing, the company discovers that only 20% of connections completed successfully.

INSTRUCTIONS

Review the network architecture and supporting documents and fulfill these requirements:

Part 1:

Analyze the configuration of the following components: DNS, Firewall 1, Firewall 2, Router 1, Router 2, VPN and Orchestrator Server.

Identify the problematic device(s).


Part 2:


Identify the correct options to provide adequate configuration for hybrid cloud architecture.


If at any time you would like to bring back the initial state of the simulation, please click the Reset All button.


Part 1:

Cloud Hybrid Network Diagram













Orchestration Server	
Name	Basic_Server
Network	10.1.1.0/24
Name	Cloud_Server
Network	10.1.2.0/24
Name	Application_Server
Baseline	Basic_Server
Type	Webserver
Version	1.0
Name	Database_Server
Baseline	Basic_Server
Type	Database Server
Version	1.0
Name	Corporate_Datacenter
Baseline	Application_Server
Count	1









Part 2:

Only select a maximum of TWO options from the multiple choice question

- Deploy a Replica of the Database Server in the Cloud Provider.
- Update the PSK (Pre-shared key) in Router 2.
- Update the A record on the DNS from 2.2.2.2 to 1.1.1.1.
- Promote deny All to allow All in Firewall 1 and Firewall 2.
- Change the Address Space on Router 2.
- Change internal IP Address of Router 1.
- Reverse the Weight property in the two CNAME records on the DNS.
- Add the Application Server at on-premises to the Load Balancer.

Options:

- A)** Deploy a Replica of the Database Server in the Cloud Provider
- B)** Update the PSK (Pre-shared key) in Router 2
- C)** Update the A record on the DNS from 2.2.2.2 to 1.1.1.1.
- D)** Promote deny All to allow All in Firewall 1 and Firewall 2.
- E)** Change the Address Space on Router 2.
- F)** Change internal IP Address of Router 1
- G)** Reverse the Weight property in the two CNAME records on the DNS

H) Add the Application Server at on-premises to the Load Balancer.

Answer:

B, E

Explanation:

- * Change the Address Space on Router2
- * Update the PSK (Pre-shared key in Router2)

Question 6

Question Type: MultipleChoice

SIMULATION

The QA team is testing a newly implemented clinical trial management (CTM) SaaS application that uses a business intelligence application for reporting. The UAT users were instructed to use HTTP and HTTPS.

Refer to the application dataflow:

1A -- The end user accesses the application through a web browser to enter and view clinical data.

2A -- The CTM application server reads/writes data to/from the database server.

1B -- The end user accesses the application through a web browser to run reports on clinical data.

2B -- The CTM application server makes a SOAP call on a non-privileged port to the BI application server.

3B -- The BI application server gets the data from the database server and presents it to the CTM application server.

INSTRUCTIONS


You are a cloud engineer who is tasked with reviewing the firewall rules as well as virtual network settings.


You should ensure the firewall rules are allowing only the traffic based on the dataflow.

You have already verified the external DNS resolution and NAT are working.

Verify and appropriately configure the VLAN assignments and ACLs. Drag and drop the appropriate VLANs to each tier from the VLAN Tags table. Click on each Firewall to change ACLs as needed.

If at any time you would like to bring back the initial state of the simulation, please click the Reset All button.





Internet

CNAME = ctm.app.com = cerberus.app.com
A = cerberus.app.com = 64.23.71.93

Virtual Switch

Action	Source	Destination	Protocol	Port
ALLOW	192.168.1.51	192.168.2.15	TCP	88
DENY	192.168.1.52	0.0.0.0 127.0.0.1 64.23.71.93 192.168.1.51 192.168.1.52 192.168.2.15 192.168.2.24 192.168.3.24 192.168.4.125	TCP UDP ANY	80 88 443 1533 9400 ANY
DENY	0.0.0.0 127.0.0.1 64.23.71.93 192.168.1.51 192.168.1.52 192.168.2.15 192.168.2.24 192.168.3.24 192.168.4.125	192.168.2.15	UDP	ANY
DENY	192.168.2.15 192.168.2.24 192.168.3.24 192.168.4.125	0.0.0.0	TCP	443
DENY	192.168.4.125	0.0.0.0	ANY	ANY

Port Groups

- VLAN 100 = NLB
- VLAN 101 = CTM
- VLAN 102 = BI
- VLAN 103 = CA
- VLAN 104 = DB
- VLAN 105 = MGMT
- VLAN 106 = WEB

VLAN Tags

- VLAN 100
- VLAN 101
- VLAN 102
- VLAN 103
- VLAN 104
- VLAN 105
- VLAN 106


1A


2A

Reset Answer Save Close

Database Server
192.168.4.125

VLAN 105





Options:

A) On firewall 3, change the DENY 0.8.8.0 entry to rule 3 not rule 1.

B) On firewall 3, change the DENY 0.0.0.0 entry to rule 3 not rule 1.

Answer:

B

To Get Premium Files for CV0-003 Visit

<https://www.p2pexams.com/products/cv0-003>

For More Free Questions Visit

<https://www.p2pexams.com/comptia/pdf/cv0-003>

