



Free Questions for [DES-5221](#) by [vceexamstest](#)

Shared by [Vang](#) on [15-04-2024](#)

For More Free Questions and Preparation Resources

[Check the Links on Last Page](#)

Question 1

Question Type: MultipleChoice

Which command shows whether a LAG protocol is static or dynamic on a Dell EMC Networking OS10 switch?

Options:

- A- show lacp neighbor
- B- show running-configuration lacp
- C- show interface port-channel summary
- D- show port-channel summary

Answer:

D

Explanation:

https://topics-cdn.dell.com/pdf/force10-s4048-on_reference-guide6_en-us.pdf

Question 2

Question Type: MultipleChoice

Which LSA type contains information about routes redistributed into OSPF?

Options:

A- 3

B- 10

C- 5

D- 8

Answer:

C

Question 3

Question Type: MultipleChoice

Which switch mode is used to manage files and display switch information?

Options:

A- Interface

B- Network

C- Exec

D- Configuration

Answer:

C

Question 4

Question Type: MultipleChoice

Refer to the exhibit.

```
OS10# show ip pim tib
```

```
PIM Multicast Routing Table
```

```
Flags: S - Sparse, C - Connected, L - Local, P - Pruned,  
       R - RP-bit set, F - Register Flag, T - SPT-bit set, J - Join SPT,  
       K - Ack-Pending state
```

```
Timers: Uptime/Expires
```

```
Interface state: Interface, next-Hop, State/Mode
```

```
(*, 239.255.255.250), uptime 21:30:30, expires 00:00:00, RP 10.0.14.1 , flags: SC
```

```
Incoming interface: Null, RPF neighbor 0.0.0.0
```

```
Outgoing interface list:
```

```
  vlan300 Forward/Sparse 21:30:30/Never
```

```
  ethernet1/1/54 Forward/Sparse 21:30:30/00:03:07
```

```
( 10.0.13.1 , 239.255.255.250), uptime 02:36:13, expires 00:00:00, flags: CJ
```

```
Incoming interface: Null, RPF neighbor 0.0.0.0
```

```
Outgoing interface list:
```

```
  vlan100 Forward/Sparse 02:36:13/00:03:12
```

```
  ethernet1/1/54 Forward/Sparse 02:36:13/Never
```

Where is the rendezvous point for the group 239.255.255.250?

Options:

A- 10.0.13.1

B- 10.0.14.1

C- eth1/1/54

D- vlan300

Answer:

B

Question 5

Question Type: MultipleChoice

What is the default PIM-SSM IP range?

Options:

A- 224.0.0.0/4

B- 224.0.0.0/24

C- 232.0.0.0/8

D- 232.0.0.0/4

Answer:

C

Explanation:

https://www.dell.com/support/manuals/us/en/04/force10-z9500/z9500_9.9.0.0_cli_pub-v1/ip-pim-ssm-range?guid=guid-995ffbd6-412f-4b34-92d1-50bb254ae371&lang=en-us

Question 6

Question Type: MultipleChoice

Which LSA type provides information necessary to reach routers originating type 5 LSA's in other areas?

Options:

- A- ASBR-Summary (Type 4)
- B- Summary (Type 3)
- C- NSSA (Type 7)

D- Router (Type 1)

Answer:

A

Question 7

Question Type: MultipleChoice

What is the valid range of VLAN IDs for Dell EMC Networking OS10 switches?

Options:

A- 1-4096

B- 1-4093

C- 0-4092

D- 0-4095

Answer:

B

Explanation:

<https://www.karma-group.ru/upload/iblock/3d5/Dell%20Networking%20OS10.pdf>

Question 8

Question Type: MultipleChoice

What is the default lease time in hours for an address lease in DHCP?

Options:

A- 36

B- 12

C- 48

D- 24

Answer:

D

Explanation:

<https://www.dell.com/support/manuals/us/en/04/force10-s4048-on/os10-enterprise-user-guide-pub/automatic-address-allocation?guid=guid-9bc516cf-79b2-434f-a8e7-e6560c37c450&lang=en-us>

Question 9

Question Type: MultipleChoice

When the show ip bgp neighbors command is issued, which BGP state reflects a successfully created adjacency with another BGP peer?

Options:

- A- ESTABLISHED
- B- PEERING
- C- ACTIVE

D- CONNECTED

Answer:

A

Question 10

Question Type: MultipleChoice

What is the size of the VLAN tag in an Ethernet frame?

Options:

A- 4 bytes

B- 8 bytes

C- 1 byte

D- 2 bytes

Answer:

A

Question 11

Question Type: MultipleChoice

What are the correct steps to configure a static LAG on a Dell Networking OS10 switch?

Options:

- A-** interface port-channel 4 channel-group 4 mode passive
interface range ethernet 1/1/14-1/1/15 channel-group 4 mode on
- B-** interface port-channel 4 channel-group 4 mode on
interface range ethernet 1/1/14-1/1/15 channel-group 4 mode passive
- C-** interface port-channel 4 no shutdown
interface range ethernet 1/1/14-1/1/15 channel-group 4 mode on
- D-** interface port-channel 4 no shutdown
interface range ethernet 1/1/14-1/1/15 channel-group 4 mode active

Answer:

C

Question 12

Question Type: MultipleChoice

Refer to the exhibit.

```
Router (Area 0.0.0.0)
Link ID          ADV Router      Age           Seq#
-----
10.0.1.1         10.0.1.1        1411          0x800000D5
10.0.1.2         10.0.1.2        320           0x800000D2
10.0.2.2         10.0.2.2        1130          0x800000CF

Network (Area 0.0.0.0)
Link ID          ADV Router      Age           Seq#
-----
192.168.100.3   10.0.2.2        1269          0x800000CD
192.168.200.3   10.0.2.2        1130          0x800000CD

Type-5 AS External
Link ID          ADV Router      Age           Seq#
-----
10.0.1.1         10.0.1.1        1175          0x80000001
144.254.32.0     10.0.1.1        1175          0x80000001
144.254.33.0     10.0.1.1        1175          0x80000001
192.168.37.0     10.0.1.1        1050          0x80000001
192.168.100.2    10.0.1.1        1175          0x80000001
S3(config-router-ospf-1)#
```

The output shown is from which command?

Options:

- A- S3(config-router-ospf-1)# show ip ospf database
- B- S3(config-router-ospf-1)# show ip ospf topology
- C- S3(config-router-ospf-1)# show ip ospf lsa
- D- S3(config-router-ospf-1)# show ip ospf statistics

Answer:

A

To Get Premium Files for DES-5221 Visit

<https://www.p2pexams.com/products/des-5221>

For More Free Questions Visit

<https://www.p2pexams.com/dell-emc/pdf/des-5221>

