



Download NetApp NS0-184 Exam Dumps Free

Shared by Maddox on 17-06-2026

For More Free Questions and Preparation Resources

Check the Links on Last Page



Question 1

Question Type: MultipleChoice

A customer wants to enable SnapMirror Synchronous across their environment. The customer must ensure that SnapMirror Synchronous will work across the environment.

In this scenario, which two statements are true? (Choose two.)

Options:

- A- A SnapMirror license is required on both the source cluster and the destination cluster.
- B- A SnapMirror Synchronous license is required on both the source and destination clusters.
- C- A SnapMirror license is not required on both the source cluster and the destination cluster.
- D- A SnapMirror Synchronous license is required on the source cluster.

Answer:

B, C

Question 2

Question Type: MultipleChoice

Which logical interface has a fixed firewall policy?

Options:

- A- data LIF
- B- cluster management LIF
- C- cluster LIF
- D- intercluster LIF

Answer:

C

Question 3

Question Type: MultipleChoice

After moving a new AFF A400 cluster into production, the administrator notices error events in ONTAP System Manager regarding SAS HA issues.

In this scenario, which NetApp tool would have identified these errors after the installation process?

Options:

- A- Cloud Manager
- B- ONTAP System Manager
- C- Active IQ Config Advisor
- D- Active IQ Unified Manager



Answer:

B

Question 4

Question Type: MultipleChoice

You are installing a new six-node ONTAP 9.8 cluster. You have completed the initial configuration of the cluster interconnect switches and the ONTAP cluster.

In this scenario, which feature should you enable?

Options:

- A- cluster switch logging
- B- cluster switch health monitor
- C- IPv6 on all cluster ports
- D- data center bridging protocol



Answer:

B

Question 5

Question Type: MultipleChoice

Click the Exhibit button.

```

cluster1::> network interface show
Vserver      Logical      Status      Network      Current      Current      Is
Interface    Admin/Oper  Address/Mask Node          Port         Home
-----
Cluster
cluster1-01_clus1
                up/up      169.254.145.151/16 cluster1-01  e0a         true
cluster1-01_clus2
                up/up      169.254.58.159/16 cluster1-01  e0b         true
cluster1-02_clus1
                up/up      169.254.110.0/16 cluster1-02  e0a         true
cluster1-02_clus2
                up/up      169.254.212.198/16 cluster1-02  e0b         true
cluster1
cluster1-01_mgmt1
                up/up      192.168.0.111/24 cluster1-01  e0c         true
cluster1-02_mgmt1
                up/up      192.168.0.112/24 cluster1-02  e0c         true
cluster_mgmt up/up      192.168.0.101/24 cluster1-01  e0c         true

```

You are installing a new AFF All SAN Array A700 HA pair.

Referring to the exhibit, which IP address would have been used to join node 02 to the cluster during setup?

Options:

- A- 192.168.0.112
- B- 169.254.212.198
- C- 169.254.145.151
- D- 192.168.0.101

Answer:

A

Question 6

Question Type: MultipleChoice

Which command would be used to measure the throughput and latency of traffic between nodes?

Options:

- A- qos statistics workload performance show

- B- cluster ping-cluster
- C- network test-path
- D- statistics node show

Answer:

C

Question 7

Question Type: MultipleChoice

A customer is creating a new SVM to host iSCSI LUNs for a Hyper-V cluster. You need to successfully map the new LUNs and make them visible to the Hyper-V cluster.

In this scenario, which host information is required to accomplish this task?

Options:

- A- IQNs
- B- WWNNs
- C- WWPNS
- D- host names

Answer:

D

Question 8

Question Type: MultipleChoice

You installed two separate clusters in an isolated data center without outbound network access. The customer wants to troubleshoot issues locally and also create custom Excel reports for capacity utilization from a local server.

In this scenario, which NetApp tool would satisfy this requirement?

Options:

- A- Active IQ Digital Advisor

- B- Active IQ Unified Manager
- C- Cloud Insights
- D- ONTAP System Manager

Answer:

B

Question 9

Question Type: MultipleChoice

Your customer plans to expand a 2-node FAS2750 switched cluster with two new controllers.

In this scenario, which two prerequisites should you examine in advance? (Choose two.)

Options:

- A- Verify that the hard drives of the new controllers are compatible with the old controllers.
- B- Verify that the existing cluster has a minimum 10 GB of free space for root volumes.
- C- Verify that the existing switches support the additional controllers.
- D- Verify that the platform of the new controllers can be mixed with the cluster's existing controllers.

Answer:

B, D



To Get Premium Files for NS0-184 Visit

<https://www.p2pexams.com/products/ns0-184>

For More Free Questions Visit

<https://www.p2pexams.com/netapp/pdf/ns0-184>

20%
DISCOUNT

P2P
exams