



Download Oracle 1Z0-106 Exam Dumps Free

Shared by Foster on 17-06-2026

For More Free Questions and Preparation Resources

Check the Links on Last Page



Question 1

Question Type: MultipleChoice

Examine these commands executed by root:

```
# mkdir -p /jail /jail/bin /jail/lib64
# cp $(which bash) /jail/bin/
# ldd $(which bash)
linux-vdso.so.1 (0x00007ffd574f5000)
libtinfo.so.6 => /lib64/libtinfo.so.6 (0x00007fb458c2c000)
libdl.so.2 => /lib64/libdl.so.2 (0x00007fb458a28000)
libc.so.6 => /lib64/libc.so.6 (0x00007fb458666000)
/lib64/ld-linux-x86-64.so.2 (0x00007fb459177000)
# cp /lib64/libtinfo.so.6 /jail/lib64/
# cp /lib64/libdl.so.2 /jail/lib64/
# cp /lib64/libc.so.6 /jail/lib64/
# cp /lib64/ld-linux-x86-64.so.2 /jail/lib64/
# chroot /jail
```

What is the output from the cd, pwd, and ls commands?

Options:

A- bash-4.4# cd

bash: cd: /root: No such file or directory

bash-4.4# pwd

/

bash-4.4# ls

bin lib64

B- bash-4.4# cd

bash: cd: /root: Unable to access chrooted file or directory /root

bash-4.4# pwd

/

bash-4.4# ls

bin lib64

```
C- bash-4.4# cd
bash: cd: /root: No such file or directory
bash-4.4# pwd
/root
bash-4.4# ls
bash: ls: command not found
D- bash-4.4# cd
bash: cd: command not found
bash-4.4# pwd
bash: pwd: command not found
bash-4.4# ls
bash: ls: command not found
```

Answer:

A

Question 2

Question Type: MultipleChoice

Examine the contents of the /etc/exports file on an NFS server:

```
/status *(rw,async)
```

```
/usr/shared/tools *(all-squash,anonuid=501,anongid=501,ro)
```

```
/projects/big *(ro) pteam(rw)
```

The NFS server exports /usr/shared/tools to NFS clients. Which statement is true?

Options:

- A- All clients except those with a local 501 user can mount /usr/shared/tools read-only.
- B- All clients can mount /usr/shared/tools read-only and NFS explicitly maps all requests to the UID and GID of the privileged local 501 user.
- C- All clients can mount /usr/shared/tools read-only and NFS explicitly maps all requests to the UID and GID of the unprivileged local 501 user.
- D- All clients can mount /usr/shared/tools read-only and all-squash overrides explicit mapping of the UID and GID defined by anonuid and anongid.
- E- All clients can mount /usr/shared/tools read-only and NFS ignores the directives defined by the anonuid and anongid options.

Answer:

C

Question 3

Question Type: MultipleChoice

Which are three of the network bonding modes supported in Oracle Linux 8?

Options:

- A- Multicast
- B- Round-robin
- C- Split Horizon
- D- 802.3ad
- E- Poison Reverse
- F- Active Backup
- G- Passive Backup

Answer:

B, D, F

Question 4

Question Type: MultipleChoice

Which two statements are true about systemd system and service manager?

Options:

- A- systemd service units expose kernel devices and can be used to implement device-based activation.
- B- systemd is the first process that starts after the system boots and is the final process left running before the system shuts down.
- C- systemd is backward-compatible with the System V init scripts that were used in earlier versions of Oracle Linux.
- D- systemd reads /etc/system to determine which services to start.
- E- The service command is used to start and stop system service units.

Answer:

A, B

Question 5

Question Type: MultipleChoice

Examine this network configuration:

NAME="ens4"

DEVICE="ens4"

ONBOOT=no

NETBOOT=yes

IPV6INIT=yes

BOOTPROTO=none

IPADDR=192.168.2.5

PREFIX=24

GATEWAY=192.168.2.1

TYPE=Ethernet

Which two statements are true after executing `nmcli con mod ens4 ipv4.method auto`?

Options:

- A- Interface ens4 automatically starts on boot.
- B- BOOTPROTO value is set to dhcp.
- C- ONBOOT value is set to yes.
- D- IPADDR value is considered null.
- E- ONBOOT value is set to dhcp.
- F- Interface ens4 is assigned an IP address of 192.168.2.5.

Answer:

B, C

Question 6

Question Type: MultipleChoice

Which command configures a fully functional and accessible interface on VLAN 800?

Options:

- A- modprobe 8021q ip link add link eth0 name eth0.800 type vlan id 800 ip link set eth0.800 up
- B- modprobe 8021q ip link add link eth0 name eth0.800 VLAN 800 ip address add 10.135.1.120/24 dev eth0.800 ip link set eth0.800 up
- C- modprobe 8021q ip link add link eth0 name eth0.800 type vlan id 800 ip address add 10.135.1.120/24 dev eth0.800 ip link set eth0.800 up
- D- modprobe 8021q ip address add 10.135.1.120/24 dev eth0.800 ip link set eth0.800 up

Answer:

C

Question 7

Question Type: MultipleChoice

Examine this output:

Last metadata expiration check: 4:30:21 ago on Mon 26 Oct 2020 03:09:52 PM GMT

Installed Packages

Name : gzip

Release : 9.el8

Architecture : x86_64

Size : 412 k

Source : gzip-1.9-9.el8.src.rpm

Repository : @System

From repo : anaconda

Summary : The GNU data compression program

URL : <http://www.gzip.org/>



License : GPLv3+ and GFDL

Description : The gzip package contains the popular GNU gzip data compression program. Gzipped files have a .gz extension.

Gzip should be installed on your system, because it is a very commonly used data compression program.

Which command generated it?

Options:

- A- dnf list /usr/bin/gzip
- B- dnf provides /usr/bin/gzip
- C- dnf info /usr/bin/gzip
- D- dnf search /usr/bin/gzip

Answer:

C



To Get Premium Files for 1Z0-106 Visit

<https://www.p2pexams.com/products/1z0-106>

For More Free Questions Visit

<https://www.p2pexams.com/oracle/pdf/1z0-106>

20%
DISCOUNT

P2P
exams