



Free Questions for 300-810 by dumpssheet

Shared by Singleton on 18-01-2024

For More Free Questions and Preparation Resources


Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Refer to the exhibit.

Image not found or type unknown



Refer to the exhibit. After receiving a new desk phone, the Jabber user can no longer make calls via phone control. The help desk collected the user's Jabber problem report and verified that they the correct Cisco UCM CTI permissions. Which configuration must be changed to correct this issue?

Options:

- A) Verify that the desk phone device has Allow Control of Device from CTI enabled.
- B) Verify that the Cisco UCM service profile has Cisco UCM CTI servers configured.
- C) Verify that the user's desk phone device is listed as a controlled device in the Cisco UCM end user configuration
- D) Verify that the device line configuration has Allow Control of Device from CTI enabled.


Answer:

A

Question 2

Question Type: MultipleChoice

Refer to the exhibit.



Refer to the exhibit. Cisco UCM is integrated with Cisco Unity connection via a SIP trunk and is configured using a globalized dial plan (directory numbers are configured with "+*"). Using Cisco best practices, which implementation allows call transfers to internal directory numbers but not to PSTN numbers?

Options:

- A) remove PSTN-PT from voicemail_CSS
- B) change the order of partitions to put GLOBAL-INTERNAL-PT first in Voicemail_CSS
- C) create a BLOCK-PSTN-PT partition and add it to Voicemail_CSS
- D) block pattern +* in the Cisco Unity restriction table

Answer:

A

Question 3

Question Type: MultipleChoice

Refer to the exhibit.

Image not found or type unknown



Refer to the exhibit. An administrator is configuring a Cisco Unity Express call handler. One of the options will transfer calls off-system to Cisco UCME. The administrator wants the transfer to finish while the transfer target is ringing. Which transfer-mode command completes the configuration?

Options:

A) attended

B) blind refer

C) semi-attended

D) Wind bye-also

Answer:

C

Question 4

Question Type: MultipleChoice

Refer to the exhibit.

Image not found or type unknown



Refer to the exhibit A collaboration engineer is configuring Jabber for Windows in softphone mode inside the corporate firewall The engineer initially tests the client by manually setting the account type and the login server domain name Everything works as expected Next the engineer resets Jabber and attempts to log in using automatic settings and receives an error Which two items must be modified to resolve the issue? (Choose two.)

Options:

- A) DNS A record for _cisco-uds
- B) DNS SRV record for _collab-edge
- C) username portion of the login email
- D) domain portion of the login email
- E) DNS SRV record for _cisco-uds


Answer:

A, E

Question 5

Question Type: MultipleChoice

Refer to the exhibit.



Refer to the exhibit. An engineer is troubleshooting an issue with Cisco Jabber for Windows. The end-user reports that Cisco Jabber cannot be used to control a Cisco 8841 IP Phone. The phone appears in the Jabber client, but there is a red X on the icon for the phone. Which end-user option resolves the issue?

Options:

- A) Standard CTI Allow Reception of SRTP Key Material
- B) Standard CTI Allow Calling Number Modification
- C) Standard CTI Allow Call Monitoring
- D) Standard CTI Allow Control of Phones Supporting Rollover Mode


Answer:

D

Question 6

Question Type: MultipleChoice

Refer to the exhibit.



Refer to the exhibit A collaboration engineer is troubleshooting an issue where a user is reporting that instant messages are not reaching the intended recipient The engineer is unable to see the full instant message in the trace file In which trace in the transaction must the engineer resolve this issue?

Options:

- A) XCP Router
- B) Client Profile Agent
- C) Presence Engine
- D) XCP Connection Manager

Answer:

A

Question 7

Question Type: MultipleChoice

Refer to the exhibit.

Image not found or type unknown



Refer to the exhibit Users complain that the message waiting light on the IP phone does not light up when receiving a new voicemail
With which codec must the engineer configure a dial peer on Cisco UCME for MW1 traffic to resolve this issue?

Options:

- A) G.729r8
- B) G.729ar8
- C) G.711ulaw
- D) G.711alaw


Answer:

C

Question 8

Question Type: MultipleChoice

Refer to the exhibit.



Refer to the exhibit. An engineer assists a user who reports that the voicemail notifications show correctly on the desk phone are not available in the jabber client. Which action resolves this issue?

Options:

- A) Reset the Jabber client and have the user sign in again
- B) Set the voicemail profile on the user's line on the CSF device.
- C) Configure the voicemail profile on the user's service profile
- D) Ensure that the voicemail server is listed in the user's CTI profile

Answer:


C

Question 9

Question Type: MultipleChoice

Refer to the exhibit.

Image not found or type unknown



Refer to the exhibit. An administrator is configuring the auto-attendant script for a Cisco Unity Express Integration to Cisco UCME and wants to play the "busOpenprompt" wave file when it is not a holiday. How should the script be configured to accomplish this goal?

Options:

- A) Check the Business Hours only if the 'Is Holiday' prompt returns a 'Yes'.
- B) Swap me Open and Closed branches in the script.
- C) Check the Business Hours only if the 'Is Holiday' prompt returns a 'No'.
- D) Swap the "busOpenPrompt" with "busclosedPrompt".


Answer:

C

Question 10

Question Type: MultipleChoice

Refer to the exhibit.



Refer to the exhibit. A collaboration engineer restored a failed primary node of an active/standby IM and presence subcluster. The engineer notices that users fallback to the node occurred. Which action resolves this issue?

Options:

- A) Reboot the primary node
- B) Wait for the primary node to establish 30 minutes of uptime
- C) Modify the Client Re-Login Limits
- D) Set the Keep-Alive (Heartbeat) interval to 15.


Answer:

B

Question 11

Question Type: MultipleChoice

Refer to the exhibit.



Refer to the exhibit A collaboration engineer is troubleshooting a Cisco Jabber for Windows client issue. The end user is reporting that they cannot control the desk phone from the Cisco Jabber client Which action must the engineer take to resolve this issue?

Options:

- A) Associate the User with the desk phone under the user configuration page on Cisco UCM
- B) Select 'Primary Line' under the user configuration page on Cisco UCM
- C) Add the 'Allow control of the device from the CTI' option under the client services profile configuration page
- D) Add the 'Allow control of the device from the CTI' option under the desk phone configuration page

Answer:

D

To Get Premium Files for 300-810 Visit

<https://www.p2pexams.com/products/300-810>

For More Free Questions Visit

<https://www.p2pexams.com/cisco/pdf/300-810>

