

Free Questions for H11-851_V3.0 by dumpssheet

Shared by Boone on 05-09-2022

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

IdeaHub does not support audio output through an external DMI display. ()

Options:

A) True

B) False

Answer:

В

Question 2

Question Type: MultipleChoice

IdeaHub's negative one-screen welcome message can be configured on the web interface.

Options:	
A) True	
B) False	
Answer:	
A	
_	
Questio	n 3
uestion Type:	MultipleChoice
uestion Type:	MultipleChoice
	eries terminals support wired and wireless sharing of materials.()
C1oudLink s	
C1oudLink s	
C1oudLink s Options: A) True	
C1oudLink s Options: A) True	

Question 4

Question Type: MultipleChoice

The multi-stream forwarding conference only completes the video forwarding on the MCU port side, and does not need to perform video codec conversion. The terminal side completes the video codec and multi-screen layout.()

Options:

- A) True
- B) False

Answer:

Α

Question 5

Question Type: MultipleChoice

CANCEL transaction can only be sent after receiving the temporary response of INVITE (including 100) and before the final response.()
Options:
A) True
B) False
Answer:
A
Question 6
Question Type: MultipleChoice
SIP alone cannot complete multimedia calls. It must be combined with other protocols to form a complete multimedia communication system, and cooperate with protocols such as RTP/RTCP and SDP to complete the multimedia conversation process.
Options:
•

A) True	
B) False	
Answer:	
A	
Question 7	
Question Type: MultipleChoice	
MCU uses H.323 registration	n, when using a number to call a terminal, it needs to initiate a request to Gk.()
Options:	
A) True	
B) False	
Answer:	
Answer:	

Question 8

Question Type: MultipleChoice

The number of participants in large-capacity meetings is large, so the demand for interactive communication is the highest.()

Options:

- A) True
- B) False

Answer:

В

Question 9

Question Type: MultipleChoice

The main indicator describing video clarity is resolution, and the main indicator describing video fluency is frame rate.()

Options:

- A) True
- B) False

Answer:

Α

Question 10

Question Type: MultipleChoice

Regarding C1oudRSE, which of the following descriptions is correct?()

Options:

- A) The C1oudRSE power supply supports 1+1 hot backup, and seamlessly switches to the backup power supply in the event of a failure to ensure continuous and reliable recording.
- B) CloudRSE supports both HD and SD resolutions, and you can only use your computer to watch on-demand and live broadcast.
- C) CloudRSE can provide single-stream and dual-stream (video image + meeting data sharing) recording and broadcasting of video

conferences.	
D) CloudRSE supports resource pool management. CloudRSE in the resource mutually backup.	e pool is mutually backup, and resource pools cannot be
Answer:	
A, C, D	
Explanation:	
True or False	
Question 11	
Question Type: MultipleChoice	
Regarding adding MCU to the SMC3.0 web interface, which of the following of	descriptions is correct?()
Ontions:	
Options:	
Options:	

- A) If you need to add the MCU to the SMC3.0, it is recommended to restore the factory configuration of the MCU before adding it.
- B) When adding MCU to SMC3.0, you only need to fill in the docking account and password on SMC3.0, not on MCU.
- C) The networking mode of the 98 series MCU is SMC2.0 by default and needs to be modified to SMC.
- D) VP96 series MCU does not support adding to SMC3.0

Answer:

B, C

To Get Premium Files for H11-851_V3.0 Visit

https://www.p2pexams.com/products/h11-851_v3.0

For More Free Questions Visit

https://www.p2pexams.com/huawei/pdf/h11-851-v3.0

