Question 1

Question Type: **MultipleChoice**

Switches run the MSTP protocol by default. Which of the following statements regarding the default status is true?

Options:

A- All switches run in the same region by default.

B- The STP calculation speed is faster than that when multiple instances are configured.

C- Due to lack of configuration, all switches switch the running mode to RSTP.

D- Each switch runs in an independent region.

Answer:

D

Question 2

Question Type: **MultipleChoice**

A user reported a failure to receive emails through the email client. Which of the following are possible causes? (Multiple Choice)

Options:

A- The user does not have the required rights.

B- The email server is faulty.

C- The link is faulty.

D- The client settings are incorrect.

Answer:

A, B, C, D

Question 3

Question Type: MultipleChoice

Which of the following statements regarding NMS usage are true? (Multiple Choice)

Options:

A- The NMS supports alarm management. For example, the Up/Down change of a port can be immediately reported to the NMS through trap, so that the network administrator can discover and rectify network faults in a timely manner.

B- The NMS supports performance management. It automatically collects statistics about the CPU usage and memory usage of devices, helping the network administrator analyze network performance bottlenecks.

C- The NMS supports configuration file management, including automatically backing up, comparing, and restoring the configuration file, allowing the network administrator to configure automatic batch configuration file backup.

D- Based on user requirements, the NMS can generate reports periodically, providing reference for subsequent network optimization.

Answer:

A, B, C, D

Question 4

Question Type: MultipleChoice

Huawei's USG6X00 series firewalls belong to the UTM firewall product and support stateful inspection packet filtering as well as intrusion detection, anti-virus, and URL filtering.

Options:

A- TRUE

B- FALSE

Answer:

B

Question 5

Question Type: MultipleChoice

, well behaved, and appropriate in language use. When communicating with customers, Huawei engineers need to be groomed

Options:

A- TRUE

B- FALSE

Answer:

A

Question 6

Which of the following operations is unnecessary to resolve a failure for hosts in the same VLAN to communicate with each other?

Options:

A- Run the display interface interface-type interface-number command in any view to check the status of communication interfaces.

B- Run the display mac-address command on the switch to check MAC address entries including the MAC address, port number, and VLAN ID.

C- Run the display vlan vlan-id command in any view to check whether the VLAN for communication interfaces has been created.

D- Run the display current-configuration command to check the PCB version and the software version of a card.

Answer:

D

Question 7

On a Layer 2 switching network devices forward data based on MAC addresses. Therefore, data filtering can be performed based on MAC addresses, and a firewall in transparent cannot filter out Layer 3 information in data packets.

Options:

A- TRUE

B- FALSE

Answer:

B

To Get Premium Files for H12-223 Visit

https://www.p2pexams.com/products/h12-223

For More Free Questions Visit

https://www.p2pexams.com/huawei/pdf/h12-223

20% DISCOUNT