

Free Questions for DES-4122 by go4braindumps

Shared by Benson on 12-12-2023

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Which mobile devices are supported by Quick Sync 2.0 in 14G PowerEdge servers?

Options:

A- Android devices only

- B- iOS, Android, and Windows Phone devices
- C- iOS and Android devices only
- D- iOS devices only

Answer:

С

Explanation:

Topic 2, Exam Part 2 Performance based Simulation

Question 2

Question Type: MultipleChoice

A Dell EMC PowerEdge server has been updated with an LCC and iDRAC DUP to the latest firmware when performing a firmware rollback?

Options:

- A- Both the iDRAC and the LCC can be rolled back
- B- The LCC can be rolled back; the iDRAC cannot be rolled back
- C- The iDRAC can be rolled back; the LCC cannot be rolled back
- D- The iDRAC cannot be rolled back and the LCC cannot be rolled back

Answer:

А

Question 3

Question Type: MultipleChoice

What is a key distinction between 1DRAC8 and 1DRAC9?

Options:

- A- iDRAC9 offers HTML5 based GUI
- B- iDRAC9 default credentials are root/calvin orderable only
- C- iDRAC8 offers HTML5 based GUI
- D- iDRAC8 default credentials are customer orderable

Answer:

D

Question 4

Question Type: MultipleChoice

What is a systems management console solution optimized for monitoring and managing Dell enterprise and remote office hardware?

Options:

A- SupportAssist Enterprise

B- iSM

C- OpenManage Essentials

D- iDRAC9

Answer:

А

Question 5

Question Type: MultipleChoice

An engineer is checking a newly delivered Dell EMC PowerEdge R640 server that will be deployed for a new database environment

The inventory consists of:

1 PowerEdge R640 Server
1 Hot-plug Power Supply, 750W - qty 1
Jumper Cord - C13/C14, 4M, 250V, 10A - qty 1
Broadcom 57412 Dual Port 10GbE SFP+ and 5720 Dual Port 1GbE BASE-T rNDC - qty 1
SFP+ SR Optic, 10GbE - qty 2
Dell Networking, Cable, SFP+ to SFP+, 10GbE, Copper Twinax DAC, 3 Meter - qty 2
CAT6 Patch cable 5 Meters - qty 2

The server power configuration will be set for gnd redundancy The management switch is 1000 Base-T and the top of rack switches 10Gb

What additional component(s) is needed for this configuration?

Options:

- A- Hot-plug power supply, 750 W qty 1
- B- Hot-plug power supply, 1100W qty 1
- C- Dell Networking, cable, 40GbE (QSFP+) to 4 x 10GbE SFP+ passive copper breakout cable, 3 meters qty 2

D- C20 to C21, PDU style, 250 V, 16 Amp, 3 5 meters power cord - qty 2

Answer:

А

Question 6

Question Type: MultipleChoice

A technician is sent on-site to troubleshoot a server that produced an error message during the most recent POST, but then completed the POST and booted to the operating system. The user cannot remember the specific error and no entry was made in the error log relating to this error.

How can the technician find out what the error message was?

Options:

- A- Access the Lifecycle Controller and view the last boot cycle video capture entry
- B- Reload the BIOS firmware
- C- Export the Server profile and analyze for any POST errors
- D- Access the iDRAC and view the last boot cycle video capture entry

Answer:

D

Question 7

A technician installs eight servers into a fully operational rack with top of rack switch Each server has a quad 1Gb NIC and redundant power supplies The company uses iDRAC in shared LOM mode with LOM1 as the selected NIC

What should the technician do to verify iDRAC connectivity on each server?

Options:

A- iDRAC Datacenter license is installed.

- **B-** Ethernet port LOM1 is cabled and the link light is green.
- C- iDRAC dedicated NIC port is cabled and the link light is green
- D- iDRAC Enterprise license is installed

Answer:

В

To Get Premium Files for DES-4122 Visit

https://www.p2pexams.com/products/des-4122

For More Free Questions Visit

https://www.p2pexams.com/dell-emc/pdf/des-4122

