

# **Free Questions for HPE6-A75 by ebraindumps**

# Shared by Mendoza on 06-06-2022

**For More Free Questions and Preparation Resources** 

**Check the Links on Last Page** 

#### **Question Type:** MultipleChoice

A university wants to deploy ClearPass with the Guest module. They have two types of users that need to use web login authentication. The first type of users are students whose accounts are in an Active Directory server. The second type of users are friends of students who need to self-register to access the network.

How should the service be setup in the Policy Manager for this Network?

### **Options:**

- A- Guest User Repository and Active Directory server both as authentication sources
- B- Active Directory server as the authentication source, and Guest User Repository as the authorization source
- C- Guest User Repository as the authentication source, and Guest User Repository and Active Directory server as authorization sources
- D- Either the Guest User Repository or Active Directory server should be the single authentication source
- E- Guest User Repository as the authentication source and the Active Directory server as the authorization source

### Answer:

A

Refer to the exhibit.

	Conditions	Role Name
1	(Authorization:remotelab AD:Department EQUALS Product Management) OR (Authorization:remotelab AD:UserDN EQUALS Executive)	Executive
2	. (Authorization: [Endpoints Repository]: OS Family EQUALS_IGNORE_CASE Windows)	Vendor
3	(Authorization: [Endpoints Repository]: Category CONTAINS SmartDevice) AND (Authorization: [Endpoints Repository]: OS Family EQUALS_IGNORE_CASE Apple)	iOS Device
4	(Authorization: remotelab AD: UserDN EXISTS )	[Employee]
5	(Authorization:remotelab AD:Department EQUALS HR) OR (Connection:NAD-IP-Address BELONGS_TO_GROUP HQ) OR (Date:Day-of-Week NOT_BELONGS_TO Saturday, Sunday)	HR Local
6	(Host:OSType CONTAINS Fedora) OR (Host:OSType CONTAINS Redhat) OR (Host:OSType CONTAINS Ubuntu)	Linux User
7	. (Connection:NAD-IP-Address BELONGS_TO_GROUP Remote NAD)	Remote Employee

Exhibit:accp67-236

An AD user's department attribute is configured as \*HR". The user connects on Monday using their Windows Laptop to a switch that belongs to the Device Group HQ. Which role is assigned to the user in ClearPass?

### **Options:**

A- Executive	
B- iOS Device	
C- Vendor	
D- Remote Employee	
E- HR Local	

### Answer:

D, E

# **Question 3**

**Question Type:** MultipleChoice


When is it necessary to use an SNMP based Enforcement profile to send a VIAN?

### **Options:**

- A- When we have to assign a vlan to a wired user on a third party wired switch that doesn't support RADIUS return attributes.
- B- When we have to assign a VLAN to a wired user on an Aruba Mobility Access Switch.
- C- When we have to assign a VIAN to a wired user on an Aruba Mobility Controller.
- **D** When we have to assign a VLAN to a wired user on a third party wired switch that doesn't support RADIUS authentication.
- E- When we have to assign a VLAN to a wireless user on an Aruba Mobility Controller.

Answer:			
В			

**Question Type:** MultipleChoice



* Name:	Employee Secure
	Enter a name for the network.
Description:	Connect to the example network.
	Wireless only
* Network Type:	
	Enterprise (802.1X)
* Security Type:	Select the authentication method used for the network. Enterprise security (802.1X) will be selected if wired networks are to be supported.
Wireless Netwo	-
	WPA2 with AES (recommended)
* Security Version:	Select the WPA encryption version for the wireless network. This setting is used for Windows, Android and Legacy OS X (10.5/6) devices only. iOS and OS X 10.7+ (Lion or later) devices auto-detect the WPA version.
* SSID:	secure_emp Enter the SSID of the wireless network to connect to.
Wireless:	<ul> <li>Hidden network</li> <li>Select this option if the wireless network is not open or broadcasting.</li> </ul>
Exhibit:accp67-	- 5 3 4

Which statements accurately describe the status of the Onboarded devices in the configuration tor the network settings shown? (Select two.)

### **Options:**

- A- They will connect to Employee\_Secure SSID after provisioning.
- B- They will connect to Employee\_Secure SSID for provisioning their devices.
- C- They will use WPA2-PSK with AES when connecting to the SSID.
- **D-** They will connect to secure\_emp SSID after provisioning.
- E- They will perform 802.1X authentication when connecting to the SSID.

### Answer: D, E

# **Question 5**

### **Question Type:** MultipleChoice

What are Operator Profiles used for?

### **Options:**

- A- to enforce role based access control for Aruba Controllers
- B- to enforce role based access control for ClearPass Policy Manager admin users
- C- to enforce role based access control for ClearPass Guest Admin users
- D- to assign ClearPass roles to guest users
- E- to map AD attributes to admin privilege levels in ClearPass Guest

Answer:			
С			

**Question Type:** MultipleChoice

## Configuration » Services » Edit - CompanyX Onboard Authorization

## Services - CompanyX Onboard Authorization

Summary Service	Authentication Roles Enforcement
Use Cached Results:	🖾 Use cached Roles and Posture attributes from previous sessions
Enforcement Policy:	CompanyX Onboard Authorization Policy Modify
Enforcement Policy Details	
Description:	Sample policy controlling authorization during Onboard provisioning
Default Profile:	[Deny Access Profile]
Rules Evaluation Algorithm:	evaluate-all
Conditions	Enforcement Profiles
1	Week         BELONGS_TO           esday,Thursday,Friday,Saturday,Sunday)         [Allow Access Profile], [Aruba Terminate Session]

Exhibit:accp67-543

Based on the configuration of the Enforcement Profiles In the Onboard Authorization service shown, which Onboarding action will occur?

### **Options:**

A- The device will be disconnected from the network after Onboarding so that an EAP-TLS authentication is not performed.

**B-** The device will be disconnected from and reconnected to the network after Onboarding is completed.

C- The device's onboard authorization request will be denied.

D- The device will be disconnected after post-Onboarding EAP-TLS authentication, so a second EAP-TLS authentication is performed.

E- After logging in on the Onboard web login page, the device will be disconnected form and reconnected to the network before Onboard begins.

### Answer:

В

# **Question 7**

### **Question Type:** MultipleChoice

Which is a valid policy simulation types in ClearPass? (Select three.)

### **Options:**

### A- Enforcement Policy

- B- Posture token derivation
- C- Role Mapping

D- Endpoint Profiler

E- Chained simulation

### Answer:

A, C, E

# **Question 8**

**Question Type:** MultipleChoice

Configuration » Identity » Local Users

Local Users



### **Options:**

A- mike

B- We can't know this from the screenshot above.

C- Employee

### Answer:

В

# **Question 9**

**Question Type:** MultipleChoice

Why is a terminate session enforcement profile used during posture checks with 802.1 x authentication?

### **Options:**

- A- To send a RADIUS CoA message from the ClearPass server to the client
- B- To disconnect the user for 30 seconds when they are in an unhealthy posture state
- C- To blacklist the user when they are in an unhealthy posture state
- D- To force the user to re-authenticate and run through the service flow again
- E- To remediate the client applications and firewall do that updates can be installed

А

# **Question 10**

**Question Type:** MultipleChoice

Which statement is true about the databases in ClearPass?

### **Options:**

A- Entries in the guest user database do not expire.

- **B-** A Static host list can only contain a list of IP addresses.
- C- Entries in the guest user database can be deleted.
- D- Entries in the local user database cannot be modified.
- E- The endpoints database can only be populated by manually adding MAC addresses to the table.

### Answer:

А

**Question Type:** MultipleChoice

# RADIUS Web Login

Use this form to make changes to the RADIUS Web Login Guest Network.

	RADIUS Web Login Editor
* Name:	Guest Network Enter a name for this web login page.
Page Name:	Aruba_login Enter a page name for this web login. The web login will be accessible from "/guest/page_name.php".
Description:	Comments or descriptive text about the web login.
Vendor Settings:	Aruba Networks   Select a predefined group of settings suitable for standard network configurations.
Address:	securelogin.arubanetworks.com Enter the IP address or hostname of the vendor's product here.
Secure Login:	Use vendor default  Select a security option to apply to the web login process.
Dynamic Address:	The controller will send the IP to submit credentials In multi-controller deployments, it is often required to post credentials to different add The address above will be used whenever the parameter is not available or fails the re

Exhibit:accp67-442

When configuring a Web Login Page in ClearPass Guest, the information shown is displayed. What is the Address field value 'securelogin.arubanetworks.com' used for?

### **Options:**

- A- for ClearPass to send a TACACS+ request to the NAD
- B- for appending to the Web Login URL, before the page name
- C- for the client to POST the user credentials to the NAD
- D- for ClearPass to send a RADIUS request to the NAD
- E- for appending to the Web Login URL, after the page name.

### Answer:

## **To Get Premium Files for HPE6-A75 Visit**

https://www.p2pexams.com/products/hpe6-a75

For More Free Questions Visit

https://www.p2pexams.com/hp/pdf/hpe6-a75

