



Free Questions for H12-223 by ebraindumps

Shared by Reilly on 29-01-2024

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Coaxial cables are used to carry video signals of cable TVs but not data signals.

Options:

A- TRUE

B- FALSE

Answer:

B

Question 2

Question Type: MultipleChoice

If a neighbor has not advertised a route, the neighbor may have not put description information about the route to the local OSPF LSDB.

Options:

A- TRUE

B- FALSE

Answer:

A

Question 3

Question Type: MultipleChoice

To improve STP running stability, a network administrator wants to configure some STP features or protection mechanism on switches. Which of the following configuration roadmaps is correct?

Options:

A- Configure the user access port as an edge port to prevent the user from connecting to the switch on this port.

B- Configure root protection on the user access port to ensure that the user does not connect to a switch with a higher priority.

C- Configure loop protection on positions where loops have occurred so that loops are always blocked.

D- Configure BPDU protection so that the switch checks the validity of each received BPDU to prevent attacks of forged BPDUs.

Answer:

B

Question 4

Question Type: MultipleChoice

In network design, a redundant network topology can be used to provide higher reliability for customer services. Which of the following topologies can be used to provide redundancy? (Multiple Choice)

Options:

A- Star topology

B- Ring topology

C- Bus topology

D- Dual-star topology

Answer:

B, D

Question 5

Question Type: MultipleChoice

Which of the following causes may result in a BGP peer relationship fault? (Multiple Choice)

Options:

- A-** An ACL is configured to disable TCP port 179.
- B-** The peer router ID conflicts with the local router ID.
- C-** The peer ebgp-max-hop command is not configured when loopback interfaces are used to establish the EBGP peer relationship.
- D-** The peer connect-interface command is not configured when loopback interfaces are used to establish the BGP peer relationship.

Answer:

A, B, C, D

Question 6

Question Type: MultipleChoice

Which of the following items is conducted in the cause list phase of the structured network troubleshooting process?

Options:

- A- One-by-one check
- B- Information filter
- C- Temporary environment setup
- D- Troubleshooting assessment

Answer:

B

Question 7

Question Type: MultipleChoice

During network design, VLANs are assigned in many ways. Which of the following ways is seldom adopted?

Options:

- A- VLAN assignment based on the access device type
- B- VLAN assignment based on the access location
- C- VLAN assignment based on security system requirements
- D- VLAN assignment based on service design

Answer:

A

Question 8

Question Type: MultipleChoice

Enterprise services have strict requirements for QoS in networks. Which of the following counters can be used to indicate network QoS.
(Multiple Choice)

Options:

A- Stability

B- Bandwidth

C- Delay

D- Jitter

E- Security

Answer:

B, C, D

To Get Premium Files for H12-223 Visit

<https://www.p2pexams.com/products/h12-223>

For More Free Questions Visit

<https://www.p2pexams.com/huawei/pdf/h12-223>

