LPI 702-100 Practice Questions

Shared by Delaney on 21-10-2026

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Which of the following lines stems from the output of last?

Options:

A- 3:26PM up 1:58, 2 users, load averages: 0.49, 0.43, 0.40
B- May 11 19:34:24 fbsd login [793]: login on ttyv0 as root
C- root ttyv0 Sat May 18 13:35 still logged in
D- 763 v1 Is+ 0:00-00 /usr/libexec/getty Pc ttyv1
E- FreeBSD 12.0-RELEASE r341666 GENERIC

Answer:

C

Question 2

Question Type: MultipleChoice

Which of the following commands have to be used in order to update FreeBSD? (Select TWO correct answers.)

Options:

A- freebsd-update all
B- freebsd-update resolvedeps
C- freebsd-update fetch
D- freebsd-update repoupdate
E- freebsd-update install

Answer:

A, E

Question 3

Question Type: MultipleChoice

Which BSD command lists, adds, or deletes swap devices?

Options:

A- diskcontro1
B- mkswap
C- swap
D- swapct1
E- swapinfo

P2P exams

Answer:

D

Question 4

Question Type: MultipleChoice

Which option of the crontab command opens the current user's crontab in an editor?

Options:

A- -w
B- -i
C- -vi
D- -rw
E- -e

P2P exams

Answer:

E

Question 5

Question Type: MultipleChoice

Which option best commands initializes ZFS on a number of block devices?

Options:

A- zpoo1 create
B- newzfs
C- zfs init
D- mkfs -t zfs
E- zfsload -i

Answer:

C

Question 6

Question Type: MultipleChoice

What file contains values for MIBs which are set during system startup? (Specify the full name of the file, including path.)

Options:

A- See in Explanation

Answer:

A

Question 7

Question Type: MultipleChoice

How often does? match the preceding expression in a regular expression?

Options:

A- Two or more times
B- Exactly one time

C- Any number of times
D- Zero or one times
E- One or more times

Answer:

D

Question 8

Question Type: MultipleChoice

Which of the following excerpts is a valid if condition in the Bourne shell?

A.

```
if [ "$var" = "test" ]
{
        echo True
}
```

B.

```
if [ "$var" = "test" ]
then
        echo True
fi
```

C.

```
if [ "$var" = "test" ]
[[
        echo True
]]
```

D.

```
if ( "$var" = "test" )
        echo True
done
```

Options:

A- Option A
B- Option B
C- Option C
D- Option D

Answer:

B

Question 9

Question Type: MultipleChoice

Which command and option can be used to perform a reverse DNS lookup?

Options:

A- dig -x
B- dnssec -check
C- host -reverse
D- nsupdate -r
E- rdns -1

Answer:

A

Question 10

Question Type: MultipleChoice

What symbol is used in the vi editor to start the forward search for a string? (Specify ONLY the single character symbol without any parameters)

Options:

A- See in Explanation

Answer:

A

P2P exams

P2P exams

To Get Premium Files for 702-100 Visit

https://www.p2pexams.com/products/702-100

For More Free Questions Visit

https://www.p2pexams.com/lpi/pdf/702-100

