



MikroTik MTCNA Mock Exam

Shared by Tillman on 17-06-2026

For More Free Questions and Preparation Resources

Check the Links on Last Page



Question 1

Question Type: MultipleChoice

What is the minimal possible wireless configuration to create an Access Point?

Options:

- A- radio name
- B- scan-list
- C- frequency
- D- band
- E- ssid
- F- DFS mode
- G- WDS
- H- mode



Answer:

H

Question 2

Question Type: MultipleChoice

Which computers would be able to communicate directly (without any routers involved):

Options:

- A- 192.168.17.15/29 and 192.168.17.20/28
- B- 10.5.5.1/24 and 10.5.5.100/25
- C- 10.10.0.17/22 and 10.10.1.30/23
- D- 192.168.0.5/26 and 192.168.0.100



Answer:

B, C

Question 3

Question Type: MultipleChoice

Why is it useful to set a Radio Name on the radio interface?

Options:

- A- To identify a station in the Access List
- B- To identify a station in Neighbor discovery
- C- To identify a station in a list of connected clients

Answer:

B

Question 4

Question Type: MultipleChoice

Which features are removed when advanced-tools package is uninstalled?

Options:

- A- neighbors
- B- LCD support
- C- ip-scan
- D- ping
- E- netwatch
- F- bandwidth-test

Answer:

C, D, E

Question 5

Question Type: MultipleChoice

What command is used to create a backup configuration?

Options:

- A- copy running backup
- B- copy running-config startup-config
- C- config mem
- D- wr mem

Answer:

B

Question 6

Question Type: MultipleChoice

There can be more than one PPPoE server in a single broadcast domain:

Options:

- A- True
- B- False

Answer:

A

Question 7

Question Type: MultipleChoice

What does the firewall action "log" do?

Options:

- A- It logs and blocks the packet
- B- It blocks and logs the packet
- C- It adds a prefix to the packet and passes it through
- D- It logs the packet

Answer:

D

Question 8

Question Type: MultipleChoice

Action=redirect is applied in

Options:

- A- chain=srcnat
- B- chain=forward
- C- chain=dstnat

Answer:

C

Question 9

Question Type: MultipleChoice

You would like to allow multiple logins with one user name on a Hot-Spot server. How should this be configured?

Options:

- A- Set 'Shared Users' option at /ip Hot-Spot user profile
- B- It's not possible
- C- Set 'Shared Users' option at /ip Hot-Spot
- D- Set 'only-one=no' at /ip Hot-Spot

Answer:

A

To Get Premium Files for MTCNA Visit

<https://www.p2pexams.com/products/mtcna>

For More Free Questions Visit

<https://www.p2pexams.com/mikrotik/pdf/mtcna>

20%
DISCOUNT

P2P
exams