NetApp NCSE NS0-194 Practice Questions

Shared by Norton on 22-10-2026

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Test user "LAB\tester" can perform an operation in the CIFS share "HR" from the SVM "svm1". However, the rest of the users from the HR department cannot perform the same operation. You want to determine why only "LAB\tester" can perform the operation.

In this scenario, which security trace filter accomplishes this task?

Options:

A- vserver security trace filter create -vserver svm1 -index 1 -protocol nfs - unix-name tester -trace-allow no
B- vserver security trace filter create -vserver svm1 -index 1 -protocol cifs - windows- name LAB\tester -trace-allow no
C- vserver security trace filter create -vserver svm1 -index 1 -protocol cifs - windows- name LAB\tester -trace-allow yes
D- vserver security trace filter create -vserver svm1 -index 1 -protocol nfs - unix-name tester -trace-allow yes

Answer:

C

Question 2

Question Type: MultipleChoice

What are two reasons to use HTTPS as the transport method for AutoSupport delivery for Active IQ? (Choose two.)

Options:

A- Only HTTPS transfers are compressed.
B- AutoSupport OnDemand (AOD) is supported.
C- HTTPS is encrypted.
D- HTTPS does not use a standard port.

Answer:

B, C

Question 3

Question Type: MultipleChoice

Referring to the exhibit, which two components should be examined? (Choose two.)

Workload	ID	Latency	Network	Cluster	Data	Disk	QoS	NVRAM	Cloud
-total-		110.35ms	327.00us	327.00us	0ms				
110.02ms	0ms	0ms	0ms						
vs1vol0	111	167.82ms	603.00us	603.00us	0ms				
167.22ms	0ms	0ms	0ms						
vol1	1234	117.76ms	191.00us	191.00us	0ms				
117.56ms	0ms	0ms	0ms						
vol2	999	44.24ms	190.00us	190.00us	0ms	44.05ms	0ms	0ms	0ms
-total-	-								
38.89ms	256.00us	256.00us	0ms	38.63ms	0ms	0ms	0ms		
vol2	999	64.47ms	266.00us	266.00us	0ms	64.20ms	0ms	0ms	0ms
vol1	1234	27.28ms	253.00us	253.00us	0ms	27.03ms	0ms	0ms	0ms
vs1vol0	111	23.72ms	249.00us	249.00us	0ms	23.47ms	0ms	0ms	0ms
-total-	-	409.81ms	169.00us	169.00us	0ms				
409.65ms	0ms	0ms	0ms						
vol1	1234	816.92ms	120.00us	120.00us	0ms				
816.80ms	0ms	0ms	0ms						
vol2	999	407.88ms	219.00us	219.00us	0ms				
407.66ms	0ms	0ms	0ms						
vs1vol0	111	3.68ms	193.00us	193.00us	0ms	3.49ms	0ms	0ms	0ms

Options:

A- cluster switches
B- SAS adapter
C- network interface card
D- disk

Answer:

B, D

Question 4

Question Type: MultipleChoice

You want to set up a FabricPool between an ONTAP cluster and Google Cloud Storage.

In this scenario, which two components are required to accomplish this task? (Choose two.)

Options:

A- a service account access key

B- a Certificate Authority (CA) certificate
C- an Express Route
D- intercluster LIFs

Answer:

B, D

Question 5

Question Type: MultipleChoice

Test user "LAB\tester" can perform an operation in the CIFS share "HR" from the SVM "svm1". However, the rest of the users from the HR department cannot perform the same operation. You want to determine why only "LAB\tester" can perform the operation.

In this scenario, which security trace filter accomplishes this task?

Options:

A- vserver security trace filter create -vserver svm1 -index 1 -protocol nfs - unix-name tester -trace-allow no
B- vserver security trace filter create -vserver svm1 -index 1 -protocol cifs - windows- name LAB\tester -trace-allow no
C- vserver security trace filter create -vserver svm1 -index 1 -protocol cifs - windows- name LAB\tester -trace-allow yes
D- vserver security trace filter create -vserver svm1 -index 1 -protocol nfs - unix-name tester -trace-allow yes

Answer:

C

Question 6

Question Type: MultipleChoice

Which CIFS server configuration determines the domain controllers that a CIFS server uses?

Options:

A- site membership
B- enabled SMB versions
C- trusted domains
D- discovery mode

Answer:

A

Question 7

Question Type: MultipleChoice

You perform a security trace when troubleshooting a data access problem for a user. The results are shown in the exhibit.

```
cluster1::> vserver security trace trace-result show -vserver svm1

Vserver: svm1

Node         Index  Filter Details             Reason
-----------  -----  -------------------------  ----------------------------
cluster1-01  1      Security Style: NTFS and   Access is denied. The
                    NT ACL                     requested permissions are not
                                               granted by the ACE while
                                               opening existing file or
                                               directory. Access is not
                                               granted for: "Read Attributes"
                    Protocol: cifs
                    Volume: -
                    Share: dept
                    Path: /list.xlsx
                    Win-User: LAB\domusr1
                    UNIX-User: pcuser
                    Session-ID: 14249952170953675090
```

What should you do to solve this issue?

Options:

A- Grant the user Read Attributes access to the path.
B- Add the user to the BUILTIN\power Users group.
C- Add the user to the BUILTIN\Users group.
D- Grant the user Execute access to the path.

Answer:

A

Question 8

Question Type: MultipleChoice

A user can read and write some files on an NFS volume, but the user is unable to read all of the files in the volume.

In this scenario, which command will help you troubleshoot this problem?

Options:

A- security login create
B- security audit show
C- vserver security trace filter create
D- vserver export-policy check-access

Answer:

C

Question 9

Question Type: MultipleChoice

You want to use the supported method to upgrade the ONTAP version of a Cloud Volumes ONTAP instance from ONTAP 9.5 to ONTAP 9.6.

In this scenario, which NetApp tool accomplishes this task?

Options:

A- Cloud Manager
B- Cloud Insights
C- Active IQ Unified Manager
D- ONTAP System Manager

Answer:

D

Question 10

Question Type: MultipleChoice

A customer is showing disk utilization is at 100% in Active IQ even though there are low protocol operations on the controller. You review the data shown in the exhibit.

disk	ut%	xfers	ureads--chain-usecs		writes--chain-usecs		
/aggr0/plex0/rg0:							
6b.34	1	2.18	0.17	1.00 10700	0.98	13.49	490
6a.19	1	2.35	0.17	1.00 36600	1.15	11.83	504
6a.45	13	17.98	16.88	2.13 5810	0.53	8.81	887
6b.18	13	17.57	16.55	2.17 5357	0.42	11.00	1189
6a.29	12	16.70	15.30	2.15 5820	0.60	6.75	1996
6b.25	13	18.31	17.13	2.17 5611	0.48	7.59	1709
6b.39	100	15.44	15.07	2.22 191927	0.00	....	.
6a.17	12	16.75	15.52	2.10 6126	0.50	8.63	1475
6b.38	12	16.98	15.95	2.09 5614	0.43	9.92	1349

In this situation, what should you do?

Options:

A- Replace disks 6b.34 and 6a.19.
B- Add disks to the aggregate to bring down the average utilization.
C- Replace disk 6b.39.
D- Reseat shelf module B.

Answer:

C

Question 11

Question Type: MultipleChoice

How many drive bays does a DS4246 shelf have?

Options:

A- 42
B- 12
C- 46

D- 24

Answer:

D

P2P exams

P2P exams

To Get Premium Files for NS0-194 Visit

https://www.p2pexams.com/products/ns0-194

For More Free Questions Visit

https://www.p2pexams.com/netapp/pdf/ns0-194

