



Free Questions for NS0-175 by vceexamstest

Shared by Hancock on 06-06-2022

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

You have taken over management of an existing FlexPod system as part of a new job role. You want to find details of existing support and service contracts available for the system.

Which two resources would you use to find this information? (Choose two.)

Options:

- A- NetApp Interoperability Matrix Tool
- B- Cisco Device Coverage Checker Tool
- C- NetApp Support website
- D- FlexPod.com website

Answer:

A, C

Question 2

Question Type: MultipleChoice

A customer has reviewed the latest vSphere CVD and asks you if they can use their older Cisco servers in the new FlexPod solution and still have supported configuration.

Which statement is true in this scenario?

Options:

- A-** FlexPod configurations are fully supported if they follow the technical specifications and compatibility matrices.
- B-** FlexPod configurations are fully supported if they follow a specific Cisco Validated Design.
- C-** FlexPod configurations are fully supported regardless of the equipment used.
- D-** FlexPod configurations are fully supported if they follow a specific NetApp Verified Architecture.

Answer:

B

Question 3

Question Type: MultipleChoice

During a design meeting, a customer states that their goal is to deliver continuous availability across both network and storage during business continuity events. The customer has two data centers that are 80 km apart, and they want the configuration to be as logically unified across both sites as possible.

In this scenario, which FlexPod data protection solution achieves this goal?

Options:

- A- FlexPod with NetApp Cloud Sync
- B- FlexPod with NetApp SnapCenter
- C- FlexPod with NetApp MetroCluster IP
- D- FlexPod with NetApp FabricPool

Answer:

C

Question 4

Question Type: MultipleChoice

A customer with a FlexPod Datacenter solution wants to enable user access on UCS Manager.

In this scenario, which three authentication methods would be configured? (Choose three.)

Options:

A- NetBIOS

B- LDAP

C- Local

D- Active Directory

E- Workgroup

Answer:

A, C, D

Question 5

Question Type: MultipleChoice

A customer is performing a server refresh of their FlexPod solution to accommodate business growth. The customer is interested in using Cisco C-Series servers, and supporting multiple 40 Gbps link to each server, upgrading from the existing 10 Gbps links.

Which two VICs support these requirements? (Choose two.)

Options:

- A- Cisco UCS 1480 VIC
- B- Cisco UCS 1497 VIC
- C- Cisco UCS 1495 VIC
- D- Cisco UCS 1440 VIC

Answer:

A, D

Question 6

Question Type: MultipleChoice

In which two sources would you verify scale out maximums for NetApp and Cisco UCS environments? (Choose two.)

Options:

A- Cisco Configurations Limits

B- Cisco UCS Hardware and Software Compatibility List

C- NetApp Hardware Universe

D- NetApp Interoperability Matrix

Answer:

B, D

Question 7

Question Type: MultipleChoice

A customer wants to deploy Cisco Intersight into their FlexPod environment. The customer is using the Cisco Intersight SaaS model.

In this scenario, which two virtual machines are required to support this requirement? (Choose two.)

Options:

- A- Cisco UCS Fabric Interconnect
- B- NetApp Active IQ Unified Manager
- C- Cisco Intersight Virtual Appliance
- D- NetApp Virtual Storage Console

Answer:

B, C

Question 8

Question Type: MultipleChoice

You want to use Cisco UCS Manager on the Fabric Interconnects to manage attached C-Series servers.

Which two connection topologies would satisfy the requirements? (Choose two.)

Options:

- A- Fabric Interconnects uplinked to Nexus switches

- B-** Servers directly connected to the Fabric Interconnects
- C-** Fabric Interconnects uplinked to MDS switches
- D-** Fabric Interconnects uplinked to Fabric Extenders

Answer:

B, C

Question 9

Question Type: MultipleChoice

A customer wants to refresh their FlexPod solution by moving from 10 Gbps to 40 Gbps networking. They use FCoE to boot from SAN.

In this scenario, which statement is true?

Options:

- A-** FCoE is supported for 32 Gbps adapters
- B-** FCoE is supported for 25 Gbps adapters

C- FCoE is supported for 40 Gbps adapters

D- FCoE is supported on only 10 Gbps unified adapters

Answer:

C

Question 10

Question Type: MultipleChoice

An administrator wants to ensure secure authentication while accessing a NetApp ONTAP system.

In this scenario, which two access methods should be used? (Choose two.)

Options:

A- RSH

B- SSH

C- HTTPS

D- HTTP

Answer:

A, B

Question 11

Question Type: MultipleChoice

A customer wants to replace their Cisco UCS 6248UP with the current Cisco UCS 6454. They are currently using six 16 Gbit uplinks per Fabric Interconnect for FC and do not want to change the speed and number of ports used.

In this scenario, what is the minimum number of unified ports that must be configured for FC for a comparable configuration?

Options:

A- 8

B- 6

C- 16

D- 12

Answer:

A

To Get Premium Files for NS0-175 Visit

<https://www.p2pexams.com/products/ns0-175>

For More Free Questions Visit

<https://www.p2pexams.com/netapp/pdf/ns0-175>

