# NetApp NS0-175 Practice Questions

**Shared by English on 22-10-2026**

**For More Free Questions and Preparation Resources**

Check the Links on Last Page

## Question 1

Question Type: MultipleChoice

You want to ass a customer's NetApp storage controllers into their Cisco Intersight management portal.

In this scenario, which IP address would you choose to add?

### Options:

A- NetApp SVM management IP address
B- NetApp Active IQ Unified Manager IP address
C- NetApp cluster IP address
D- NetApp Virtual Storage Console IP address

### Answer:

B

## Question 2

Question Type: MultipleChoice

A customer wants to deploy Cisco Intersight into their FlexPod environment. The customer is using the Cisco Intersight SaaS model.

In this scenario, which two virtual machines are required to support this requirement? (Choose two.)

### Options:

A- Cisco UCS Fabric Interconnect
B- NetApp Active IQ Unified Manager
C- Cisco Intersight Virtual Appliance
D- NetApp Virtual Storage Console

### Answer:

B, C

## Question 3

Question Type: MultipleChoice

An administrator wants to ensure secure authentication while accessing a NetApp ONTAP system.

In this scenario, which two access methods should be used? (Choose two.)

### Options:

A- RSH
B- SSH
C- HTTPS
D- HTTP

### Answer:

A, B

## Question 4

Question Type: MultipleChoice

You want to ass a customer's NetApp storage controllers into their Cisco Intersight management portal.

In this scenario, which IP address would you choose to add?

### Options:

A- NetApp SVM management IP address
B- NetApp Active IQ Unified Manager IP address
C- NetApp cluster IP address
D- NetApp Virtual Storage Console IP address

### Answer:

B

## Question 5

Question Type: MultipleChoice

A customer is designing a FlexPod solution that must satisfy the requirements shown below:

have disaster recovery to an alternative data center,

must have continuous replication of data for a database,

must leverage a 100Gbps capable switch,

have a maximum distance of 700 km.

In this scenario, which two components would be used to satisfy the requirements? (Choose two.)

### Options:

A- MetroCluster FC
B- Cisco Nexus 3232C
C- MetroCluster IP
D- Cisco MDS 9132T

### Answer:

A, C

## Question 6

Question Type: MultipleChoice

You are sizing a FlexPod Virtual Desktop solution for a customer with 500 virtual desktops in a shared Remote Desktop Services (RDS) topology.

In this scenario, which Cisco best practice should you use?

### Options:

A- You should avoid placing more than 20 users per physical host
B- You should avoid over-committing physical CPU resources for virtual machines
C- You should avoid changing the virtual host disk queue depth
D- You should avoid multiple vCPUs per individual virtual machine

### Answer:

B

## Question 7

Question Type: MultipleChoice

You are creating a FlexPod with a significant AI workload and would like to use NVIDIA's SXM2-based GPUs.

Which Cisco UCS server would you use in this scenario?

### Options:

A- Cisco UCS C240 M5
B- Cisco UCS B200 M5
C- Cisco UCS C480 ML M5
D- Cisco UCS C125 M5

### Answer:

C

## Question 8

Question Type: MultipleChoice

You received from a customer the requirements shown below.

25 servers

25GbE connectivity

NFS and iSCSI protocols

30 TB flash storage

50 TB hybrid storage

In this scenario, which FlexPod solution would satisfy the requirements?

### Options:

A- Cisco UCS 6454 Fabric Interconnect, Cisco B-Series servers, Cisco Nexus 9300 Series, NetApp AFF A400, and FAS2750
B- Cisco UCS 6332 Fabric Interconnect, Cisco B-Series servers, Cisco Nexus 9300 Series, NetApp AFF A400, and FAS8300
C- Cisco UCS 6454 Fabric Interconnect, Cisco B-Series servers, Cisco Nexus 9300 Series, NetApp AFF A400, and FAS8300
D- Cisco UCS 6324 Fabric Interconnect, Cisco B-Series servers, Cisco Nexus 9300 Series, NetApp AFF A400, and FAS2750

### Answer:

B

## Question 9

Question Type: MultipleChoice

A customer wants to deploy a FlexPod Datacenter solution that supports a secure multitenant design with VMware vSphere 6.x as the hypervisor. The customer wants to ensure that virtual machines are encrypted in transit and at rest and restricted to their specified tenant.

Which component should the customer use to implement this capability?

### Options:

A- Cisco TrustSec
B- NetApp Storage Encryption
C- NetApp Volume Encryption
D- VMware vSphere virtual machine encryption

### Answer:

B

## Question 10

Question Type: MultipleChoice

A customer with a FlexPod Datacenter solution wants to enable user access on UCS Manager.

In this scenario, which three authentication methods would be configured? (Choose three.)

## Options:

A- NetBIOS
B- LDAP
C- Local
D- Active Directory
E- Workgroup

## Answer:

A, C, D

P2P exams

P2P exams

To Get Premium Files for NS0-175 Visit

https://www.p2pexams.com/products/ns0-175

For More Free Questions Visit

https://www.p2pexams.com/netapp/pdf/ns0-175

