



Free Questions for 4A0-N02 by certscare

Shared by Mccullough on 06-06-2022

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Which of the following statements about the SD-WAN portal is TRUE?

Options:

- A-** The SD-WAN portal is an optional addition to the Nuage Networks VNS solution.
- B-** The SD-WAN portal cannot be deployed as a high availability cluster.
- C-** The SD-WAN portal is configured either by the Graphical User Interface (GUI) or a Command Line Interface (CLI).
- D-** The SD-WAN portal cannot be used to bootstrap NSGs.

Answer:

A

Question 2

Question Type: MultipleChoice

Which protocol is used between VSAP and the VSC?

Options:

A- XMPP

B- OpenFlow

C- BGP and OSPF or ISIS

D- SNMP

Answer:

D

Question 3

Question Type: MultipleChoice

Which of the following statements about the Nuage Networks SD-WAN portal is TRUE?

Options:

- A- It runs directly on any Linux-based bare metal server.
- B- It is packaged as a docker container.
- C- It is deployed as a KVM, Hyper-V or ESXi virtual machine.
- D- It must be hosted in a public cloud such as AWS.

Answer:

A

Question 4

Question Type: MultipleChoice

Which Nokia product is the core component of VNO?

Options:

- A- Cloudband Network Director (CBND)

- B-** CloudBand Application Manager (CBAM)
- C-** CloudBand Infrastructure Software (CBIS)
- D-** Nuage Networks Virtualized Services Directory (VSD)

Answer:

B

Question 5

Question Type: MultipleChoice

Which of the following is NOT a VSAP web application?

Options:

- A-** Service Navigator
- B-** Security Management
- C-** Inventory Management
- D-** Fault Management

Answer:

A

Question 6

Question Type: MultipleChoice

Which statement regarding the forwarding policies used in VNS for traffic redirection (also known as service chaining) is FALSE?

Options:

- A-** Forwarding policies can be applied to ingress and egress traffic.
- B-** Redirection targets should be created in advance and associated with vports.
- C-** Redirection targets cannot be associated with bridge vports (physical appliances).
- D-** Traffic between two branch offices or between two devices in the same branch office can be redirected to an appliance located in the data center.

Answer:

D

Question 7

Question Type: MultipleChoice

Which of the following statements about the NSG support for NAT-T is TRUE?

Options:

- A- NAT-T is a network port level attribute.
- B- NAT-T NPM probes are disabled by default.
- C- Direct Symmetric to Symmetric mapping is supported.
- D- Address restricted mapping requires the use of two NPM probes.

Answer:

A

Question 8

Question Type: MultipleChoice

Which of the NAT-T variants creates a NAT table similar to the diagram?

Options:

- A- Symmetric mapping
- B- Port restricted mapping
- C- Address restricted mapping
- D- Endpoint-independent mapping

Answer:

C

To Get Premium Files for 4A0-N02 Visit

<https://www.p2pexams.com/products/4a0-n02>

For More Free Questions Visit

<https://www.p2pexams.com/nokia/pdf/4a0-n02>

