Oracle 1Z0-078 Practice Questions

Shared by Patterson on 10-11-2026

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Which two tasks must be performed before launching the Oracle universal installer to install Oracle Database Software for RAC? (Choose two.)

Options:

A- ssh user equivalence for the Oracle software owner must be configured on all cluster nodes where the Database software will be installed.
B- Grid Infrastructure must be installed on all cluster nodes.
C- The Clusterware stack must be up on all cluster nodes.
D- The Clusterware stack must be up on all cluster nodes where the Database software will be installed.
E- SSH user equivalence for the Oracle software owner must be configured on all cluster nodes.
F- Grid Infrastructure must be installed on all cluster nodes where the Database software will be installed.

Answer:

A, B

Question 2

Question Type: MultipleChoice

Which three statements are true about diagnostic reporting for the OCR and OLR files? (Choose three.)

Options:

A- The OCRCHECK utility can check the OLR in an online fashion with the clusterware running on all nodes.
B- The OCRCONFIG utilty can be used to repair a corrupt OCR file in an online fashion with the clusterware running on all nodes.
C- The CLUVFY utility can check the integrity of the OCR but not the OLR.
D- The OCRDUMP utility can dump specific keys from the OLR in an online fashion with the clusterware running on all nodes.
E- The OCRDUMP utility can dump specific keys from the OCR in an online fashion with the clusterware running on all nodes.

Answer:

A, D, E

Question 3

Question Type: MultipleChoice

Which two statements are true concerning Oracle 19c Clusterware-managed application VIPs? (Select two.)

Options:

A- An application VIP is created on the default network by the appvipcfg utility.
B- Application VIPs do not fail over to surviving cluster nodes when the node hosting the VIP fails.
C- If an application sends messages to be displayed and sets the display variable, then an application VIP is required.
D- An application VIP can be created with the crsccl utility.
E- An application VIP is created on the interconnect network by the crsccl utility.

Answer:

A, D

Question 4

Question Type: MultipleChoice

Which two steps must always be performed to delete node host04 from an Oracle 19c Clusterware cluster that does not use Grid Naming Service (GNS)? (Choose two.)

Options:

A- Run the crsctl unpin css - host04 command as root on host01, or on either host02 or host03.
B- Run the crsctl delete node -n host04 command as root on host04.
C- Run the crsctl delete node -n host04 command as root on host01, or on either host02 or host03.
D- Run the crsct1 unpin css - host04 command as root on host04.
E- Run the rootcrs.pl -deconfig -force command as root on host04.
F- Run the rootcrs.pl -deconfig -force command as root on host01, or on either host02 or host03.

Answer:

C, E

Question 5

Question Type: MultipleChoice

Which two statements are true about High Availability NFS (HANFS)? (Choose two.)

Options:

A- HANFS provides high availability in case of an NFS client failure.
B- HANFS' performance depends on the characteristics of the underlying ASM disks.
C- HANFS does not depend on NFS services provided by the underlying operating system.
D- HANFS provides high availability in case of cluster node failure.
E- NFS client requests are distributed by DNS in a round-robin fashion to the cluster nodes that export the NFS

Answer:

B, D

Question 6

Question Type: MultipleChoice

A Java application using thick JDBC connections will soon be deployed, and you must configure a RAC database to support highly available connections.

Broken connections must be re-established as quickly as possible.

Which feature will support this requirement?

Options:

A- Transparent Application Failover (TAF) using Fast Application Notification (FAN)
B- Transparent Application Failover (TAF)
C- Fast Connection Failover (FCF)
D- Fast Connection Failover (FCF) with Transparent Application Failover (TAF)

Answer:

C

Question 7

Question Type: MultipleChoice

Examine the output of the asmcmd and srvctl commands:

```
$ asmcmd showclustermode

ASM cluster : Flex mode enabled

$ srvctl status asm -detail

ASM is running on host01, host03
ASM is enabled.

$ srvctl config asm

ASM home: /u01/app/12.1.0/grid
Password file: +DATA/orapwASM
ASM listener: LISTENER
ASM instance count: 2
Cluster ASM listener: ASMNET1LSNR_ASM
```

Then you execute this command:

$ srvctl relocate asm -currentnode host03 -targetnode host02

Which three statements are true regarding the execution of this command based on the output shown? (Choose three.)

Options:

A- It fails because the ASM instance has not been shut down first on HOST03.
B- It succeeds and starts an ASM instance on HOST02 but the ASM instance on HOST03 is not shut down until all connected clients disconnect.

C- It succeeds and starts an ASM instance on HOST02 and shuts down the ASM instance on HOST03.
D- It succeeds and 19c database instances connected to the ASM instance on HOST03 can be reconnected to the ASM instance on HOST02.
E- It succeeds and 19c database instances connected to the ASM instance on HOST03 can be reconnected to the ASM instance on HOST01.
F- It fails because an ASM instance is not configured to run on HOST02.

Answer:

B, D, F

Question 8

Question Type: MultipleChoice

Examine this command and output:

```
[root@host01 ~]# /sbin/acfsutil snap create snap001 /u01/app/grid/acfsmount/

acfsutil snap create: Snapshot operation is complete.
```

Examine this command:

```
[root@host01 ~]# /sbin/acfsutil snap create -p snap001 snap002
/u01/app/grid/acfsmount/
```

Which statement must be true for the successful execution of the second command?

Options:

A- The disk group compatibility attribute for advm must be set to 12. l or higher.
B- The parent snapshot must be read-only.
C- The underlying advm volume must be configured with high redundancy.
D- The parent snapshot must be read/write.

Answer:

B

Question 9

Question Type: MultipleChoice

Which two statements are true about initialization parameters for Clustered ASM instances? (Choose two.)

Options:

A- The maximum value of ASM_POWER_LIMIT is 1024.
B- The default value of INSTANCE_TYPE is ASM.
C- A change to ASM_DISKSTRING requires a restart of all ASM instances for the change to take effect.
D- The ASM_DISKGOUPS parameter is optional.
E- ASM_POWER_LIMIT controls the number of RDBMS instances that can access a disk group while it is being rebalanced.

Answer:

B, D

Question 10

Question Type: MultipleChoice

Which three resources are managed using global concurrency control in an Oracle 19c RAC multi-instance database? (Choose three.)

Options:

A- Database block buffers
B- Mutexes
C- Redo log buffers
D- Latches
E- Enqueues
F- Cursors

Answer:

B, D, E

To Get Premium Files for 1Z0-078 Visit

https://www.p2pexams.com/products/1z0-078

For More Free Questions Visit

https://www.p2pexams.com/oracle/pdf/1z0-078

