Oracle 1Z0-133 Practice Questions

Shared by Woods on 10-11-2026

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Which three statements are true about the default behavior of WebLogic server proxy plug-ins?

Options:

A- The proxy will pin a client to a specific server if a session cookie is created.
B- The proxy fails over to another server if a connection or request times out.
C- The proxy distributes requests to cluster members based on their CPU usage.
D- The proxy dynamically learns the latest locations of cluster members.
E- The proxy always uses SSL, regardless of the client's protocol.
F- The proxy replicates session data to its backup proxy.

Answer:

A, B, D

Question 2

Question Type: MultipleChoice

You successfully deployed an application on WebLogic 12c but notice that its deployment name is different than what you expected.

After checking various places and making multiple deployment attempts, you decide to be on the safe side and just use the method that takes precedence over the others when setting the deployment name. Which method should you use to override the default deployment name?

Options:

A- Define the name in the library's manifest file
B- Configure the <module-name> element in web.xml
C- Run weblogic.Deployer with the --name option
D- Set a computed name based on the deployment source file
E- Set the element in application.xml

Answer:

E

Question 3

Question Type: MultipleChoice

Consider a cluster of four servers: ServerA, ServerB, ServerC, and ServerD.

The cluster hosts a web application and is accessed using a proxy plug-in. This web application is configured to use in-memory session replication.

A user is directed to ServerA. An HTTP session is established on ServerA and also replicated to ServerC, but ServerA subsequently fails. Which server will this user be redirected to?

Options:

A- ServerD
B- ServerB
C- none; the user will receive an error message
D- ServerC
E- any other available server

Answer:

D

Question 4

Question Type: MultipleChoice

You monitor a running JDBC data source with the console and note the following values:

Current Capacity = 10

Current Capacity High Count = 20

Identify two plausible explanations for these metrics. (Choose two.)

Options:

A- The workload was lower than it is now
B- The statement cache size is 20
C- The pool size has increased
D- The statement cache size is 10
E- The pool size has decreased
F- The workload was higher than it is now

Answer:

E, F

Question 5

Question Type: MultipleChoice

Which two statements are true when an Administration Server is compared to a Managed Server? (Choose two.)

Options:

A- An administration Server manages the domain configuration
B- A domain must have at least one of each type of server
C- An administration Server keeps a domain log, but a Managed Server does not
D- A Managed Server keeps a server log, but an Administration Server does not
E- Java EE applications are deployed only to a Managed Server

Answer:

C, D

Question 6

Question Type: MultipleChoice

Consider a multiple node domain. On the administration server's node, you edit setDomainEnv.sh in the bin directory and add a new JAR file to the CLASSPATH. You stop and restart all three WebLogic Server in the domain. Upon investigation, you discover that only applications deployed to one WebLogic Server are able to access the JAR file code. How do you explain this?

Options:

A- You must also set the domain attribute ''CLASSPATH Discovery Enabled.''
B- Each machine that hosts WebLogic Servers has its own domain directories. The script must be modified there as well.
C- Only the first server to receive the new configuration from the administration server gets the updated CLASSPATH

D- The CLASSPATH is not for application code. It is for interval WebLogic Server code. So, only applications deployed to the administrative server can access code through the CLASSPATH

Answer:

B

Question 7

Question Type: MultipleChoice

Which two statements are true about Log Filters? (Select two.)

Options:

A- You do not have to lock the configuration to create Log Filters
B- Log Filters are created at the domain level
C- The administration console assists in the creation of Log Filter expressions
D- You can apply a Log Filter to the server log, but not to standard out

Answer:

B, C

Question 8

Question Type: MultipleChoice

You are using the Configuration Wizard to create a new domain that will host an EJB application without a cluster. Remote EJB clients can therefore take advantage of WebLogic Server's load balancing and failover capabilities.

However, a proxy server exists between the EJB clients and this new cluster.

Which cluster attribute should you modify in the Configuration Wizard to ensure that external EJB clients are routed correctly through the proxy?

Options:

A- Messaging Mode
B- Cluster Address

C- Broadcast Channel
D- Replication Channel
E- Cluster Type

Answer:

B

Question 9

Question Type: MultipleChoice

While using the Configuration Wizard to create a new domain, you do not set the Listen Address for the administration server and accept the default value. What is the result?

Options:

A- Server startup fails
B- The server binds to localhost
C- The server prompts for an address when it is started the first time
D- The server attempts to bind to all network interfaces on the host OS

Answer:

B

Question 10

Question Type: MultipleChoice

Examine the partial server log entry shown below:

####

<> < > < > < 1369013281005 >

Which two statements are true?

Options:

A- The server's name is oracleDS1.

B- The server's machine name is host01.
C- The transaction ID is 001129.
D- The JDBC subsystem generated the message.
E- The user's identity is managed1.
F- The severity level of the message is Critical.

Answer:

B, D

Question 11

Question Type: MultipleChoice

Consider an application that comprises both web and EJB components.

What are two benefits of implementing a multitier cluster architecture over a single-tier(basic) cluster architecture? (Chose two.)

Options:

A- Dynamic clusters are only supported for the multitier architecture
B- Remote EJB access is blocked
C- Each cluster can be scaled independently
D- Future web clusters can share the same EJB tier
E- All servers can be managed (started/stopped) together

Answer:

D, E

Question 12

Question Type: MultipleChoice

The admin server's domain files were backed up by using the tar command on Linux. The admin server crashes and the domain files become corrupted. The domain files are restored from the backup. You try and start the admin server by using the usual domain start script. The script does not run. The error is ''permission denied''.

How should you troubleshoot this?

Options:

A- Check the ownership and file system permissions of the start script
B- Ensure you are currently logged in as a WebLogic Server administrator before running the script
C- Stop any running managed servers and then start the admin server
D- After the restoration of a domain, you must start the admin by using WLST
E- Be sure to start the admin server as the root user

Answer:

A

Question 13

Question Type: MultipleChoice

As part of troubleshooting an application, you need to analyze the HTTP session count and the server heap size over the past six hours. You are using the Administration console. You want to view both metrics together and correlate their values.

Which three steps should you take in the Administration console?

Options:

A- Create a custom view.
B- Start the JVM Runtime view.
C- Drag each metric onto two charts in the same view.
D- Access the Monitoring Dashboard.
E- Click the application's Monitoring tab.

Answer:

C, D, E

To Get Premium Files for 1Z0-133 Visit

https://www.p2pexams.com/products/1z0-133

For More Free Questions Visit

https://www.p2pexams.com/oracle/pdf/1z0-133

