Oracle 1Z0-134 Practice Questions

Shared by Mcdonald on 10-11-2026

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

You are reviewing the scheduled maintenance of your domain after adding a new cluster.

Which statement is true when configuring a migratable target within a WebLogic Server cluster? (Choose the best answer.)

Options:

A- Allow Post-Migration Script To Run On a Different Machine is selected by default.
B- The default server migration policy is Auto-Migrate Exactly-once Services.
C- The participating cluster should include at least one configured server.
D- An automatically migrated service will always be hosted on the specified User Preferred Server.

Answer:

D

Question 2

Question Type: MultipleChoice

What is the first action to take during a Rolling Update? (Choose the best answer.)

Options:

A- Change the Startup Mode to Development; Production Mode is not supported.
B- Remove all managed servers from any cluster and reassign them after the update.
C- Do a Force Shutdown of all the servers, including the Administration Server.
D- Back up your applications, database schema, other application data, and domains.
E- Stop all Node Managers that support the domain to be updated.

Answer:

D

Question 3

Question Type: MultipleChoice

You are designing an application that uses JMS transactions to coordinate a group of messages for production and consumption, treating messages sent or received as an atomic unit.

What are two ways you can use transactions in JMS? (Choose two.)

Options:

A- You create a JMS-transacted session if you are using only JMS in your transactions.
B- You set various levels of control over message acknowledgement.
C- Use message-driven beans if consumers are nondurable.
D- Use a JTA user-transactions in a non-transacted JMS session.

Answer:

A, D

Question 4

Question Type: MultipleChoice

A client application asynchronously receives the message sent to a JMS Queue. The client is going to send a response to the sender.

Which two JMS Header fields from the original message are used to send the response? (Choose two.)

Options:

A- JMSResponseMode
B- JMSTimeStamp
C- JMSDeliveryMode
D- JMSCorrelationID
E- JMSReplyTo

Answer:

D, E

Question 5

Question Type: MultipleChoice

Review this scenario of an application running on a storage-disabled, managed Coherence server that uses a Coherence two-tier near cache:

Cache data is already written to the distributed cache.

There is a local near cache configured on the application side (storage-disabled node).

Application requests the data from Coherence twice.

Assuming this is the server's first access of this data from the cache, how many network round trips between Coherence cluster instances take place in total? (Choose the best answer.)

Options:

A- 3
B- 4
C- 1
D- 2

Answer:

C

Question 6

Question Type: MultipleChoice

Which two objects can be considered potential clients of a Node Manager? (Choose two.)

Options:

A- an administration server
B- a WLST session
C- an HTTP server
D- any other Node Manager
E- a remote JMS client
F- the weblogic.Deployer utility

Answer:

A, B

Explanation:

A Node Manager client can be local or remote to the Node Managers with which it communicates. You access either version of Node Manager---the Java version or the script-based (SSH) version---from the following clients:

A: an administration server

B: WLST commands and scripts---WLST offline serves as a Node Manager command-line interface that can run in the absence of a running Administration Server.

P2P exams

Question 7

Question Type: MultipleChoice

You are analyzing the JMSDeliveryMode header field for all the messages for all the queues deployed to your JMSServer.

Which two values do you expect to find for this header? (Select two.)

Options:

A- PERSISTENT
B- NON_PERSISTENT
C- TRANSIENT
D- PERMANENT
E- MULTIMODE
F- EXACTLY_ONCE

P2P exams

Answer:

A, B

Explanation:

JMSDeliveryMode specifies PERSISTENT or NON_PERSISTENT messaging.

Question 8

Question Type: MultipleChoice

You are troubleshooting an issue with a WLS data source. However, your attempt to execute a manual test on the connection pool fails when you invoke the testPool() method on the corresponding JDBCDataSourceRuntimeMBean.

Which configuration condition would contribute to the failure of executing the test? (Choose the best answer.)

Options:

A- The TestTableName property is either not set or is set to an invalid SQL statement.
B- The TestFrequencySeconds property is set to a value greater than 0.
C- The TestReservedConnections property is enabled.
D- The ManualTestEnabled property is set to false.
E- The ConnectionReserveTimeoutSeconds property is set to a value other than -1.

Answer:

A

Explanation:

testPool tests the connection pool in the data source by reserving and releasing a connection from it.

TestTableName is the name of the database table to use when testing physical database connections. This name is required when you specify a Test Frequency and enable Test Reserved Connections, Test Created Connections, and Test Released Connections.

Question 9

Question Type: MultipleChoice

You are planning to use WebLogic JMS for implementing my enterprise messaging architecture. Which messaging paradigm is invalid in this context? (Select the best answer.)

Options:

A- Point to Point messaging
B- Publish Subscribe messaging
C- Datagram messaging
D- Persistent messaging

Answer:

C

Question 10

Question Type: MultipleChoice

You have been asked to assist developers with executing a partial redeployment of static files within a Java EE Web Application deployed to WebLogic Server. The Web Application has already been deployed as an exploded archive directory.

Which of the following represents the correct conditions for this to be successful? (Choose the best answer.)

Options:

A- The -redeploy argument is used when executing the weblogic.Deployer command.
B- The -distribute argument is used when executing the weblogic.Deployer command.
C- The -distribute argument is used when executing the weblogic.Deployer command and the domain must be in development mode.
D- The -redeploy argument is used when executing the weblogic.Deployer command and the domain must be in development mode.

Answer:

B

Question 11

Question Type: MultipleChoice

You are using the Domain Template Builder to create a new template using an existing domain as the source.

Which two directories are included by default? (Choose two.)

Options:

A- bin directory
B- lib directory
C- servers directory
D- common directory
E- logs directory
F- replication directory

Answer:

A, B

Explanation:

If you selected a domain as the source for your new template, then the bin and lib directories are included by default:

Question 12

Question Type: MultipleChoice

Which three tools allow you to create a Domain Template? (Choose three.)

Options:

A- JDeveloper
B- pack command
C- Smart Template Wizard
D- weblogic.Build
E- Domain Template Builder
F- WLST
G- Archive command

Answer:

B, E, F

To Get Premium Files for 1Z0-134 Visit

https://www.p2pexams.com/products/1z0-134

For More Free Questions Visit

https://www.p2pexams.com/oracle/pdf/1z0-134

