



**Free Questions for 830-01 by vceexamstest**

**Shared by Berg on 15-04-2024**

**For More Free Questions and Preparation Resources**

**Check the Links on Last Page**

## Question 1

---

**Question Type:** MultipleChoice

---

In a virtual-in-path deployment, when the Steelhead appliance exports data to a flow data collector:

### Options:

---

- A- All traffic has the LAN and WAN interface index.
- B- All traffic has the WAN interface index.
- C- All traffic has the LAN interface index.
- D- All traffic has the primary interface index.

### Answer:

---

B

## Question 2

---

**Question Type:** MultipleChoice

---

Authentication fails for certain users after configuring the Server-Side Steelhead Appliance to be a RODC. What could be the issue?

**Options:**

---

- A- These users make use of NTLM authentication.
- B- These users exclusively make use of Kerberos authentication.
- C- Overlapping open is enabled.
- D- SMB signing is required.

**Answer:**

---

B

## Question 3

---

**Question Type:** MultipleChoice

---

On Steelheads, by default tcpdump:

### Options:

---

- A- captures packets with an 802.1Q tag.
- B- does not capture packets with an 802.1Q tag
- C- does not capture packets with an 803.3Q tag.
- D- does not capture packets with an 802.11Q tag.

### Answer:

---

B

## Question 4

---

### Question Type: MultipleChoice

---

After completing the SRDF configuration on both Steelhead appliances and restarting the optimization service, the SRDF connections in the Current Connections report show a red protocol error icon in the Notes column. What could be a cause of this issue?

### Options:

---

- A- A SRDF protocol error can occur when attempting to optimize traffic originating from the LAN-side of the Steelhead appliance. Please check the LAN-side Symmetrix array for compatibility.

- B-** The red icon indicates that RiOS is optimizing the connection normally.
- C-** A SRDF protocol error can occur when attempting to optimize traffic originating from the WAN-side of the Steelhead appliance. Please check the WAN-side Symmetrix array for compatibility.
- D-** Symmetrix needs to be enabled on the EMC server.

**Answer:**

---

A

## Question 5

---

**Question Type:** MultipleChoice

---

Citrix remote applications, running on the server and to access printers and disk drives, are not performing well. What can you configure to improve the performance?

**Options:**

---

- A-** Enable Citrix CDMoptimization.
- B-** Enable SecureICAencryption.

**C-** Session Reliability (CGP) Port.

**D-** Enable Citrix Traffic Fallback Behavior.

**Answer:**

---

A

## Question 6

---

**Question Type: MultipleChoice**

---

Citrix optimization does not work although you removed ports 1494 and 2598 from the Interactive Ports label and enabled Citrix optimization on the client-side Steelhead appliance. What could be the problem? (Select 2)

**Options:**

---

**A-** You need to enable Citrix optimization on the server-side Steelhead appliance.

**B-** Secure ICA encryption needs to be enabled.

**C-** Citrix CDM optimization needs to be enabled.

**D-** You need to restart the optimization service.

**Answer:**

---

A, D

## Question 7

---

**Question Type: MultipleChoice**

---

What type of problem does the error message below indicate:

Sep 7 22:53:50 SH pm[18184]: [pm.NOTICE]: Output from sport:

/opt/rbt/bin/sport (pid 27529) received signal 12 (SIGUSR2) marking bit

**Options:**

---

- A-** It is not a problem. The message is displayed when a system dump is generated.
- B-** The management process crashed
- C-** The optimization process crashed
- D-** The management process received permission to apply QoS marking
- E-** The sport process received permission to apply QoS marking

**Answer:**

---

A



**To Get Premium Files for 830-01 Visit**

**<https://www.p2pexams.com/products/830-01>**

**For More Free Questions Visit**

**<https://www.p2pexams.com/riverbed/pdf/830-01>**

