



SolarWinds Hybrid-Cloud-Observability-Network-Monitoring Mock Exam

Shared by Yates on 17-06-2026

For More Free Questions and Preparation Resources

Check the Links on Last Page



Question 1

Question Type: MultipleChoice

Which two of the following best practices are used when creating a universal device poller (UDP)? (Select two.)

Options:

- A- Call SolarWinds support for object ID (OID) options.
- B- Consult vendor documentation for OID.
- C- Perform SNMPwalk to determine if OID exists.
- D- Run WBemtest to test communication to OID.

Answer:

B, C

Question 2

Question Type: MultipleChoice

Which tool can be used to display the physical layout of interfaces on graphical stencils?

Options:

- A- device studio
- B- device view
- C- NetPath
- D- network insight

Answer:

B

Question 3

Question Type: MultipleChoice

It is taking longer than normal for a single mission critical node to poll for dat

a. Where would the polling interval for the node be changed?

Options:

- A- Node Details Summary > Edit Node > Polling
- B- Node Details Summary > Resources > Memory
- C- Settings > All Setting > Core Thresholds
- D- Settings > All Settings > Polling Settings

Answer:

A

Question 4

Question Type: MultipleChoice

A NetPath probe is to be built to monitor the paths between two sites. No Windows servers are available to run the agent. Which two of the following options can be used to set up the probe? (Choose two.)

Options:

- A- Install the agent on a red hat Linux server.
- B- Install the agent on a Windows 10 computer.
- C- Run the probe from the hybrid cloud observability (HCO) server.
- D- Use the network device agent to run the probe from the router.

Answer:

B, C

Question 5

Question Type: MultipleChoice

A node is not able to calculate CPU load threshold. Where in SolarWinds' platform can a user confirm CPU load is included in the node status calculation?

Options:

- A- core thresholds
- B custom poller thresholds
- C- node status contributors
- D- polling settings

Answer:

C

Question 6

Question Type: MultipleChoice

Which two of the following authentication methods are supported when configuring a database log collection in hybrid cloud observability? (Choose two.)

Options:

- A- Kerberos
- B- mixed mode
- C- oAUTH
- D- Windows

Answer:

A, D

Question 7

Question Type: MultipleChoice

The status of the interfaces for a network switch shows as "unknown" in SolarWinds' platform web console, although the node status is "up". What could be the reason?

Options:

- A- hardware sensors are disabled on the node
- B- ICMP is blocked between the node and the polling engine

- C- interface details have changed on the device
- D- interfaces are not managed in hybrid cloud observability (HCO)

Answer:

C

Question 8

Question Type: MultipleChoice

Which three of the following technologies are supported to create device studio pollers? (Choose three.)

Options:

- A- multi-CPU / memory
- B- node details
- C- single CPU / memory
- D- VLAN details

Answer:

A, B, C

P2P
exams

P2P
exams

To Get Premium Files for Hybrid-Cloud-Observability-Network-Monitoring Visit

<https://www.p2pexams.com/products/hybrid-cloud-observability-network-monitoring>

For More Free Questions Visit

<https://www.p2pexams.com/solarwinds/pdf/hybrid-cloud-observability-network-monitoring>

20%
DISCOUNT

P2P
exams