



Free Questions for 1Z0-149 by vceexamstest

Shared by Terrell on 12-12-2023

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

Examine these statements issued by user SH which execute successfully:

```
CREATE OR REPLACE PACKAGE products_pkg AS
  TYPE PriceList IS TABLE OF NUMBER;
  PROCEDURE print_price (p_price PriceList);
END products_pkg;
/
```

```
CREATE OR REPLACE PACKAGE BODY products_pkg AS
  PROCEDURE print_price (p_price PriceList) IS
  BEGIN
    FOR i IN p_price.FIRST..p_price.LAST LOOP
      DBMS_OUTPUT.PUT_LINE(p_price(i));
    END LOOP;
  END;
END products_pkg;
/
```

```
DBMS_OUTPUT.PUT_LINE(p_price(i)); END LOOP; END; END products_pkg; /
```

Now, examine this anonymous block executed by SH:

```
1 DECLARE
2   TYPE PriceList IS TABLE OF NUMBER;
3   list1 products_pkg.PriceList := products_pkg.PriceList(500, 800, 1000);
4   list2 PriceList := PriceList(400, 600, 800);
5 BEGIN
6   products_pkg.print_price(list1);
7   products_pkg.print_price(list2);
8 END;
/
```

Which is true about the anonymous block?

Options:

- A- It will execute successfully only if PriceList is removed from the DECLARE section and defined as a standalone collection type.
- B- It will execute successfully only if PriceList is defined as an associative array in the package and anonymous block.
- C- It will fail at lines 6 and 7.
- D- It will fail only at line 7.

Answer:

D

Question 2

Question Type: MultipleChoice

Examine these statements from a block of code:

```
CURSOR c1 IS  
  SELECT * FROM products  
  FOR UPDATE OF price;
```

```
UPDATE products  
  SET price = price * 1.05  
  WHERE CURRENT OF c1;
```

Which two are true? (Choose two.)

Options:

- A- The lock acquired when executing the OPEN c1 command will be released only after a COMMIT or ROLLBACK statement is issued.
- B- Only the PRICE column can be updated in the PRODUCTS table.
- C- The FOR UPDATE OF clause can be used only if the WHERE CURRENT OF clause is used in the executable part of the block.
- D- The WHERE CURRENT OF clause can be used only if the FOR UPDATE clause is used in the cursor definition.
- E- An OPEN c1 command will acquire a lock only on the PRICE column in the PRODUCTS table.

Answer:

A, D

Question 3

Question Type: MultipleChoice

Which block of code displays the error message "Incorrect price value"?

A.

```
DECLARE
    price CONSTANT NUMBER(4) := 10000;
BEGIN
    NULL;
EXCEPTION
    WHEN VALUE_ERROR THEN
        DBMS_OUTPUT.PUT_LINE('Incorrect price value');
END;
/
```

B.

```
BEGIN
DECLARE
    price CONSTANT NUMBER(4) := 50000;
BEGIN
    NULL;
END;
EXCEPTION
    WHEN VALUE_ERROR THEN
        DBMS_OUTPUT.PUT_LINE('Incorrect price value');
END;
/
```

C.

```
BEGIN
DECLARE
    error_detected EXCEPTION;
    PRAGMA EXCEPTION_INIT(error_detected, -2001);
    price CONSTANT NUMBER(4) := 10000;
BEGIN
    NULL;
END;
EXCEPTION
    WHEN error_detected THEN
        DBMS_OUTPUT.PUT_LINE('Incorrect price value');
END;
/
```

D.


```
DECLARE
    price CONSTANT NUMBER(4) := 10000;
BEGIN
    NULL;
EXCEPTION
    WHEN OTHERS THEN
        DBMS_OUTPUT.PUT_LINE('Incorrect price value');
END;
/
```

Options:

A- Option A

B- Option B

C- Option C

D- Option D

Answer:

B

Question 4

Question Type: MultipleChoice

Examine this code:

```
BEGIN
  RAISE_APPLICATION_ERROR(-3167, 'User Error');
END;
/
```

What will be the outcome?

Options:

A- It will execute successfully and will display the user-defined error message.

B- It will result in an error as the range of the error code can only be from "-20000 to -20999."

C- It will result in an error as the range of the error code can only be from "-1000 to -2000."

D- It will result in an error as the range of the error code can only be from "-2000 to -2999."

Answer:

B

Question 5

Question Type: MultipleChoice

Which three are true regarding code based access control (CBAC)? (Choose three.)

Options:

A- In a multitenant environment, the DELEGATE option of CBAC cannot be used.

B- CBAC roles can be granted to a program unit only if they are directly granted to its owner.

C- CBAC roles can be granted to a program unit only if they are the predefined roles automatically defined by the standard scripts as part of database creation.

D- You can use CBAC to attach database roles to a PL/SQL function or procedure only.

- E-** In CBAC, the ADMIN and DELEGATE options cannot both be granted to the same user.
- F-** You can use CBAC to attach database roles to a PL/SQL function, procedure, or package.
- G-** CBAC cannot be used to secure definer's rights.

Answer:

B, E, F

Question 6

Question Type: MultipleChoice

Which two are true about lexical units? (Choose two.)

Options:

- A-** Character literals are case-sensitive.
- B-** Spaces can be embedded in delimiters.
- C-** Identifiers include labels.
- D-** A character literal with zero characters has the BOOLEAN value NULL.

E- All user-defined identifiers must start with an alphabet.

Answer:

A, E

Question 7

Question Type: MultipleChoice

Examine this statement which executes successfully:

```
SQL> SET SERVEROUTPUT ON;
```

Now, examine this code which is executed:

```
SQL> DECLARE
  2  v_hiredate DATE := '12-June-2020';
  3  v_location VARCHAR2(13);
  4  v_deptno NUMBER(2) NOT NULL;
  5  v_comm CONSTANT NUMBER := 5;
  6  BEGIN
  7  DBMS_OUTPUT.PUT_LINE ('Hire date ' ||v_hiredate);
  8  DBMS_OUTPUT.PUT_LINE ('Location ' ||v_location);
  9  DBMS_OUTPUT.PUT_LINE ('Department ');
 10  DBMS_OUTPUT.PUT_LINE ('Commission ' ||v_comm);
 11  END;
 12 /
```

What is true about the result?

Options:

A- It returns an error in line 2.

B- It returns an error in line 4.

C- It returns an error in line 9.

D- It executes and displays output.

Answer:

B

To Get Premium Files for 1Z0-149 Visit

<https://www.p2pexams.com/products/1z0-149>

For More Free Questions Visit

<https://www.p2pexams.com/oracle/pdf/1z0-149>

