



Free Questions for 300-620 by vceexamstest

Shared by Tillman on 20-10-2022

For More Free Questions and Preparation Resources

Check the Links on Last Page

Question 1

Question Type: MultipleChoice

A Cisco APIC is configured with RADIUS authentication as the default. The network administrator must ensure that users can access the APIC GUI with a local account if the RADIUS server is unreachable. Which action must be taken to accomplish this goal?

Options:

- A- Create an additional login domain that references local accounts
- B- Enable the fallback check with the default authentication domain
- C- Associate console authentication with the 'RADIUS' realm.
- D- Reference the local realm in the fallback domain

Answer:

D

Question 2

Question Type: MultipleChoice

An engineer must securely export Cisco APIC configuration snapshots to a secure, offsite location. The exported configuration must be transferred using an encrypted tunnel and encoded with a platform-agnostic data format that provides namespace support. Which configuration set must be used?

Policy: Import Policy
Protocol: TLS
Format: XML

Policy: Export Policy
Protocol: TLS
Format: JSON

Policy: Import Policy
Protocol: SCP
Format: JSON

Policy: Export Policy
Protocol: SCP
Format: XML

Options:

A- Option A

B- Option B

C- Option C

D- Option D

Answer:

D

Question 3

Question Type: MultipleChoice

What is MP-BGP used for in Cisco ACI fabric?

Options:

- A- MP-BGP VPNv4 AF is used to propagate L3Out routes that are received from a border leaf to the fabric.
- B- MP-BGP VPNv4 AF is used between spines in an ACI Multi-Pod fabric to propagate the endpoint
- C- MP-BGP VPNv4 AF is used as protocol on L3Out between a border leaf and an external router
- D- MP-BGP Layer 2 VPN EVPN AF is used to propagate L3Out routes that are received from a border leaf.

Answer:

A

Question 4

Question Type: MultipleChoice

Refer to the exhibit A customer must back up the current Cisco ACI configuration securely to the remote location using encryption and authentication. The backup job must run once per day The customer s security policy mandates that any sensitive information including passwords, must not be exported from the device Which set of steps meets these requirements?

- Export destination using FTP protocol.
Use XML format.
- Export destination using SCP protocol.
Disable Global AES Encryption.
- Export destination using SCP protocol.
Use XML format.
- Export destination using FTP protocol.
Disable Global AES Encryption.

Options:

- A-** Option A
- B-** Option B
- C-** Option C
- D-** Option D

Answer:

B

Question 5

Question Type: MultipleChoice

A network engineer must configure a Cisco ACI system to detect network loops for untagged and tagged traffic. The loop must be detected and stopped by disabling an interface within 4 seconds. Which configuration must be used?

Admin State: Disabled Enabled

Controls: Enable MCP PDU per VLAN

Key:

Confirm Key:

Loop Detect Multiplication Factor:

Loop Protection Action: Port Disable

Initial Delay (sec):

Transmission Frequency (sec): (msec):

Admin State: Disabled Enabled

Controls: Enable MCP PDU per VLAN

Key:

Confirm Key:

Loop Detect Multiplication Factor:

Loop Protection Action: Port Disable

Initial Delay (sec):

Transmission Frequency (sec): (msec):

Admin State: Disabled Enabled

Controls: Enable MCP PDU per VLAN

Key:

Confirm Key:

Loop Detect Multiplication Factor:

Loop Protection Action: Port Disable

Initial Delay (sec):

Transmission Frequency (sec): (msec):

Options:

A- Option A

B- Option B

C- Option C

Answer:

B

Question 6

Question Type: MultipleChoice

A network engineer is integrating a new Hyperflex storage cluster into an existing Cisco ACI fabric. The Hyperflex cluster must be managed by vCenter so a new vSphere Distributed switch must be created. In addition, the hardware discovery must be performed by a vendor-neutral discovery protocol. Which set of steps meets these requirements'?

- Configure an Interface Policy group, select CDP, and apply it to the desired interfaces.
Enter the vCenter IP and credentials in the Create vCenter Controller dialog box.
In the Create VMware VMM domain dialog box, select Read-Only Mode.
- Configure an Interface Policy group, select CDP, and apply it to the designated interfaces.
Create a VMware VMM domain, add it to the VLAN pool, and associate it to the designated interfaces.
Select Read Only Mode In the Create VMware VMM domain dialog box.
- Configure an Interface Policy group, select LLDP, and apply it to the selected interfaces.
Create a VLAN pool, add it to the VMware VMM domain, and include the appropriate interfaces.
Enter the vCenter IP and credentials in the Create vCenter Controller dialog box.
- Configure a Switch Policy group, select LLDP, and apply it to the indicated interfaces.
Set up a VMware VMM domain and apply it to the appropriate interfaces.
Enter the APIC management IP and credentials in the Create vCenter Controller dialog box.

Options:

- A- Option A
- B- Option B
- C- Option C
- D- Option D

Answer:

C

Question 7

Question Type: MultipleChoice

An engineer must connect a new host to port 1 '1 on Leaf 101. A Cisco ACI fabric has an MOP policy configured but experience excessive Layer 2 loops The engineer wants the Cisco ACI fabric to detect and prevent Layer 2 loops m the fabric Which set of actions accomplishes these goals'?

- Enable MCP globally.
Associate the MCP policy with an interface selector.
- Enable MCP globally.
Associate the MCP policy with an interface policy group.
- Enable MCP locally.
Associate the MCP policy with an interface policy group.
- Enable MCP locally.
Associate the MCP policy with an interface profile.

Options:

A- Option A

B- Option B

C- Option C

D- Option D

Answer:

B

Question 8

Question Type: MultipleChoice

What are two descriptions of ACI multi-site? (Choose two.)

Options:

A- The Inter-Site network routers should run OSPF to establish peering with the spines.

B- The Multi-Site orchestrator must be directly attached to one ACI leaf.

C- Routers in the inter-Site network must run OSPF, DHCP relay, and MP-BGP

D- ACI Multi-Site is a solution that allows one APIC cluster to manage multiple ACI sites

E- ACI Multi-Site is a solution that supports a dedicated APIC cluster per site

Answer:

A, E

Question 9

Question Type: MultipleChoice

What is the effect of enabling the disable Remote EP learn feature?

Options:

- A-** It disables remote IP endpoint learning on all leaf nodes in the fabric.
- B-** It disables remote IP endpoint learning on leaf switches that do not have L3Outs.
- C-** It limits learning of compute leaf endpoints on border leaves.
- D-** It prevents border leaf switches from receiving routes through peering with external routers.

Answer:

A

Explanation:

<https://unofficialaciguide.com/2018/11/29/aci-best-practice-configurations/>

To Get Premium Files for 300-620 Visit

<https://www.p2pexams.com/products/300-620>

For More Free Questions Visit

<https://www.p2pexams.com/cisco/pdf/300-620>

